

BARBAR TAB MANAGEMENT

CTRL , / .

PREV / NEXT BUFFER

cycle along the bar

CTRL p

PICK BY LETTER

a letter lands on every tab — type it, you're there. the fastest jump

SPC x

CLOSE

CTRL-c and SPC b c do the same

SPC b c

FORCE CLOSE

unsaved changes? capital C doesn't ask

SPC b o

CLOSE ALL OTHERS

declutter in one stroke

SPC b P

PIN THIS BUFFER

pinned tabs stick to the left with a pin icon

SPC b 0

CLOSE ALL BUT PINNED

pin your 2-3 working files, nuke the exploration debris

:BufferMoveNext

REORDER TABS

:BufferMovePrevious goes the other way — arrange by workflow

SPC SPC

TOO MANY TABS? FUZZY IT

the buffer picker beats scanning a crowded bar

GITSIGNS HUNKS

]c / **[c**

SPC **h** **p**

SPC **h** **s**

V ... **SPC** **hs**

SPC **h** **r**

SPC **h** **S** / **R**

SPC **h** **d**

SPC **h** **b**

SPC **t** **b** / **D**

NEXT / PREV HUNK

+ added ~ changed _ deleted — read the gutter

PREVIEW THE HUNK

inline diff popup — look before you act

STAGE HUNK

on a staged hunk it un-stages — it's a toggle

STAGE ONLY THESE LINES

visual-select part of a hunk first — line-level precision

RESET HUNK — DISCARD IT

works on a visual selection too · this one is destructive

STAGE / RESET WHOLE FILE

capitals go big

DIFF VS INDEX

side-by-side · **SPC h D** = diff vs last commit

BLAME THIS LINE, FULLY

commit, author, date, message in a float

TOGGLE BLAME / DELETED

b = inline blame everywhere · D = ghost the deleted lines

DAP-UI DEBUGGING

F7

OPEN / CLOSE THE COCKPIT

left: scopes · breakpoints · stacks · watches ·
bottom: repl · console

CR

EXPAND / COLLAPSE

drill into structs, maps, slices in the scopes tree

e

EDIT A VALUE, LIVE

change a variable mid-run and keep stepping — test the fix before writing it

r

SEND TO REPL

evaluate expressions against the paused program

o

JUMP TO SOURCE

on a stack frame — go where the code actually is

d

REMOVE

delete a watch or breakpoint from its pane

t

TOGGLE A BREAKPOINT

from inside the breakpoints pane — no need to visit the file

F5

F2

F1

F3

RUN · OVER · INTO · OUT

the driving keys still work while the UI is up

SPC

B

CONDITIONAL BREAKPOINT

break when `i == 4999`, not on every loop pass

UFO CODE FOLDING

zM

COLLAPSE EVERYTHING

an unfamiliar file becomes a table of contents of signatures

zR

OPEN EVERYTHING

zp

PEEK WITHOUT OPENING

floating preview of the folded body — glance and move on

za

TOGGLE THIS FOLD

zo opens · zc closes — treesitter decides the boundaries

zr / zm

ONE LEVEL AT A TIME

reduce / more folding — sink deeper into nesting gradually

zj / zk

HOP FOLD TO FOLD

function-to-function travel while collapsed

zv

REVEAL THE CURSOR

after a search lands inside a fold — open just enough to see it

[z /]z

START / END OF THIS FOLD

where does this function begin and end?

zM → zj → zp

THE SKIM LOOP

collapse all, hop between functions, peek the interesting ones

WHICH-KEY MENU

SPC *wait...*

keep typing

BS

ESC

SPC **s** **k**

g / **z** / **]**

' / **"**

desc = "..."

THE MENU APPEARS

you set delay = 0 — it's instant, use it shamelessly

DRILL INTO A GROUP

SPC h shows every hunk action with its description

BACK UP ONE LEVEL

wrong group? backspace, not escape

BAIL OUT ENTIRELY

SEARCH KEYMAPS INSTEAD

know what you want but not where it lives? fuzzy-
find the description

WORKS ON THOSE TOO

pause after g, z, [or] — the menu covers every
prefix, not just SPC

MARKS & REGISTERS TOO

pause after ' to see your marks, after " to see register
contents

FEED IT WHEN YOU MAP

every keymap you add with a desc shows up in the
menu and in SPC s k