

MOVE FASTER

w / **b**

HOP A WORD FORWARD / BACK

e = end of word · stop mashing llll

f *char*

JUMP TO THAT CHAR ON THE LINE

; = next match , = back · t stops just before it

0 / **\$**

START / END OF LINE

^ = first non-blank character

{ / **}**

BLOCK UP / BLOCK DOWN

jumps by paragraph — fast vertical travel

CTRL **d** / **u**

HALF-PAGE DOWN / UP

cursor stays centered-ish — smooth scroll is on

12 **j**

LEAP 12 LINES DOWN

the relative numbers in the gutter ARE the count — read, type, land

gg / **G**

TOP / BOTTOM OF FILE

SEARCH WORD UNDER CURSOR

n = next hit N = previous · # searches backwards

/ *text*

SEARCH ANYTHING

n / N to walk hits · ESC clears the highlight

JUMP THROUGH CODE

g r d

GO TO DEFINITION

CTRL t

JUMP BACK

CTRL-o = back anywhere CTRL-i = forward again

g r r

EVERY REFERENCE

CTRL-ENTER in the list = open in vertical split

g r i

**GO TO
IMPLEMENTATION**

g r t = type definition

g 0

**EVERY SYMBOL IN THIS
FILE**

jump straight to any function — no scrolling

g W

**EVERY SYMBOL IN THE
PROJECT**

K

DOCS UNDER CURSOR

zM / zR

FOLD ALL / UNFOLD ALL

fold first, skim the skeleton · za = toggle one zp = peek inside

FIND ANYTHING

SPC **F**

FIND FILE BY NAME

SPC **G**

GREP THE WHOLE PROJECT

live ripgrep — pattern is a regex

SPC **SPC**

OPEN BUFFERS

SPC **/**

FUZZY SEARCH THIS FILE

SPC **s** **w**

GREP WORD UNDER CURSOR

SPC **e**

FILE TREE SIDEBAR

q closes it · tree is for orienting — pickers are for going

SPC **s** **r**

RESUME LAST PICKER

SPC s . = recent files

SPC **s** **k**

SEARCH EVERY KEYMAP

forgot a binding? never leave the editor

CTRL **q**

RESULTS → QUICKFIX LIST

inside any picker · then :cnext or :cfd to operate on all of them

EDIT AT THE SPEED OF THOUGHT

c i "

CHANGE INSIDE QUOTES

works from anywhere on the line

c i a

CHANGE THIS ARGUMENT

a = argument in any function call

d a)

DELETE AROUND PARENS

i = inside · a = around · also b " ' { [

y a f

YANK FUNCTION CALL

c i n q = change inside NEXT quotes

s a iw "

WRAP WORD IN QUOTES

visual: s a) wraps the selection

s r " '

SWAP " FOR '

s d " deletes the surround entirely

⌘ /

TOGGLE COMMENT

normal, visual, and insert mode

⌘ S

SAVE — ANY MODE

save also auto-formats

.

REPEAT LAST EDIT

* then n . n . = hand-guided refactor

FIX WHAT'S BROKEN

gre / **grE**

NEXT / PREV DIAGNOSTIC

hop squiggle to squiggle

SPC **c** **a**

CODE ACTION — THE FIX MENU

auto-import, quick-fix, refactor suggestions

g **r** **n**

RENAME SYMBOL EVERYWHERE

semantic, cross-file — always try this before find & replace

SPC **s** **d**

ALL PROJECT DIAGNOSTICS

the damage report after a big refactor

SPC **f**

FORMAT NOW

js/ts formats only when an eslint config exists — that's by design

SPC **S** **r**

SPECTRE: FIND & REPLACE

project-wide with per-match approval · t f = literal (non-regex) mode

:cfd **%s/old/new/ge** | **update**

EDIT EVERY QUICKFIX FILE

grep → CTRL-q → this = surgical mass edit

GIT WITHOUT LEAVING

]c / **[c**

NEXT / PREV CHANGE

walk your uncommitted hunks

SPC **h** **s**

STAGE THIS HUNK

works on a visual selection too · **SPC h S** stages the file

SPC **h** **r**

DISCARD THIS HUNK

surgical undo — kill the debris, keep the commit clean

SPC **h** **p**

PREVIEW HUNK DIFF

SPC **h** **b**

BLAME THIS LINE

SPC t b = blame every line, inline, always on

SPC **g** **g**

LAZYGIT

commit, push, branch, rebase — full TUI in a float

SPC **g** **e**

GIT STATUS IN SIDEBAR

SPC **g** **o** **b**

OPEN LINE ON GITHUB

visual-select first to link a range — instant share link

DEBUG, NOT PRINTLN

SPC **b**

TOGGLE BREAKPOINT

press, then PAUSE — typing another key makes it a buffer command

SPC **B**

CONDITIONAL BREAKPOINT

prompts for the condition — break only when it matters

F5

RUN / CONTINUE

F2

STEP OVER

F1

STEP INTO

F3

STEP OUT

F7

TOGGLE DEBUG UI

also shows the last session's output · UI auto-opens on start

BUFFERS · SPLITS · TERMINAL

CTRL **,** **/** **.**

PREV / NEXT BUFFER

CTRL **p**

**PICK BUFFER BY
LETTER**

letters appear on each tab — faster than cycling past
4 buffers

SPC **x**

CLOSE BUFFER

CTRL-c does it too

SPC **b** **o**

CLOSE ALL OTHERS

type it fast — pausing after SPC b drops a breakpoint

SPC **b** **P**

PIN BUFFER

then SPC b O closes everything except pinned

CTRL **h j k l**

HOP BETWEEN SPLITS

CTRL **/**

TOGGLE TERMINAL

session survives hiding — leave the test watcher
running in it

ESC **ESC**

LEAVE TERMINAL MODE

back to normal mode so you can scroll and yank
output

FILES ARE JUST TEXT

-

OPEN FOLDER AS A BUFFER

oil — the directory becomes editable text

edit name + :w

RENAME

use real vim editing: visual block, :s, macros — mass rename ten files

new line + :w

CREATE FILE

end the name with / to make a directory

dd + :w

DELETE — GOES TO TRASH

not permanent, you configured that

dd ... p + :w

MOVE FILE

delete the line here, paste it in another oil buffer, write

CTRL s

OPEN IN SPLIT

CTRL-t = tab CTRL-p = preview

g.

TOGGLE HIDDEN FILES

g?

ALL OIL KEYS

SPC r p / SPC r P copy the path under the cursor

SPACE IS THE COMMAND CENTER

SPC *wait...*

SPC **s** *...*

SPC **g** *...*

SPC **h** *...*

SPC **b** *...*

SPC **t** *...*

SPC **s** *...*

SPC **r** *...*

SPC **c** **a**

THE WHOLE MENU APPEARS

which-key, zero delay — this poster is a backup, that menu is the truth

SEARCH

f files · g grep · k keymaps · d diagnostics · h help · . recent

GIT

g lazygit · e status sidebar · l log · o b open on github

HUNKS

s stage · r reset · p preview · b blame · S stage whole file

BUFFERS

c close · o close others · P pin — pause here = breakpoint instead!

TOGGLES

l relative numbers · h inlay hints · b line blame

SPECTRE

r toggle panel · w search word under cursor

UTILS

p copy relative path · P absolute path · t terminal

CODE ACTION

the one non-prefix you use constantly

FILE OPS IN THE SIDEBAR

SPC **e**

a

r

d

c / **m**

y ... **p**

h / **l**

H / **I**

]g / **]d**

OPEN THE EXPLORER

these keys work while the tree is focused · q closes it

NEW FILE

end with / to create a folder

RENAME

DELETE

COPY / MOVE

YANK FILES, PASTE ELSEWHERE

works on multiple selected files

CLOSE / OPEN NODE

BACKSPACE = up a directory · Z collapses everything

SHOW HIDDEN / IGNORED

NEXT GIT CHANGE / DIAGNOSTIC

[goes back · jump straight to dirty or broken files in the tree

COMPLETION, NO MOUSE

ENTER

ACCEPT — AUTO-IMPORTS TOO

picking an unimported symbol adds the import line for you

TAB / ↑TAB

NEXT / PREV SUGGESTION

CTRL-n / CTRL-p work too

CTRL SPC

OPEN MENU / SHOW DOCS

press once for the menu, again for documentation

CTRL e

DISMISS THE MENU

get it out of the way, keep typing

CTRL k

SIGNATURE HELP

also pops automatically while you type call arguments

sources

LSP · PATHS · SNIPPETS

blink.cmp — file paths complete inside strings

WHAT HAPPENS ON SAVE

:W / **⌘S**

GO

LUA

C / C++

JS / TS

SPC **f**

:ConformInfo

always

SAVE = AUTO-FORMAT

conform.nvim runs the right formatter, 500ms budget

GOIMPORTS + GOFUMPT

imports add and remove themselves — never touch them by hand

STYLUA

CLANG-FORMAT

ESLINT_D — IF CONFIG EXISTS

nearest eslint config above the file wins (monorepo-aware) — no config, no formatting, ON PURPOSE

FORMAT RIGHT NOW

works on a visual selection too

WHO FORMATS THIS BUFFER?

the answer when "why didn't it format"

INDENT IS AUTO-DETECTED

guess-indent matches each file's existing style — don't fight it

TOGGLES & LITTLE WINS

SPC **t** **h**

SPC **t** **b**

SPC **t** **l**

SPC **r** **p**

v ... **p**

:s/old/new

ESC

SPC **-**

SPC **q**

INLAY HINTS

parameter names + inferred types rendered in your code (great in go)

INLINE BLAME, EVERY LINE

SPC t D = show deleted lines inline

RELATIVE NUMBERS ON/OFF

COPY FILE PATH

relative · SPC r P = absolute · works in oil too

PASTE KEEPS YOUR YANK

paste over a selection as many times as you want — your remap

LIVE PREVIEW AS YOU TYPE

a split shows every match changing before you hit enter

CLEAR SEARCH HIGHLIGHT

OIL IN A FLOATING WINDOW

file manager without giving up your layout

DIAGNOSTICS → LIST

everything wrong with this buffer, walkable

START UP & STAY HEALTHY

f **g** **r**

ON THE START SCREEN

f find file · g grep · r recent · c your config · L lazy · q quit

:Lazy

PLUGIN MANAGER

S sync · U update · X clean · P profile slow startups

:Mason

LSP / FORMATTER INSTALLS

gopls, ts_ls, rust-analyzer, pyright, clangd & friends live here

:LspInfo

WHAT'S ATTACHED HERE?

first stop when completions or gotos go quiet

:checkhealth

FULL SYSTEM DIAGNOSIS

run it whenever anything feels haunted

SPC **s** **n**

EDIT YOUR OWN CONFIG

fuzzy-find your nvim config files from anywhere

:Neotree

OLD TREE, STILL AROUND

installed but unbound — snacks explorer replaced it

OIL: THE FULL MANUAL

-

OPEN PARENT AS TEXT

SPC - = floating window · press - again to keep going up

edit + **:w**

RENAME · CREATE · DELETE · MOVE

edit names, add lines, dd lines — one :w commits the whole batch

CR / **CTRL** **p**

OPEN / PREVIEW

CTRL **s** **h** **t**

VSPLIT / HSPLIT / TAB

one modifier, three destinations

- / **`**

JUMP TO CWD / CD HERE

~ = cd for this tab only

g

BROWSE THE TRASH

your deletes go to trash, not oblivion — restore by moving back

gs / **gx**

SORT / OPEN IN FINDER

g.

TOGGLE HIDDEN FILES

SPC **r** **p**

COPY PATH UNDER CURSOR

r P = absolute · q closes · CTRL-r refreshes

INSIDE ANY PICKER

just type

CR

CTRL v s t

TAB

CTRL q

CTRL g

OPT r h i

/

?

FILTER LIVE

works in files, grep, buffers, keymaps — every picker in your sidebar

OPEN

SHIFT-CR = pick which window it opens in

VSPLIT / SPLIT / TAB

SELECT MULTIPLE

tab marks item and moves on · CTRL-a selects everything

EVERYTHING → QUICKFIX

selection if you made one, else all results

LIVE GREP ↔ FUZZY REFINE

grep first, flip to fuzzy to narrow the results you already have

REGEX · HIDDEN · IGNORED

toggles while you search

HOP INPUT ↔ LIST

in the list: j k gg G move, q quits

EVERY PICKER KEY

the built-in version of this poster

SPECTRE: REPLACE EVERYWHERE

SPC **S** **r**

TAB / **↑TAB**

dd

CR

SPC **r** **c**

SPC **R**

SPC **q**

tf

SPC **l**

OPEN THE PANEL

SPC S w = pre-filled with the word under cursor

SEARCH ↔ REPLACE FIELDS

type the pattern, tab down, type the replacement — results update live

DROP A MATCH FROM THE BATCH

exclude the false positives before you pull the trigger

JUMP TO THAT FILE

REPLACE JUST THIS ONE

REPLACE ALL

everything still in the list — after your dd pruning

MATCHES → QUICKFIX

LITERAL MODE — YOUR KEY

search has . () \$ in it? flip this · ti = ignore case th = hidden files

RESUME LAST SEARCH

LAZYGIT IN 9 KEYS

SPC **g** **g**

OPEN

q quits back to nvim · ESC backs out of anything

1 ... **5**

SWITCH PANELS

status · files · branches · commits · stash

SPACE

STAGE / UNSTAGE FILE

a = stage everything

CR

DRILL INTO THE FILE

then SPACE stages individual lines — surgical commits

c

COMMIT

A

AMEND LAST COMMIT

staged changes get folded into it

P / **p**

PUSH / PULL

n

NEW BRANCH

in the branches panel · SPACE checks out the highlighted one

z / **?**

UNDO / ALL KEYBINDINGS

z reverts the last lazygit action — yes, really

TEXT OBJECTS, COMPLETE

i / **a**

q

b

f

a

t

n / **l**

v **a)** **a)**

sa **sd** **sr**

INSIDE / AROUND

every object below pairs with c, d, y, v — that's the whole grammar

ANY QUOTE

" ' or backtick — whichever is closest · ciq just works

ANY BRACKET

([{ — whichever is closest · dab eats the nearest pair

FUNCTION CALL

daf deletes name(args...) entirely

ARGUMENT

cia rewrites one arg, daa removes it AND its comma

HTML / JSX TAG

cit = change tag contents

NEXT / LAST OBJECT

cinq = change in NEXT quotes — cursor doesn't have to be there yet

REPEAT TO GROW OUTWARD

each a) expands the selection to the next enclosing pair

SURROUND: ADD · DELETE · REPLACE

saiw" wraps word · sd" strips · sr"" swaps · visual + sa) wraps selection

THE REFACTOR MENU

SPC **c** **a**

v ... **SPC** **c** **a**

GO

TS

ESLINT

RUST

g **r** **n**

gre → **SPC** **ca**

SPC **s** **d**

"WHAT CAN YOU DO HERE?"

on a squiggle = fixes · on clean code = refactors

SELECT FIRST = EXTRACT

select lines, then code action — extract function / variable

FILL STRUCT · INVERT IF

gopls — on an empty struct literal it fills every field

ADD ALL MISSING IMPORTS

also: move to new file, remove unused, organize imports

FIX ALL AUTO-FIXABLE

one action clears every eslint complaint in the file

FILL MATCH · IMPL MEMBERS

rust-analyzer has the deepest menu — check every squiggle

RENAME — SAFEST REFACTOR

semantic, cross-file — never regex-rename an identifier

THE REPAIR LOOP

next diagnostic, fix, repeat until clean

THE REFACTOR WORKLIST

every diagnostic in the project, one list

THE TAB BAR

CTRL , / .

PREV / NEXT BUFFER

cycle along the bar

CTRL p

PICK BY LETTER

a letter lands on every tab — type it, you're there. the fastest jump

SPC x

CLOSE

CTRL-c and SPC b c do the same

SPC b c

FORCE CLOSE

unsaved changes? capital C doesn't ask

SPC b o

CLOSE ALL OTHERS

declutter in one stroke

SPC b P

PIN THIS BUFFER

pinned tabs stick to the left with a pin icon

SPC b 0

CLOSE ALL BUT PINNED

pin your 2-3 working files, nuke the exploration debris

:BufferMoveNext

REORDER TABS

:BufferMovePrevious goes the other way — arrange by workflow

SPC SPC

TOO MANY TABS? FUZZY IT

the buffer picker beats scanning a crowded bar

GITSIGNS: EVERY HUNK KEY

]c / **[c**

SPC **h** **p**

SPC **h** **s**

V ... **SPC** **hs**

SPC **h** **r**

SPC **h** **S** / **R**

SPC **h** **d**

SPC **h** **b**

SPC **t** **b** / **D**

NEXT / PREV HUNK

+ added ~ changed _ deleted — read the gutter

PREVIEW THE HUNK

inline diff popup — look before you act

STAGE HUNK

on a staged hunk it un-stages — it's a toggle

STAGE ONLY THESE LINES

visual-select part of a hunk first — line-level precision

RESET HUNK — DISCARD IT

works on a visual selection too · this one is destructive

STAGE / RESET WHOLE FILE

capitals go big

DIFF VS INDEX

side-by-side · SPC h D = diff vs last commit

BLAME THIS LINE, FULLY

commit, author, date, message in a float

TOGGLE BLAME / DELETED

b = inline blame everywhere · D = ghost the deleted lines

INSIDE THE DEBUG UI

F7

OPEN / CLOSE THE COCKPIT

left: scopes · breakpoints · stacks · watches ·
bottom: repl · console

CR

EXPAND / COLLAPSE

drill into structs, maps, slices in the scopes tree

e

EDIT A VALUE, LIVE

change a variable mid-run and keep stepping — test the fix before writing it

r

SEND TO REPL

evaluate expressions against the paused program

o

JUMP TO SOURCE

on a stack frame — go where the code actually is

d

REMOVE

delete a watch or breakpoint from its pane

t

TOGGLE A BREAKPOINT

from inside the breakpoints pane — no need to visit the file

F5

F2

F1

F3

RUN · OVER · INTO · OUT

the driving keys still work while the UI is up

SPC

B

CONDITIONAL BREAKPOINT

break when `i == 4999`, not on every loop pass

FOLDING IS SKIMMING

zM

zR

zp

za

zr / **zm**

zj / **zk**

zv

[z / **]z**

zM → **zj** → **zp**

COLLAPSE EVERYTHING

an unfamiliar file becomes a table of contents of signatures

OPEN EVERYTHING

PEEK WITHOUT OPENING

floating preview of the folded body — glance and move on

TOGGLE THIS FOLD

zo opens · zc closes — treesitter decides the boundaries

ONE LEVEL AT A TIME

reduce / more folding — sink deeper into nesting gradually

HOP FOLD TO FOLD

function-to-function travel while collapsed

REVEAL THE CURSOR

after a search lands inside a fold — open just enough to see it

START / END OF THIS FOLD

where does this function begin and end?

THE SKIM LOOP

collapse all, hop between functions, peek the interesting ones

YOU CAN'T FORGET A KEY

SPC *wait...*

keep typing

BS

ESC

SPC **s** **k**

g / **z** / **]**

' / **"**

desc = "..."

THE MENU APPEARS

you set delay = 0 — it's instant, use it shamelessly

DRILL INTO A GROUP

SPC h shows every hunk action with its description

BACK UP ONE LEVEL

wrong group? backspace, not escape

BAIL OUT ENTIRELY

SEARCH KEYMAPS INSTEAD

know what you want but not where it lives? fuzzy-find the description

WORKS ON THOSE TOO

pause after g, z, [or] — the menu covers every prefix, not just SPC

MARKS & REGISTERS TOO

pause after ' to see your marks, after " to see register contents

FEED IT WHEN YOU MAP

every keymap you add with a desc shows up in the menu and in SPC s k

READ THE DIFF FIRST

SPC **h** **d**

THIS FILE VS INDEX

side-by-side vim diff — what have I changed since staging?

SPC **h** **D**

VS LAST COMMIT

everything since HEAD, staged or not

]c / **[c**

HOP CHANGE TO CHANGE

same keys inside diff view and in a normal buffer

do

TAKE THE OTHER SIDE

diff-obtain: pull their version of this change into your buffer

dp

PUSH YOURS ACROSS

diff-put: send your version to the other window

:diffoff!

DONE COMPARING

or just close the other window

SPC **h** **p**

QUICK PEEK INSTEAD

inline hunk popup when a full split is overkill

SPC **g** **e**

ALL CHANGED FILES

git status in the sidebar — your review checklist

nvim -d a b

DIFF ANY TWO FILES

or :vert difffsplit other_file from inside a buffer

STAGE LIKE A SURGEON

]c

SPC h p

SPC h s

V ... SPC hs

SPC h r

SPC h u

SPC g e

SPC gg → c

result

1 · WALK TO A HUNK

start at the top of the file, visit every change

2 · LOOK AT IT

does this belong in the commit you're building?

3 · YES → STAGE IT

3½ · ONLY THESE LINES

select part of a hunk — debug print and real fix in one hunk? split them

DEBRIS → DISCARD

stray prints, commented experiments — gone before they embarrass you

OOPS → UN-STAGE

staged the wrong hunk? toggle it back out

REPEAT PER FILE

the git-status sidebar is your worklist across the repo

COMMIT WHAT'S STAGED

lazygit shows exactly what's going in — no surprises

COMMITMENTS THAT REVIEW THEMSELVES

one idea per commit — reviewers and future-you both win

REWRITE HISTORY SAFELY

SPC **gg** → **4**

s / **f**

r

e

d

CTRL **j** / **k**

↑C ... **↑V**

3 → **r** / **M**

z

GO TO THE COMMITS PANEL

everything below happens there — before you push

SQUASH / FIXUP DOWN

merge a "typo fix" commit into the real one below it — f discards its message

REWORD THE MESSAGE

works on any unpushed commit, not just the last

EDIT — STOP THE REBASE HERE

amend files into an older commit, then continue

DROP A COMMIT

delete it from history entirely

MOVE A COMMIT UP / DOWN

reorder history by just... moving it

CHERRY-PICK

copy commits here, paste them on another branch

REBASE ONTO / MERGE IN

branches panel: rebase your branch onto the highlighted one, or merge it into yours

UNDO THE LAST ACTION

lazygit tracks its own undo via reflog — experiment bravely

REWRITE BEFORE PUSH, NEVER AFTER

IT'S ALL INTERACTIVE REBASE UNDERNEATH

CONFLICTS, CALMLY



CONFLICTS SHOW IN RED

the files panel marks every conflicted file



OPEN THE CONFLICT VIEW

each conflict shown as competing hunks



PICK THE HIGHLIGHTED SIDE

arrow keys move between ours / theirs and between conflicts



KEEP BOTH

when the two changes don't actually collide



IT OFFERS TO CONTINUE

resolve the final conflict and lazygit asks to continue the merge / rebase



ABORT · SKIP · CONTINUE

mid-rebase options menu — abort is always available, nothing is ruined



OR FIX BY HAND IN NVIM

search the markers, keep the lines you want, delete the rest + all three markers



NOTHING IS EVER LOST

every state you've been in is still reachable — worst case, reset to the reflog entry

GIT AT THE PROMPT

gst

gd

/

gdca

ga

/

gaa

gcmmsg

"..."

gco

/

gcb

gpc

/

glc

gsta

/

gstp

gll

git-clean-branches

STATUS

oh-my-zsh git plugin — you have all of these already

DIFF / DIFF STAGED

gdca answers "what exactly am I about to commit?"

ADD / ADD ALL

prefer hunk staging in nvim — gaa is for the rare all-in commit

COMMIT WITH MESSAGE

CHECKOUT / NEW BRANCH

PUSH / PULL THIS BRANCH

your functions — gpc sets upstream on a brand-new branch automatically

STASH / STASH POP

park changes, switch context, get them back

THE PRETTY GRAPH

your alias — all branches, decorated, relative dates

DELETE MERGED BRANCHES

your function — keeps main/master/dev, sweeps the rest

WHY DOES THIS CODE EXIST?

SPC **h** **b**

BLAME THIS LINE

commit, author, date, full message — the "why" is in the message

SPC **t** **b**

BLAME AS YOU BROWSE

inline blame on every line you visit — leave it on while exploring

SPC **g** **L**

THIS FILE'S WHOLE LIFE

lazygit log scoped to the current file — capital L

SPC **g** **l**

REPO HISTORY

enter on any commit to browse the files it touched

gll

SEE THE BRANCH SHAPE

your graph alias — where did this branch diverge?

`git log -S "needle"`

WHEN WAS THIS ADDED?

the pickaxe — finds commits that added or removed that exact string

`git log -L 10,25:f.go`

HISTORY OF THESE LINES

every change ever made to lines 10-25 of that file

SPC **g** **o** **b**

SHARE THE EVIDENCE

visual-select the lines, get a github permalink