

MOVE FASTER

w / **b**

HOP A WORD FORWARD / BACK

e = end of word · stop mashing llll

f *char*

JUMP TO THAT CHAR ON THE LINE

; = next match , = back · t stops just before it

0 / **\$**

START / END OF LINE

^ = first non-blank character

{ / **}**

BLOCK UP / BLOCK DOWN

jumps by paragraph — fast vertical travel

CTRL **d** / **u**

HALF-PAGE DOWN / UP

cursor stays centered-ish — smooth scroll is on

12 **j**

LEAP 12 LINES DOWN

the relative numbers in the gutter ARE the count — read, type, land

gg / **G**

TOP / BOTTOM OF FILE

SEARCH WORD UNDER CURSOR

n = next hit N = previous · # searches backwards

/ *text*

SEARCH ANYTHING

n / N to walk hits · ESC clears the highlight

JUMP THROUGH CODE

g r d

GO TO DEFINITION

CTRL t

JUMP BACK

CTRL-o = back anywhere CTRL-i = forward again

g r r

EVERY REFERENCE

CTRL-ENTER in the list = open in vertical split

g r i

**GO TO
IMPLEMENTATION**

g r t = type definition

g 0

**EVERY SYMBOL IN THIS
FILE**

jump straight to any function — no scrolling

g W

**EVERY SYMBOL IN THE
PROJECT**

K

DOCS UNDER CURSOR

zM / zR

FOLD ALL / UNFOLD ALL

fold first, skim the skeleton · za = toggle one zp = peek inside

FIND ANYTHING

SPC **F**

FIND FILE BY NAME

SPC **G**

GREP THE WHOLE PROJECT

live ripgrep — pattern is a regex

SPC **SPC**

OPEN BUFFERS

SPC **/**

FUZZY SEARCH THIS FILE

SPC **s** **w**

GREP WORD UNDER CURSOR

SPC **e**

FILE TREE SIDEBAR

q closes it · tree is for orienting — pickers are for going

SPC **s** **r**

RESUME LAST PICKER

SPC s . = recent files

SPC **s** **k**

SEARCH EVERY KEYMAP

forgot a binding? never leave the editor

CTRL **q**

RESULTS → QUICKFIX LIST

inside any picker · then :cnext or :cfd to operate on all of them

EDIT AT THE SPEED OF THOUGHT

c i "

CHANGE INSIDE QUOTES

works from anywhere on the line

c i a

CHANGE THIS ARGUMENT

a = argument in any function call

d a)

DELETE AROUND PARENS

i = inside · a = around · also b " ' { [

y a f

YANK FUNCTION CALL

c i n q = change inside NEXT quotes

s a iw "

WRAP WORD IN QUOTES

visual: s a) wraps the selection

s r " '

SWAP " FOR '

s d " deletes the surround entirely

⌘ /

TOGGLE COMMENT

normal, visual, and insert mode

⌘ S

SAVE — ANY MODE

save also auto-formats

.

REPEAT LAST EDIT

* then n . n . = hand-guided refactor

FIX WHAT'S BROKEN

gre / **grE**

NEXT / PREV DIAGNOSTIC

hop squiggle to squiggle

SPC **c** **a**

CODE ACTION — THE FIX MENU

auto-import, quick-fix, refactor suggestions

g **r** **n**

RENAME SYMBOL EVERYWHERE

semantic, cross-file — always try this before find & replace

SPC **s** **d**

ALL PROJECT DIAGNOSTICS

the damage report after a big refactor

SPC **f**

FORMAT NOW

js/ts formats only when an eslint config exists — that's by design

SPC **S** **r**

SPECTRE: FIND & REPLACE

project-wide with per-match approval · t f = literal (non-regex) mode

:cfd **%s/old/new/ge** | **update**

EDIT EVERY QUICKFIX FILE

grep → CTRL-q → this = surgical mass edit

GIT WITHOUT LEAVING

]c / **[c**

NEXT / PREV CHANGE

walk your uncommitted hunks

SPC **h** **s**

STAGE THIS HUNK

works on a visual selection too · **SPC h S** stages the file

SPC **h** **r**

DISCARD THIS HUNK

surgical undo — kill the debris, keep the commit clean

SPC **h** **p**

PREVIEW HUNK DIFF

SPC **h** **b**

BLAME THIS LINE

SPC t b = blame every line, inline, always on

SPC **g** **g**

LAZYGIT

commit, push, branch, rebase — full TUI in a float

SPC **g** **e**

GIT STATUS IN SIDEBAR

SPC **g** **o** **b**

OPEN LINE ON GITHUB

visual-select first to link a range — instant share link

DEBUG, NOT PRINTLN

SPC **b**

TOGGLE BREAKPOINT

press, then PAUSE — typing another key makes it a buffer command

SPC **B**

CONDITIONAL BREAKPOINT

prompts for the condition — break only when it matters

F5

RUN / CONTINUE

F2

STEP OVER

F1

STEP INTO

F3

STEP OUT

F7

TOGGLE DEBUG UI

also shows the last session's output · UI auto-opens on start

BUFFERS · SPLITS · TERMINAL

CTRL **,** **/** **.**

PREV / NEXT BUFFER

CTRL **p**

**PICK BUFFER BY
LETTER**

letters appear on each tab — faster than cycling past 4 buffers

SPC **x**

CLOSE BUFFER

CTRL-c does it too

SPC **b** **o**

CLOSE ALL OTHERS

type it fast — pausing after SPC b drops a breakpoint

SPC **b** **P**

PIN BUFFER

then SPC b O closes everything except pinned

CTRL **h j k l**

HOP BETWEEN SPLITS

CTRL **/**

TOGGLE TERMINAL

session survives hiding — leave the test watcher running in it

ESC **ESC**

LEAVE TERMINAL MODE

back to normal mode so you can scroll and yank output

FILES ARE JUST TEXT

-

OPEN FOLDER AS A BUFFER

oil — the directory becomes editable text

edit name + :w

RENAME

use real vim editing: visual block, :s, macros — mass rename ten files

new line + :w

CREATE FILE

end the name with / to make a directory

dd + :w

DELETE — GOES TO TRASH

not permanent, you configured that

dd ... p + :w

MOVE FILE

delete the line here, paste it in another oil buffer, write

CTRL s

OPEN IN SPLIT

CTRL-t = tab CTRL-p = preview

g.

TOGGLE HIDDEN FILES

g?

ALL OIL KEYS

SPC r p / SPC r P copy the path under the cursor