

```
#include <iostream> using namespace std;
```

```
int partition(int arr[], int low, int high) {  
    int pivot = arr[high];  
    int i = low - 1;  
  
    for (int j = low; j < high; j++) {  
        if (arr[j] < pivot) {  
            i++;  
            int temp = arr[i];  
            arr[i] = arr[j];  
            arr[j] = temp;  
        }  
    }  
  
    int temp = arr[i + 1];  
    arr[i + 1] = arr[high];  
    arr[high] = temp;  
  
    return i + 1; }  
  
void quickSort(int arr[], int low, int high) {  
    if (low < high) {  
        int pi = partition(arr, low, high);  
        quickSort(arr, low, pi - 1);  
        quickSort(arr, pi + 1, high);  
    } }  
  
int main() {  
    int arr[] = { 10, 7, 8, 9, 1, 5 };  
    int n = sizeof(arr) / sizeof(arr[0]);  
  
    cout << "Original array: ";  
    for (int i = 0; i < n; i++) {  
        cout << arr[i] << " ";  
    }  
    cout << endl;  
  
    quickSort(arr, 0, n - 1);  
  
    cout << "Sorted array: ";  
    for (int i = 0; i < n; i++) {  
        cout << arr[i] << " ";  
    }  
    cout << endl;  
  
    return 0; }
```