razorbox

README · GITHUB.COM/RAFU1987/RAZORBOX

Lightweight, dependency-free Vanilla JS lightbox with classic gallery controls. Supports images, galleries, videos (HTML5, YouTube, Vimeo), inline HTML, iframes, Google Maps, and PDFs. Includes smooth crossfade/slide transitions, captions **below** the content, thumbnails, zoom (trackpad pinch, mouse wheel, touch), slideshow, fullscreen, keyboard and touch navigation, and dark/light themes.

CSS is distributed separately; JavaScript never injects a stylesheet. The backdrop fades smoothly on opening; the native scrollbar is hidden without replacing it, and returns after the closing animation finishes.

Live demo

Installation

razorbox is in alpha. Until 1.0, every release is published under `latest`.

```
yarn add @rafu1987/razorbox
# or
npm install @rafu1987/razorbox
```

The package is ESM-only and ships TypeScript declarations.

Distribution files

The package contains both versions, with CSS always separate from JS:

- `dist/razorbox.js` and `dist/razorbox.css`: readable
- `dist/razorbox.min.js` and `dist/razorbox.min.css`: minified
- `src/scss/razorbox.scss`: SCSS source, exported as `@rafu1987/razorbox/scss`

The usual imports will be optimized by your application build:

```
import razorbox from '@rafu1987/razorbox'
import '@rafu1987/razorbox/css'
```

If you need the pre-minified assets explicitly:

```
import razorbox from '@rafu1987/razorbox/min'
import '@rafu1987/razorbox/css/min'
```

Usage

```
import razorbox from '@rafu1987/razorbox'
import '@rafu1987/razorbox/css'

const lightbox = razorbox.bind('[data-razorbox]', {
  transition: 'fade', // or 'slide'
  thumbnails: true,
  theme: 'dark',      // 'light' or 'auto'
  locale: 'auto'      // checks <html lang>, then browser language
})
```

`bind()` delegates clicks from the document, so links added later work without re-binding.

Images and galleries

Links sharing the same `data-razorbox` value form a gallery. Captions appear **below the image** (not on top of it), inside the lightbox viewport.

```
<a href="/images/01.jpg" data-razorbox="gallery" data-caption="First picture">
  <img src="/images/01-thumb.jpg" alt="Landscape">
</a>
<a href="/images/02.jpg" data-razorbox="gallery" data-caption="Second picture">
  <img src="/images/02-thumb.jpg" alt="Coast">
</a>
```

HTML5 video, YouTube and Vimeo

```
<a href="/media/demo.mp4" data-razorbox data-type="video" data-poster="/media/poster.jpg">HTML5
video</a>
<a href="https://www.youtube.com/watch?v=lPYHfdapsEY" data-razorbox>YouTube</a>
<a href="https://vimeo.com/253905163" data-razorbox>Vimeo</a>
```

Autoplay is requested by default (with `videoMuted: false`), but browsers may block autoplay with sound. When that happens (often on iOS), Vimeo starts muted by itself and, with `videoMutedFallback: true` (default), YouTube is started muted too instead of showing its play button. A "Turn on sound" button (label key `unmute`) is then shown over the video; one tap enables sound. Videos stop when the slide changes or the lightbox closes. `videoPrivacy: true` uses `youtube-nocookie.com` and Vimeo's `dnt=1` option. These do not replace consent management for third-party content.

Inline HTML and iframes

```
<a href="#my-content" data-razorbox data-type="html">Open content</a>
<div id="my-content" hidden><h2>Hello!</h2><p>Inline content.</p></div>

<a href="/embedded-page.html" data-razorbox data-type="iframe">Open iframe</a>
```

For programmatically supplied trusted HTML, use `lightbox.open([{ type: 'html', html: '<p>Hello</p>' }])` on a bound instance. Existing inline elements are restored when closed.

Google Maps and PDFs

```
<a href="https://www.google.com/maps/search/?api=1&amp;query=Empire+State+Building" data-
razorbox>Google Map</a>
<a href="/files/brochure.pdf" data-razorbox>PDF preview</a>
```

Maps support embed URLs or `mapApiKey` for the official Maps Embed API; ordinary Maps links use a compatibility embed and include an external Google Maps link. PDFs use the browser's native viewer with an open-in-new-tab fallback. Third-party iframes may require consent and appropriate CSP settings.

Opening programmatically

```
lightbox.open([
  '/images/01.jpg',
  { src: '/media/demo.mp4', poster: '/media/poster.jpg', caption: 'Clip' },
  { type: 'html', html: '<h2>Trusted markup</h2>' }
], 1)
```

`open()` returns `false` when none of the items is valid (for example a `javascript:` iframe URL).

API reference

Options

OPTION	DEFAULT	DESCRIPTION
`selector`	`'[data-razorbox]'`	Trigger selector when passing options as the first constructor argument.
`root`	`document`	Element, document or shadow root that trigger clicks are delegated from.
`loop`	`true`	Wrap from the last item to the first and back.
`thumbnails`	`true`	Enable the thumbnail rail and its toolbar button.
`thumbsOpen`	`false`	Show the thumbnail rail when opening.
`slideshow`	`true`	Enable the slideshow button.

OPTION	DEFAULT	DESCRIPTION
`autoplay`	`false`	Start the slideshow on open (image galleries only).
`slideshowInterval`	`3500`	Slideshow delay in milliseconds.
`zoom`	`true`	Enable image zoom and pan.
`zoomFactor`	`2`	Magnification of the toolbar zoom button. Clicking again returns to fit.
`maxZoom`	`8`	Maximum zoom from wheel, trackpad pinch and touch gestures.
`wheelZoom`	`true`	Zoom with the mouse wheel and Mac trackpad pinch.
`fullscreen`	`true`	Enable the fullscreen button.
`keyboard`	`true`	Enable keyboard shortcuts.
`closeOnBackdrop`	`true`	Close when clicking outside the content.
`captionHtml`	`false`	Render captions as HTML. Only use with trusted captions.
`preload`	`1`	Number of neighboring images to preload in each direction.
`transition`	`'fade'`	`'fade'` or `'slide'`.
`transitionDuration`	`300`	Content transition in milliseconds (0 to 2000).
`videoAutoplay`	`true`	Start videos when their slide opens.
`videoMuted`	`false`	Start videos muted.
`videoMutedFallback`	`true`	If audible YouTube autoplay is blocked, start muted instead of showing the play button.
`videoPrivacy`	`true`	Use `youtube-nocookie.com` and Vimeo `dnt=1`.
`mapApiKey`	`''`	Google Maps Embed API key. Prefer a referrer-restricted key.
`theme`	`'dark'`	`'dark'`, `'light'` or `'auto'` (follows `prefers-color-scheme`).
`locale`	`'auto'`	`'auto'`, `'en'`, `'de'` or `'fr'`.
`l10n`	`null`	Overrides for individual labels, for example `{ close: 'Close viewer' }`.
`onOpen`	`null`	Called after opening. See Events.
`onChange`	`null`	Called after the current item changes.
`onClose`	`null`	Called after the closing animation.

Data attributes

ATTRIBUTE	DESCRIPTION
`data-razorbox`	Marks a trigger. Triggers with the same value form a gallery.
`data-src`	Content URL, if it differs from `href`.

ATTRIBUTE	DESCRIPTION
`data-type`	`image`, `video`, `youtube`, `vimeo`, `html`, `iframe`, `map` or `pdf`. Detected from the URL when omitted.
`data-caption`	Caption shown below the content.
`data-alt`	Alternative text. Defaults to the `alt` of the trigger's `<img>`.
`data-thumb`	Thumbnail URL. Defaults to the trigger's `<img>`.
`data-poster`	Poster image for HTML5 videos.
`data-embed-src`	Google Maps `/maps/embed` URL to use instead of the compatibility embed.

Methods

METHOD	DESCRIPTION
`razorbox.bind(selector?, options?)`	Creates an instance and starts listening for trigger clicks.
`open(items, startIndex = 0)`	Opens an array of items or URLs. Returns `false` if none is valid.
`close(immediate = false)`	Closes the lightbox, skipping the animation when `immediate` is `true`.
`next()`, `prev()`, `goTo(index)`	Navigate between items.
`play()`, `pause()`, `togglePlay()`	Control the slideshow.
`toggleZoom()`	Zoom to `zoomFactor`, or back to fit.
`toggleThumbnails()`	Show or hide the thumbnail rail.
`toggleFullscreen()`	Enter or leave fullscreen. Returns a promise.
`destroy()`	Closes the lightbox, removes its DOM and stops listening.

Properties

PROPERTY	DESCRIPTION
`isOpen`, `isPlaying`	Current state.
`index`, `items`	Current index and a copy of the normalized items.
`locale`	Resolved locale, for example `'de'`.
`options`	The merged options. Changes apply the next time the lightbox opens.
`razorbox.activeInstance`	The instance that is currently open, or `null`.

Events

`onOpen`, `onChange` and `onClose` receive one object:

```
razorbox.bind('[data-razorbox]', {
  onChange ({ instance, index, item, length }) {
    console.log(`${index + 1} of ${length}: ${item.type} ${item.src}`)
  }
})
```

Keyboard

KEY	ACTION
← →	Previous and next item
Esc	Close
Tab	Moves focus between controls; focus stays inside the lightbox
Space	Play or pause the slideshow
T	Show or hide thumbnails
Z	Toggle zoom
F	Toggle fullscreen

Localization

English, German and French are bundled, with automatic detection via `<html lang>` (useful for TYPO3), then the browser languages. Override with `locale: 'de'` or `locale: 'fr'`, and change individual labels with `l10n`. Labels may use the placeholders `{number}`, `{total}`, `{type}` and `{alt}`. All keys are listed in `src/i18n.js`.

Theming

Use `theme: 'dark'`, `'light'` or `'auto'`, and override `--rb-*` custom properties on `.razorbox` for colors and sizes:

```
.razorbox {
  --rb-background: #0b0b0f;
  --rb-focus-color: #ffcc00;
  --rb-button-size: 48px;
  --rb-thumbnails-height: 96px;
}
```

Available properties: `--rb-background`, `--rb-text-color`, `--rb-caption-color`, `--rb-icon-color`, `--rb-focus-color`, `--rb-toolbar-background`, `--rb-toolbar-hover`, `--rb-toolbar-inset`, `--rb-button-size`, `--rb-arrow-background`, `--rb-arrow-hover`, `--rb-counter-background`, `--rb-media-background`, `--rb-html-background`, `--rb-html-color`, `--rb-thumbnails-background`, `--rb-thumbnails-height`, `--rb-thumb-background`, `--rb-thumb-border`, `--rb-backdrop-duration`, `--rb-transition`.

Image zoom

Use the mouse wheel over an image or pinch on a MacBook trackpad (Chromium/Firefox and Safari gestures). Zoom centers on the pointer, up to `maxZoom`. The toolbar Zoom button magnifies to `zoomFactor`, and a second click, including after a deep pinch, returns the image to fit. Drag the image to pan; two-finger touch pinch is supported. Set `wheelZoom: false` to disable desktop wheel and trackpad zoom. Browser and OS gesture behavior can vary.

Accessibility

The lightbox is a labelled modal dialog (`role="dialog"`, `aria-modal="true"`). Opening moves focus to the close button, `Tab` is kept inside the dialog, and closing returns focus to the trigger. Every control has a localized label, slide changes are announced through a polite live region, and the thumbnail toggle exposes `aria-expanded` and `aria-controls`. CI runs axe-core (WCAG 2.2 AA and best-practice rules) against image, video, HTML and iframe slides in both themes.

Development

```
yarn install
yarn dev            # demo page with hot reload
yarn build          # dist/ (commit it; CI checks it is current)
yarn release:check  # lint, unit, package, browser and accessibility tests
```

See CONTRIBUTING.md for the project layout and all scripts.

Releasing

Releases are cut locally with np and published by GitHub Actions with npm provenance.

1. Make sure `main` is clean and up to date.
2. Run `yarn release` and choose the version.
3. np runs `release:check`, then the `version` script writes the new `CHANGELOG.md` section and rebuilds `dist/`. np commits `Release vX.Y.Z`, tags and pushes.
4. The tag triggers the Release workflow. It runs CI, publishes to npm under `latest`, and creates the GitHub release from the changelog section.

The changelog section is generated from the commit subjects since the last tag, grouped by prefix: `[!!!]` (breaking), `[SECURITY]`, `[FEATURE]`, `[BUGFIX]`, `[TASK]` and `[DOCS]`. Release and merge commits are skipped. To write the notes yourself instead, add a `## X.Y.Z` section to `CHANGELOG.md` before releasing and the script leaves it alone.

Security

Please report vulnerabilities privately. See SECURITY.md.

License

MIT.