

Contents

1	Installation	3
1.1	Full Installation	3
1.2	Local Installation	3
2	Initialization	3
3	Widgets	4
3.1	Button	5
3.2	Text	5
3.3	Textbox	6
3.4	Entry	6
3.5	Dropdown	6
3.6	Droptype	7
3.7	Label	7
3.8	Check	8
3.9	Multiplechoice	8
3.10	Image	8
3.11	Menu	8
3.12	Tabs	9
3.13	Frame	9
3.14	Slider	9
3.15	Progressbar	10
3.16	Scroll	10
3.17	Listbox	10
3.18	Spinbox	11
3.19	Separator	11
4	Functions	11
4.1	Import_Theme	12
4.2	Getfonts	12
4.3	Style	12
4.4	Themes	13
4.5	Error	13
4.6	Info	13
4.7	Warning	13
4.8	Ask	14
4.9	Askstring	14
4.10	Askcolor	14
4.11	Stringvar	14
4.12	Intvar	15
4.13	Booleanvar	15
4.14	Seticon	15
4.15	Getdir	15
4.16	Openfile	16

4.17	Savefile	16
4.18	Sizablefalse	16
4.19	Sizabletrue	17
4.20	Show	17
4.21	Gettheme	17
4.22	Getgeo	17

Easytk Docs

Rafugafu

Note: You can always combine easytk with normal tkinter.

Note: These are the Easytk docs, not the tkinter and ttkbootstrap docs. Anything of tkinter or ttkbootstrap will not be explained. You can find the tkinter docs [here](#) and the ttkbootstrap docs [here](#).

Note: Most of the examples are not full code. They usually need to be preceded by `import {modules used}` ; `root = easytk.win()` and succeeded by `root.show()`

1 Installation

1.1 Full Installation

First, download the [easytk.py](#) file from the Easytk GitHub.

Next, install ttkbootstrap using `pip install ttkbootstrap`.

Now, any Python programs in your home directory will be able to use easytk.

1.2 Local Installation

If you don't want to install it for your entire home directory or are packaging it with an application, just copy the `easytk.py` file to your application's folder. Then, only the Python programs inside that folder will be able to use easytk. You will still have to install ttkbootstrap for easytk to work.

2 Initialization

To make a window, use

```
import easytk
root = easytk.win()
```

This is equivalent to

```
import ttkbootstrap as ttk
root = ttk.Window()
```

To show the window at the end, you can use `root.show()` instead of `root.mainloop()`.

If you want to make a subwindow (toplevel) of an already existing window `root`, use `subwin = root.subwin()` instead. Then you can use the `subwin` normally.

3 Widgets

These are all the widgets:

- button
- text
- textbox
- entry
- dropdown
- droptype
- label
- check
- multiplechoice
- image
- menu
- tabs
- frame
- slider
- progressbar
- scroll
- listbox
- spinbox
- separator

Note: Some of these widgets have the same name as different ones in normal tkinter and ttkbootstrap. Do not get confused.

The widgets are part of the window class itself, so use `w = root.{widget}({args})`, not `w = easytk.{widget}({args})`. You also do not need to specify the master. If you want to put the widget inside a frame inside the window, you can specify the master to be the frame.

Example:

```
frame = root.frame()
w = root.{widget}(master = frame, {args})
```

Then you can `grid`, `pack`, or `place` it normally.

You can treat any widget, once made, exactly like a normal tkinter or ttkbootstrap widget.

Example:

```
b = root.button(text = 'Click Me!',
command = lambda: b.config(state = 'disabled'))
b.grid()
```

Now here are specifications and examples for each one:

3.1 Button

Use `b = root.button({args})` to make a button in a window called `root`.

Example:

```
b = root.button(text = 'Click Me!')
b.grid()
```

There are two extra args: `image` and `imsize`. If you want to put an image in the button, you can use the `image` and `imsize` args like this:

`b = root.button(image = 'abc.png')`. Using the `imsize` arg is not necessary. The default is (10, 10).

Example:

```
b = root.button(image = 'abc.png', imsize = (10, 10))
b.grid()
```

Note: The higher the values given to the `imsize`, the smaller the image becomes.

3.2 Text

Use `t = root.text({args})` to write some text in a window called `root`.

Example:

```
t = root.text(text = 'Hello!')
t.grid()
```

There are two extra args: `image` and `imsize`. If you want to put an image in the text, you can use the `image` and `imsize` args like this:

`t = root.text(image = 'abc.png')`. Using the `imsize` arg is not necessary. The default is (10, 10).

Example:

```
t = root.text(image = 'abc.png', imsize = (10, 10))
t.grid()
```

Note: The higher the values given to the `imsize`, the smaller the image becomes.

3.3 Textbox

Use `tb = root.textbox({args})` to make a textbox in a window called `root`.

Example:

```
tb = root.textbox(wrap = 'word')
tb.grid()
```

The only extra arg is `scrolled`. If it is set to `False`, it will create a normal `tkinter.Text`. If it is set to `True`, it will create a `ttkbootstrap.scrolled.ScrolledText`. By default, it is set to `False`.

Example:

```
tb = root.textbox(scrolled = True)
tb.grid()
```

3.4 Entry

Use `e = root.entry({args})` to make an entry widget in a window called `root`.

Example:

```
e = root.entry()
e.grid()
```

The args are the same as normal `tkinter` and `ttkbootstrap`.

3.5 Dropdown

Use `d = root.dropdown({args})` to make a dropdown in a window called `root`.

Example:

```
s = root.stringvar()
d = root.dropdown(options = ['Option 1', 'Option 2', 'Option 3'],
stringvar = s, showdefault = 'Option 1')
d.grid()
```

There are a few differences in the args: `showdefault` and `options`. The `showdefault` option sets the default text to be displayed on the dropdown before you change it. It does not need to be part of the options. The `options` arg takes a `list` or a `tuple` and sets the possible options in the dropdown menu.

Example:

```
s = root.stringvar()
d = root.dropdown(options = ['Option 1', 'Option 2', 'Option 3'],
stringvar = s, showdefault = 'Click Me!')
d.grid()
```

3.6 Droptype

Use `d = root.droptype({args})` to make a droptype in a window called `root`.

Example:

```
d = root.droptype(options = [1, 2, 3])
d.grid()
```

There is one extra arg: `command`. The `command` option triggers a given function when the value of the droptype is changed, *only by clicking*. If you change it with the keyboard, the function will not be called.

Example:

```
d = root.droptype(options = [1, 2, 3], command = lambda: print(d.get()))
d.grid()
```

3.7 Label

This is actually not a widget in normal tkinter. This is a label that pops up when you hover your mouse over the widget it is attached to.

Use `root.label({widget}, {text}, {args})` to attach a label to the given widget.

Example:

```
b = root.button(text = 'Click Me!')
root.label(b, 'This is a button.')
b.grid()
```

The args are: `color`, `border`, and `master`.

The `color` arg sets the color of the label when it shows. The default is light yellow. It can be in any format tkinter recognizes.

The `border` arg sets how the border looks. It can be either of (`flat`, `raised`, `sunken`, `groove`, `ridge`). The default is `raised`.

The `master` arg sets the window it will appear in. It is very important to set it to be the same as the widget you are attaching it to.

Example:

```
f = root.frame()
b = root.button(master = f, text = 'Click Me!')
root.label(b, 'This is a button.', color = 'blue',
border = 'sunken', master = f)
f.grid()
b.grid()
```

Note: If you copy this code, the frame will only be big enough for the button. You will manually have to expand the frame to leave enough space for the label.

3.8 Check

Use `c = root.check({args})` to make a checkbox in a window called `root`.

Example:

```
b = root.booleanvar()
c = root.check(text = 'Click Me!', variable = b,
command = lambda: print(b.get()))
c.grid()
```

The args are the same as normal tkinter and ttkbootstrap.

3.9 Multiplechoice

Use `m = root.multiplechoice({args})` to make a multiplechoice option in a window called `root`.

Example:

```
v = root.stringvar()
root.multiplechoice(text = 'Option 1', var = v,
command = lambda: print(v.get(), 'is selected')).grid()
root.multiplechoice(text = 'Option 2', var = v,
command = lambda: print(v.get(), 'is selected')).grid()
```

There are a few differences in the args from normal tkinter: `variable` is renamed to `var`, and the `value` option does not exist. The `value` is automatically set to the `text`. The rest of the args are the same.

3.10 Image

This is actually not a widget in normal tkinter. This is an image that you can put anywhere in a window.

Use `i = root.image({args})` to make an image in a window called `root`.

Example:

```
root.image(image = 'abc.png', imsize = (1, 1)).grid()
```

The args are: `image`, and `imsize`. The `image` arg specifies the filename of the image. The `imsize` arg is not necessary.

Note: The higher the values given to the `imsize`, the smaller the image becomes.

3.11 Menu

Use `m = root.menu({args})` to make a menu in a window called `root`.

Example:


```

m = root.menu()
a = root.menu(m)
m.add_cascade(menu = a, label = 'Menu A')
a.add_command(label = 'Hello!', command = None)
root.config(menu = m)

```

The args are the same as normal tkinter and ttkbootstrap.

3.12 Tabs

Use `tabs = root.tabs({args})` to make a menu in a window called `root`.

Example:

```

tabs = root.tabs()
t1 = root.frame(tabs)
t2 = root.frame(tabs)
root.text(master = t1, text = 'Tab 1.').grid()
root.text(master = t2, text = 'Tab 2.').grid()
tabs.add(t1, text = 'Tab 1')
tabs.add(t2, text = 'Tab 2')
tabs.grid()

```

The args are the same as normal tkinter and ttkbootstrap.

3.13 Frame

Use `f = root.frame({args})` to make a frame in a window called `root`.

Example:

```

f = root.frame({args})
root.button(master = f, text = 'Click Me!').grid()
f.grid()

```

The only extra arg is `scrolled`. If it is set to `False`, it will create a normal `ttkbootstrap.Frame`. If it is set to `True`, it will create a `ttkbootstrap.scrolled.ScrolledFrame`. By default, it is set to `False`.

Example:

```

f = root.frame(scrolled = True)
for i in range(15):
    root.button(master = f, text = f'Button {i}').grid(column = 0, row = i)
f.grid()

```

3.14 Slider

Use `s = root.slider({args})` to make a slider in a window called `root`.

Example:

```

val = root.text(text = 'Value: 0')
val.grid()
s = root.slider(range_ = (0, 100),
command = lambda v: val.config(text = f'Value: {round(float(v))}'))
s.grid()

```

There are a few differences in the args: `from_` and `to` has become `range_`. The `range_` arg takes a `list` or a `tuple` in the form `(n_1, n_2)` and creates a slider ranged from `n_1` to `n_2`. The rest of the args are the same.

3.15 Progressbar

Use `p = root.progressbar({args})` to make a progressbar in a window called `root`.

Example:

```

def setp(val):
    p['value'] = val

p = root.progressbar(length = 100)
p.grid()
s = root.slider(range_ = (0, 100), command = setp)
s.grid()

```

The args are the same as normal tkinter and ttkbootstrap.

3.16 Scroll

Use `s = root.scroll({args})` to make a scrollbar in a window called `root`.

Example:

```

s = root.scroll()
s.pack(side = 'right', fill = 'y')
l = root.listbox(contents = [f'Item {i}' for i in range(1, 26)]),
yscrollcommand = s.set
l.pack(side = 'left', fill = 'both')
s.config(command = l.yview)

```

The args are the same as normal tkinter and ttkbootstrap.

3.17 Listbox

Use `l = root.listbox({args})` to make a listbox in a window called `root`.

Example:

```

l = root.listbox(contents = [f'Item {i}' for i in range(1, 26)])
l.grid()

```

There is one extra arg: `contents`. This takes a `list` or a `tuple` and makes a listbox with the given contents already made.

3.18 Spinbox

Use `s = root.spinbox({args})` to make a spinbox in a window called `root`.

Example:

```
s = root.spinbox(range_ = (0, 100))
s.grid()
```

There are a few differences in the args: `from_` and `to` has become `range_`. The `range_` arg takes a `list` or a `tuple` in the form `(n_1, n_2)` and creates a spinbox ranged from `n_1` to `n_2`. The rest of the args are the same.

3.19 Separator

Use `s = root.separator({args})` to make a separator in a window called `root`.

Example:

```
s = root.separator()
s.grid()
```

There is one difference in the args: `orient` has become `way`.

Example:

```
s = root.separator(way = 'vertical')
s.grid()
```

4 Functions

These are all the extra or modified functions in `easytk`:

- `import_theme`
- `getfonts`
- `style`
- `themes`
- `error`
- `info`
- `warning`
- `ask`
- `askstring`

- askcolor
- stringvar
- intvar
- booleanvar
- seticon
- getdir
- openfile
- savefile
- sizablefalse
- sizabletrue
- show
- gettheme
- getgeo

Now here are specifications and examples for each one:

4.1 Import__Theme

Use `root.import_theme(path)` to import a `ttkbootstrap` theme made using the TTK Creator. Then, you can use it normally using `root.style`.

Example:

```
root.import_theme('custom_theme.json')
root.style('custom_theme')
```

4.2 Getfonts

Use `root.getfonts()` to get a list of all the installed fonts that can be used with the [widgets](#).

Example:

```
root.text(text = 'The installed fonts are:').grid()
root.listbox(contents = root.getfonts()).grid()
```

4.3 Style

The `style` function can be used to set a theme, or return a `ttkbootstrap.Style` object. It takes two args: `style`, and `master`. If the `master` arg is not given, it will be set to the window you are calling the function with.

Example:

`root.style(style = 'clam')` will set the theme of the window to `clam`.

Note: The `style` function can use the themes from `ttkbootstrap` as well.

4.4 Themes

Use `root.themes()` to get a list of all the usable themes.

Example:

```
root.text(text = 'Theme:').grid(column = 0, row = 0)
s = root.stringvar()
root.dropdown(options = root.themes(), stringvar = s,
showdefault = root.gettheme(),
command = lambda x: root.style(x)).grid(column = 1, row = 0)
```

The `themes` function also returns themes from `ttkbootstrap`.

4.5 Error

Use `root.error({args})` to show an error message from a window called `root`.

Example:

```
root.error(title = 'Error!', message = 'There was an error:\n{error}')
```

The args are: title and message.

Note: This is equivalent to

`from tkinter import messagebox as mb; mb.showerror({args})`, but with a style.

4.6 Info

Use `root.info({args})` to show an info dialogue box from a window called `root`.

Example:

```
root.info(title = 'Info!', message = 'Finished process successfully!')
```

The args are title and message.

Note: This is equivalent to

`from tkinter import messagebox as mb; mb.showinfo({args})`, but with a style.

4.7 Warning

Use `root.warning({args})` to show a warning message from a window called `root`.

Example:

```
root.warning(title = 'Warning!', message = 'Warning:\n{warning}.')
```

The args are title and message.

Note: This is equivalent to

`from tkinter import messagebox as mb; mb.showwarning({args})`, but with a style.

4.8 Ask

Use `root.ask({args})` to show a dialogue box asking something from a window called `root`. The args are: `title`, `question`, and `options`. The `title` and `message` args take an `str` as an input and make a dialogue box with the given title and message. The `options` arg takes a `list` or a `tuple` as an input with the contents: `('yes', 'no')`, `('ok', 'cancel')`, `('yes', 'no', 'cancel')`, or `('retry', 'cancel')`. The rest of the args are the same as `tkinter.messagebox.askyesno` or whatever corresponds to the given options.

Example:

```
root.ask(title = '', question = "The document '{doc}' contains\
unsaved changes.\n Do you want to save before closing?",
options = ('yes', 'no', 'cancel'))
```

The function returns the same output as the corresponding function in normal `tkinter`.

4.9 Askstring

Use `root.askstring({args})` to show a dialogue box asking for a string input. The args are: `title` and `prompt`.

Example:

```
root.askstring(title = '', prompt = 'What is your name: ')
```

This will show a dialogue box asking for your name with the buttons `Ok` and `Cancel`. If you click `Cancel` or close the window, it will return `None`. If you fill in the entry and click `Ok`, it will return your answer.

4.10 Askcolor

Use `root.askcolor({args})` to show a color picker.

Example:

```
print(root.askcolor())
```

If you select a color and click on `Okay`, it will return the color you chose in a hex format. If you close the window or click `Cancel`, it will return `None`.

4.11 Stringvar

Use `root.stringvar({args})` to get a `tkinter.StringVar({args})`. The `master` arg, if not given, will default to `root` in the `tkinter.StringVar` that is returned.

Example:

```
s = root.stringvar()
d = root.dropdown(options = ['Option 1', 'Option 2', 'Option 3'],
stringvar = s, showdefault = 'Click Me!')
d.grid()
```

4.12 Intvar

Use `root.intvar({args})` to get a `tkinter.IntVar({args})`. The master arg, if not given, will default to `root` in the `tkinter.StringVar` that is returned.

Example:

```
i = root.intvar()
s = root.spinbox(range_ = (0, 100), textvariable = i)
s.grid()
```

4.13 Booleanvar

Use `root.booleanvar({args})` to get a `tkinter.BooleanVar({args})`. The master arg, if not given, will default to `root` in the `tkinter.BooleanVar` that is returned.

Example:

```
b = root.booleanvar()
c = root.check(text = 'Click Me!', variable = b,
command = lambda: print(b.get()))
c.grid()
```

4.14 Seticon

Use `root.seticon({image})` to set the icon of a window called `root`.

Example:

```
root.seticon('abc.png')
```

You do not have to give it a `tkinter.PhotoImage` as an input. Instead, it takes the filename of an image as an input.

4.15 Getdir

Use `root.getdir({args})` to ask for a directory from the user. The args are the same as `tkinter.filedialog.askdirectory`.

Example:

```
curdir = os.getcwd()
def chdir():
    global curdir
    newdir = root.getdir()
    if newdir:
        curdir = newdir
        refresh()

def refresh():
    l.delete(0, 'end')
    for file in os.listdir(curdir):
```

```

l.insert('end', file)

root.button(text = 'Change Directory', command = chdir).grid()
root.text(text = 'Files:').grid()
l = root.listbox(contents = os.listdir(curdir))
l.grid()

```

4.16 Openfile

Use `root.openfile({types})` to open a file picker. You can filter the types of files it is allowed to open by giving the optional `types` arg. The `types` arg takes a list or a tuple. The default is ('all'). If you have more than one, you will get a dropdown menu in the bottom selecting the filters.

Example:

If you have given `root.openfile(types = ('py', 'txt'))`, then you will get a file picker with the default filter being *.py, but you will be able to select *.txt as well. If you have selected 'all', then there will be no filters.

If you select a file and click on Okay or double click on a file, it will return the file name. If you close the window or click on Cancel, it will return None.

Example:

```
print(root.openfile(types = ('py', 'txt')), 'is your file')
```

4.17 Savefile

Use `root.savefile({types})` to open a file save dialogue. You can filter the types of files it is allowed to return by giving the optional `types` arg. The `types` arg takes a list or a tuple. The default is ('all'). If you have more than one, you will get a dropdown menu in the bottom selecting the filters.

Example:

If you have given `root.savefile(types = ('py', 'txt'))`, then you will get a file save dialogue with the default file extension being *.py, but you will be able to select *.txt as well. If you have selected 'all', then you will manually have to type the file extension as well.

4.18 Sizablefalse

Use `root.sizablefalse()` to make the window unresizable.

Example:

```

def change():
    global i
    i = not i

i = 0
root.button(text = 'Click Me!',

```



```
command = lambda: [exec(('root.sizablefalse()',
'root.sizabletrue()')[i]), change()]).grid()
```

4.19 Sizabletrue

Use `root.sizabletrue()` to make the window sizable again.

Example:

```
def change():
    global i
    i = not i

i = 0
root.button(text = 'Click Me!',
command = lambda: [exec(('root.sizablefalse()',
'root.sizabletrue()')[i]), change()]).grid()
```

4.20 Show

Use `root.show()` to show the window after making it. This is the exact same as `root.mainloop()`.

Example:

```
root = easytk.win()
root.title('')
```

4.21 Gettheme

Use `root.gettheme()` to get the name of the theme currently in use in a window called `root`.

Example:

```
root.text(text = f'Theme: {root.gettheme()}').grid()
```

4.22 Getgeo

Use `root.getgeo()` to get the dimensions of a window called `root`. When called, the function returns a tuple in the form `({width}, {height})`.

Example:

```
def config():
    d = root.getgeo()
    t.config(text = f'Dimensions: {d[0]}x{d[1]}')

t = root.text(text = '')
t.grid()
root.bind('<Configure>', lambda e: config())
```