MACHINE LEARNING ALGORITHMS AND PREDICTIVE MODELS FOR UNDERGRADUATE STUDENT RETENTION AT AN HBCU

A Dissertation

Submitted to the Graduate School

of

BOWIE STATE UNIVERSITY

In partial fulfillment of

the requirements for the

Degree of

DOCTOR OF SCIENCE

Department of Computer Science

By

Ji-Wu Jia

Bowie, MD, 2013

UMI Number: 3604273

All rights reserved

INFORMATION TO ALL USERS

The quality of this reproduction is dependent upon the quality of the copy submitted.

In the unlikely event that the author did not send a complete manuscript and there are missing pages, these will be noted. Also, if material had to be removed, a note will indicate the deletion.



UMI 3604273

Published by ProQuest LLC (2013). Copyright in the Dissertation held by the Author.

Microform Edition © ProQuest LLC.
All rights reserved. This work is protected against unauthorized copying under Title 17, United States Code



ProQuest LLC.
789 East Eisenhower Parkway
P.O. Box 1346
Ann Arbor, MI 48106 - 1346

Machine Learning Algorithms and Predictive Models for Undergraduate Student Retention at an HBC

Ву

Ji-Wu Jia

DISSERTATION COMMITTEE APPROVAL:

Macker Multe, Chair

Dr. Manohar Mareboyana

Dr. Sadanand Srivastava

Dr. Darvl Stone

Dr. Soo-Yeon Ji

, External Examiner

Dr. Kofi Nyarko

ABSTRACT

Title of Dissertation:

MACHINE LEARNING ALGORITHMS AND

PREDICTIVE MODELS FOR UNDERGRADUATE

STUDENT RETENTION AT AN HBCU

Ji-Wu Jia,

Dissertation Chaired By: Dr. Manohar Mareboyana

Department of Computer Science

In this dissertation, I have presented algorithms, which are applied to monitor

undergraduate student retention using student data. The study has also made some

improvements to the classification algorithms such as Decision tree, Support Vector

Machines (SVM), and neural networks that resulted in better prediction accuracies. The

experiments revealed that the main factors that influence student retention at the

Historically Black Colleges and Universities (HBCU) are the cumulative grade point

average and total credit hours taken. The target functions derived from the bare minimum

decision tree and SVM algorithms were further revised to create a two-layer neural

network and a regression to predict the retention. These new models improved the

classification accuracy from 94.03% and 93.64% to 94.42% and 94.29% respectively.

Institutions are increasingly focusing on methods for student retention and

graduation. This dissertation examines the data of undergraduate students who continue

111

to be enrolled in an HBCU institution or who have graduated within six years, in order to determine the factors that influence student retention and derive models to predict the retention. To address this issue, the dissertation focuses on generating predictive models of undergraduate student retention using machine learning techniques.

This study applied several machine learning techniques to the student data with a goal to maximize classification accuracy (percentage of instances classified correctly). We further pruned the Weka J48 decision tree, improved the estimated accuracy, and simplified the learning rules for the HBCU undergraduate student retention. After the retention neural networks models were created, the study used learning feedback based performance improvement algorithm to improve the neural networks model's accuracy.

The research presented in the dissertation evaluated the HBCU undergraduate student retention in the six years period and split the six years to seven student academic levels. The study classified and created retention models for each level, and then the dissertation validated the models by seven independent corresponding test datasets. The six-year retention model's out-of-sample error is 6.95%, which is close to the in-sample error 5.58%.

ACKNOWLEDGEMENTS

I would like to first acknowledge the School of Arts and Sciences, the Graduate School, and the Department of Computer Science at Bowie State University. The doctoral program in Applied Science has been a perfect fit for me, as I have learned so much along the way.

Special thanks to Dr. George Acquaah, Dr. Cosmas U. Nwokeafor, Dr. Lethia Jackson, Dr. Hoda El-Sayed, Dr. Manohar Mareboyana, Dr. Sadanand Srivastava, Dr. Darsana Josyula, Dr. Kofi Nyarko, Dr. Daryl Stone, Dr. Soo-Yeon Ji, Dr. Bo Yang, Dr. Joseph Gomes, Dr. Claude Turner, Dr. Joan Langdon, and Dr. Mario Fenyo for their friendly and supportive guidance and assistance throughout this dissertation process. Thanks also to all of my committee members for taking the time to thoroughly review my work and to provide many helpful suggestions and valuable feedback along the way.

Thanks to the Bowie State University Division of Information Technology for their support.

Thanks to Ms. Gayle Fink for her support during my dissertation writing and finally I would like to thank my family for their support.

DEDICATION

This dissertation is dedicated to my wife and my family.

TABLE OF CONTENTS

	Page
Abstract	iii
Acknowledgements	v
Dedication	
Table of Contents.	vii
List of Tables	xi
List of Figures.	xiii
List of Acronyms	xv
Chapter I Introduction	1
Background of the Problem - Undergraduate Student Retention	1
Statement of the Problem	2
Research Questions and Hypothesis	2
Significance of the Study	3
Definition of Terms	
Contributions	
Organization of the Study	
Chapter II Literature Review	
Definition of Undergraduate Student Retention	
Traditional Statistical Analysis Methods	16

Using Data Mining to Improve College Student Retention	19
Using WEKA	19
Using Neural Network with the Overall College GPA	23
Using Naive Bayes, SVM, and Decision Tree with 17 Factors	24
Using Stepwise Logistic Regression and the Certain Insurmountable Problems	26
Associate Rules as the Data Mining Results	27
Summary	27
Chapter III Methodology.	28
Predictive Models for Undergraduate Student Retention at the HBCU	28
Using Machine Learning.	28
Population and Sample	29
Data Collection	31
Machine Learning.	34
Six-Year Training Dataset's Weka J48 Decision Tree	34
Six-Year Training Dataset's Naive Bayes	38
Six-Year Training Dataset's Simple Logistic	42
Six-Year Training Dataset's JRip	43
Five-Year Training Dataset's J48 Decision Tree	44
Four-Year Training Dataset's J48 Decision Tree	44
Three-Year Training Dataset's Bare Minimum Decision Tree	45
Two-Year Training Dataset's J48 Decision Tree	45
One-Year Training Dataset's JRip.	46
Zero-Year Training Dataset's JRip	47

Summary of the Retention Algorithms	50
Chapter IV Results	51
Measuring Performance	51
Six-Year Training Dataset's Bare Minimum Decision Tree Algorithm	51
The Information Theory of the Classification for Six-Year Training Dataset	54
Six-Year Training Dataset's Two-Layer Neural Network Learning Algorithm	56
Improvement Performance of the Six-Year Training Dataset's Two-Layer N	Neura
Network	59
Major Predictors of Undergraduate Student Retention	61
Academic PLAN Clusters the RETENTION into Two Groups	62
Commuting DISTANCE Affects the Retention	65
Built Six-Year Training Dataset's One-Layer Neural Network Derived from S	Simple
Logistic Regression.	65
Improved Six-Year Training Dataset's Two Models' Accuracies	68
Five-Year Training Dataset's Retention Neural Network	69
Four-Year Training Dataset's Retention Neural Network	70
Three-Year Training Dataset's Retention Neural Network	70
Two-Year Training Dataset's Retention Neural Network	71
One-Year Training Dataset's Retention Neural Network	72
Zero-Year Training Dataset's Retention Neural Network	73
Summary of the Retention Models	73
Support Vector Machines	74
The Results of Test Datasets	76

Retention Models' Validation	79
The Final Retention Model	81
Frameworks	84
Chapter V Summary, Conclusions, Discussion, and Recommendations	86
Summary	86
Conclusions.	88
Discussion	89
Recommendations	90
References	92
Appendix A Training Dataset	102
Appendix B Test Dataset.	104
Appendix C Permission to Use Bowie Undergraduate Student Data	105
Appendix D The Letter for Test Dataset	107

LIST OF TABLES

Table Title	Page
Humphreys' Results	18
Lin's Data Factors List.	20
Lin's Datasets.	
Lauria's Factors	21
Zhang's Results.	25
Dataset Attributes List	32
J48 Summary	36
J48 Results	38
Naive Bayes Summary	39
RETENTION with Numeric Attributes	40
RETENTION with PLAN	41
Simple Logistic Classification Summary	42
JRip Classification	43
One-Year JRip Classification.	46
Zero-Year Training Dataset	48
Zero-Year JRip Summary	49
Classification Accuracies by Year	50
LAST UG CUMGPA and TOT TAKEN CH	62

Comparison of Naive Bayes and Real Academic Plan	63
The Below 44.9% Retention Group	64
The Above 44.9% Retention Group	65
Improved Models' Accuracies	69
Summary of the Retention Models	74
Test Dataset Numeric Attributes	77
Test Dataset's Academic Plans	78
Test Datasets' Accuracies by Year	79
Six-Year Model's Predictive Values	80
Models' Predictive Accuracies	80
Models' Predictive Errors.	80

LIST OF FIGURES

Figure Title	Page
The Problems and the Hypothesis.	4
Zhang's Student Dropouts	25
Process Identifying Student Retention Model Using Machine Learning	29
J48 Visualization	
J48 Classification Errors View	
J48 Decision Tree	37
Naive Bayes Classification Errors	39
Simple Logistic Classification Errors.	43
JRip Errors	44
Five-Year J48 Decision Tree.	44
Four-Year J48 Decision Tree.	45
Three-Year Bare Minimum Decision Tree.	45
Two-Year J48 Decision Tree.	46
One-Year JRip Decision Tree.	47
Zero-Year JRip Decision Tree	49
J48 Decision Tree	51
The Bare Minimum Decision Tree.	54
The Basic Retention Learning Model Algorithm	56

Artificial Neuron Model	57
Two-Layer Neural Network.	58
Improved Two-Layer Neural Network	60
The Improved Model Compared to the Dataset	61
One-Layer Neural Network	66
Improved One-Layer Neural Network	67
The Improved One-Layer Neural Network Model Compared to	the
Dataset	
Five-Year Retention Neural Network	
Four-Year Retention Neural Network.	
Three-Year Retention Neural Network	71
Two-Year Retention Neural Network.	71
One-Year Retention Neural Network	72
Zero-Year Retention Neural Network.	73
Training Datasets' Retention Results	74
The Data Points Boundary with a Curve	75
Test Datasets' Retention Results.	79
The Final Retention Model.	84
Framework of Machine Learning for Retention	85

LIST OF ACRONYMS

AI Artificial Intelligence

DM Data Mining

DT Decision Tree

EDM Educational Data Mining

HBCU Historically Black Colleges and Universities

KDD Knowledge Discovery in Databases

MDT Minimum Decision Tree

NN Neural Networks

NP Nondeterministic Polynomial Time Complexity

OPAA Office of Planning, Analysis and Accountability

SVM Support Vector Machines

VCU Virginia Commonwealth University

WEKA Waikato Environment for Knowledge Analysis

CHAPTER I

INTRODUCTION

1. Background of the Problem - Undergraduate Student Retention

Student retention has become an indication of academic performance and enrollment management. One of the biggest challenges that higher education faces is to improve student retention. (Zhang, 2009) Student retention is the Institution's capacity to engage faculty and administrators in a collaborative effort to construct educational settings that engage all students in learning (Tinto, 2006). Retention is one of the most widely studied areas in higher education (Tinto, 2006). In general, the higher the number of students remaining in the university, the better the academic programs, and the higher the revenue (Zhang, 2009).

Undergraduate students comprise more than 70% of the general university population in the USA. Most studies focus on undergraduate student retention.

Undergraduate student retention is a long-standing problem in higher education and has been the subject of a great deal of research over the past 75 years (Pittman, 2008). Universities with high attrition rates face substantial loss of tuition, fees, and potential alumni contributions, while the students themselves also face negative consequences. Despite the identified consequences of college dropout for universities and students and the concentrated efforts from all educational institutions on improving student retention, attrition rates remain relatively high across the United States. Data from the National

Center for Public Policy and Higher Education reveal that only 73.6% of first-time, full-time freshmen (enrolled in 2002) returned for their second semester. In terms of college completion data from 2005, only 39.5% of undergraduate students enrolled in public institutions completed their degrees within five years. Tinto's widely accepted model of student retention examines factors contributing to a student's decision to continue his or her higher education. The primary focus of this model is a student's academic and social integration into the university (Yu, 2010).

2. Statement of the Problem

Most Historically Black Colleges and Universities (HBCUs) were created at a time when Black students could not attend White institutions. HBCUs were established before 1964, the year the Civil Rights Act outlawed racial segregation, with the intention of serving the African American community (Stone, 2008). African American students are even more likely to drop out of school than their White counterparts.

The problem is that the HBCU needs predictive models for undergraduate student retention to increase the retention rate. This study will investigate, determine, examine, develop, and evaluate the issue being studied. The purpose of this study will be to determine the variables that explain undergraduate student retention at the HBCU. This study is designed to investigate the predictive models for undergraduate student retention at the HBCU.

3. Research Questions and Hypothesis

The dissertation is to answer the following three questions:

1. Can a target function be defined that explains the mapping between student data (academic and social) and six years student retention?

- 2. Which models can be used to learn different target functions?
- 3. What is the accuracy of the target function? What methodology can be used to improve the target function's accuracy?

The research hypothesis is as follows:

If we use the algorithms and the modeling target functions, then we can predict the undergraduate student six years retention.

4. Significance of the Study

The HBCU needs predictive models for undergraduate student retention to increase the retention rate. This study will investigate, determine, examine, develop, and evaluate the issue being studied. This study is applying computer science knowledge to the retention problem at the HBCU. The purpose of this study is to explore the effectiveness of machine learning techniques applied to undergraduate student six years retention at the HBCU, and uses those techniques to find patterns of undergraduate students in six years retention at the HBCU. The objective of the study is to reveal algorithms and predictive models of undergraduate student six years retention at the HBCU.

This study is to create predictive models for undergraduate student retention using decision tree and further using Jia Heuristic Algorithm to prune the decision tree to bare minimum decision tree, therefore to obtain the learning rules, and then create neural networks models to predict the retention. This study also created an algorithm for improving the models' accuracy. The problem and the dissertation hypothesis are shown in Figure 1.1.




FIGURE 1.1 THE PROBLEMS AND THE HYPOTHESIS

The HBCU can use the study's found algorithms and predictive models to predict undergraduate student retention.

5. Definition of Terms

• Knowledge Discovery in Databases (KDD)

Knowledge discovery in databases (KDD) is the process of finding useful information and patterns in data (Dunham, 2003; Mitchell, 1997; Russell, 2010).

Data Mining

Data mining is the use of algorithms to extract the information and patterns derived by the KDD process (Dunham, 2003; Mitchell, 1997; Russell, 2010).

Data mining is a form of exploratory data analysis for automatically extracting patterns and relationships from immense quantities of data rather than testing preformulated hypotheses. In addition, typical data mining techniques include cross-validation, which is considered a form of re-sampling. The major goal of cross-validation is to avoid over-fitting, which is a common problem when modelers try to account for every structure in one dataset (Yu 2010).

KDD Process and Data Mining Process

The KDD process consists of the following five steps (Dunham, 2003; Mitchell, 1997; Russell, 2010):

- a. Selection: The data needed for the data mining process may be obtained from many different and heterogeneous data sources.
- b. Preprocessing: The data to be used by the process may have incorrect or missing data. Erroneous data may be corrected or removed; whereas, missing data must be supplied or predicted.
- c. Transformation: Data from different sources must be converted into a common format for processing.
- d. Data Mining: This process applies algorithms to the transformed data to generate the desired results.
- e. Evaluation: How the data mining results are presented to the users is extremely important.

Machine Learning

Machine learning is used to adapt to new circumstances and to detect and extrapolate patterns (Russell, 2010).

Machine Learning is the study of computer algorithms that improve automatically through experience. Successful applications range from data mining programs that discover general rules from large databases, to information filtering systems that learn the users' reading preferences, to autonomous vehicles that learn to drive on public highways (Mitchell, 1997).

Knowledge representation stores what it knows or hears (Russell, 2010). Artificial Intelligence (AI) includes many Data Mining techniques such as neural networks and classification. However, AI is more general and involves areas outside traditional data mining. AI application also may not be concerned with scalability as datasets may be small (Dunham, 2003).

Machine learning is the area of AI that examines how to write programs that can learn. In data mining, machine learning is often used for prediction or classification. With machine learning, the computer makes a prediction and then, based on whether it is correct, "learns" through examples, domain knowledge, and feedback (Dunham, 2003).

Classification

Classification maps data into predefined groups or classes (Dunham, 2003). Dunham defined classification as the following:

Given a database $D = \{t_1, t_2, ..., t_n\}$ of tuples (items, records) and a set of classes $C = \{C_1, ..., C_m\}$, the classification problem is to define a mapping $f: D \to C$ where each t_i is assigned to one class. A class, C_j , contains precisely those tuples mapped to it; that is, $C_j = \{t_i \mid f(t_i) = C_j, 1 <= i <= n, and t_i \in D\}$.

• Prediction

Many real-world data mining applications can be seen as predicting future data states based on past and current data. Prediction can be viewed as a type of classification. The difference is that prediction is predicting a future state rather than a current state. Prediction applications include flooding, speech recognition, machine learning, and pattern recognition (Dunham, 2003).

Decision Tree

A decision tree is a predictive modeling technique used in classification, cluster, and prediction tasks. Decision tree uses a "divide and conquer" technique to split the problem search space into subsets (Dunham, 2003). Dunham defined it as the following:

A decision tree is a tree where the root and each internal node are labeled with a question. The arcs emanating from each node represent possible answers to the associated question. Each leaf node represents a prediction of a solution to the problem under consideration.

Decision Tree Model

Decision tree model is a computational model consisting of three parts (Dunham, 2003):

- 1. A decision tree as defined above
- 2. An algorithm to create the tree
- 3. An algorithm that applies the tree to data and solves the problem under consideration.

These decisions generate rules for the classification of a dataset (Baradwaj, 2011).

• NP (Non-deterministic Polynomial Time)-Hard Problem

Occam's razor refers to the simplest hypothesis that fits the data (Mitchell, 1997). Minimum set covering is an NP-hard problem (Mitchell, 1997). Finding a minimal decision tree (nodes, leaves, or depth) is an NP-hard optimization problem (Mitchell, 1997).

Class NP means that there are an extremely large number of possibilities for the optimal answer, and we do not have an efficient deterministic algorithm to sift them to find the correct one (McConnell, 2001).

Entropy Measures Homogeneity of Examples

Entropy characterizes the impurity of an arbitrary collection of examples (Mitchell, 1997; Dunham, 2003). Given a collection *S*, containing positive and negative examples of some target concept, the entropy of *S* relative to this Boolean classification is

$$Entropy(S) = -P_1 \log_2 P_1 - P_2 \log_2 P_2 \tag{1}$$

Where P_1 is the fraction of positive examples in S and P_2 is the fraction of negatives examples in S.

Notice that the entropy is 0 if all members of S belong to the same class. Note that the entropy is 1 when the collection contains an equal number of positive and negative examples.

For general entropy:

$$Entropy(S) = \sum_{j} -P_{j} \log_{2} P_{j}$$
 (2)

Where P_j is the fraction of j type examples in S.

• Information Gain Measures the Expected Reduction in Entropy

A measure of the effectiveness of an attribute in classifying the training data, called information gain, is simply the expected reduction in entropy caused by partitioning the examples according to this attribute (Mitchell, 1997; Dunham, 2003). More precisely, the information gain, Gain(S, A) of an attribute A, relative to a collection of examples S, is defined as