

Import Json file and do projection, aggregation, limit,count ,skip and remove using python and hdfs.

Aim:

To import Json file and do projection, aggregation, limit,count ,skip and remove using python and hdfs.

Procedure:

Step 1: Create json file on bash & save as emp.json

nano emp.json ; Paste the below content on it

```
[  
{"name": "John Doe", "age": 30, "department": "HR", "salary": 50000},  
{"name": "Jane Smith", "age": 25, "department": "IT", "salary": 60000},  
{"name": "Alice Johnson", "age": 35, "department": "Finance", "salary": 70000},  
{"name": "Bob Brown", "age": 28, "department": "Marketing", "salary": 55000},  
{"name": "Charlie Black", "age": 45, "department": "IT", "salary": 80000}  
]
```

Step 2: put the employees.json local directory to home/hadoop directory

Step 3: Install Required Packages

Open your terminal or command prompt and run the following commands to install the required Python packages.

pip install pandas

pip install hdfs

Step 4: Verify Installation

Test the package installations by running the following Python commands in a Python shell or a script:

```
import pandas as pd
```

```
from hdfs import InsecureClient
```

```
# Check pandas version
```

```
print("Pandas version:", pd.__version__)
```

```
# Test HDFS client connection

client = InsecureClient('http://localhost:9870', user='hadoop')

print("HDFS status:", client.status('/'))
```

This will print the version of Pandas installed and confirm whether the HDFS connection is successful.

Step 5: Create the process_data.py File

Create a new Python file named process_data.py and add the following code to it:

```
from hdfs import InsecureClient

import pandas as pd

import json

# Connect to HDFS

hdfs_client = InsecureClient('http://localhost:9870', user='hdfs')

# Read JSON data from HDFS

try:

    with hdfs_client.read('/home/hadoop/emp.json', encoding='utf-8') as reader:

        json_data = reader.read() # Read the raw data as a string

        if not json_data.strip(): # Check if data is empty

            raise ValueError("The JSON file is empty.")

        print(f"Raw JSON Data: {json_data[:1000]}") # Print first 1000 characters for debugging

        data = json.loads(json_data) # Load the JSON data

except json.JSONDecodeError as e:

    print(f"JSON Decode Error: {e}")

    exit(1)

except Exception as e:

    print(f"Error reading or parsing JSON data: {e}")

    exit(1)
```

```
# Convert JSON data to DataFrame
try:
    df = pd.DataFrame(data)
except ValueError as e:
    print(f"Error converting JSON data to DataFrame: {e}")
    exit(1)

# Projection: Select only 'name' and 'salary' columns
projected_df = df[['name', 'salary']]

# Aggregation: Calculate total salary
total_salary = df['salary'].sum()

# Count: Number of employees earning more than 50000
high_earners_count = df[df['salary'] > 50000].shape[0]

# Limit: Get the top 5 highest earners
top_5_earners = df.nlargest(5, 'salary')

# Skip: Skip the first 2 employees
skipped_df = df.iloc[2:]

# Remove: Remove employees from a specific department
filtered_df = df[df['department'] != 'IT']

# Save the filtered result back to HDFS
filtered_json = filtered_df.to_json(orient='records')

try:
    with hdfs_client.write('/home/hadoop/filtered_employees.json', encoding='utf-8',
        overwrite=True) as writer:
```

```

        writer.write(filtered_json)

    print("Filtered JSON file saved successfully.")
except Exception as e:
    print(f"Error saving filtered JSON data: {e}")
    exit(1)

# Print results

print(f"Projection: Select only name and salary columns")
print(f"{projected_df}")

print(f"Aggregation: Calculate total salary")
print(f"Total Salary: {total_salary}")

print(f"# Count: Number of employees earning more than 50000")
print(f"Number of High Earners (>50000): {high_earners_count}")
print(f"Top 5 Earners: \n{top_5_earners}")
print(f"Skipped DataFrame (First 2 rows skipped): \n{skipped_df}")
print(f"Filtered DataFrame (IT department removed): \n{filtered_df}")

```

Step 6: Run the process_data.py Script

Run the script in your terminal or command prompt by typing the following command:

```
python3 process_data.py
```

Make sure your HDFS is up and running, and the /home/hadoop/emp.json file exists on your HDFS.

The script will read the JSON file from HDFS, process the data, and save the filtered results back to HDFS.

Step 7: Check the output.

OUTPUT:

```
Activities Terminal Sep 17 19:30 user@Ubuntu: ~
user@ubuntu:~$ python3 process_data.py
Raw JSON Data: [
{"name": "John Doe", "age": 30, "department": "HR", "salary": 50000},
{"name": "Jane Smith", "age": 25, "department": "IT", "salary": 60000},
{"name": "Alice Johnson", "age": 35, "department": "Finance", "salary": 70000},
{"name": "Bob Brown", "age": 28, "department": "Marketing", "salary": 55000},
{"name": "Charlie Black", "age": 45, "department": "IT", "salary": 80000}
]

Filtered JSON file saved successfully.
Projection: Select only name and salary columns
  name  salary
0  John Doe  50000
1  Jane Smith 60000
2  Alice Johnson 70000
3  Bob Brown 55000
4  Charlie Black 80000
Aggregation: Calculate total salary
Total Salary: 315000

Count: Number of employees earning more than 50000
Number of High Earners (>50000): 4

Limit: Top 5 highest salary
Top 5 Earners:
  name  age  department  salary
4  Charlie Black  45      IT      80000
2  Alice Johnson  35     Finance  70000
1  Jane Smith    25      IT      60000
3  Bob Brown    28     Marketing  55000
0  John Doe     30      HR      50000

Skipped DataFrame (First 2 rows skipped):
  name  age  department  salary
2  Alice Johnson  35     Finance  70000
3  Bob Brown    28     Marketing  55000
4  Charlie Black  45      IT      80000

Filtered DataFrame (IT department removed):
  name  age  department  salary
0  John Doe  30      HR      50000
2  Alice Johnson  35     Finance  70000
3  Bob Brown  28     Marketing  55000
user@ubuntu:~$
```

Result:

Thus the program to import Json file and to do projection, aggregation, limit, count, skip and remove using python and hdf5 is executed successfully.

