

Nordvik Bearing Industries GmbH

Technical Data Sheet — Deep Groove Ball Bearing

Model / Part No.	SKB-6205-2RS
Document No.	NBI-DS-6205-2RS-R3
Revision	Rev. 3
Date	2026-02-11

1. Description

Single row deep groove ball bearing with double-side rubber seals (2RS), pre-lubricated with high-performance grease. Suitable for general industrial machinery, electric motors, pumps, and conveyor rollers requiring moderate radial and axial load capacity at standard operating speeds.

2. Dimensional Specifications

Parameter	Value
Bore Diameter (d)	25 mm
Outside Diameter (D)	52 mm
Width (B)	15 mm
Chamfer (r min.)	1.1 mm
Weight	0.130 kg

3. Performance Ratings

Parameter	Value
Dynamic Load Rating (Cr)	14000 N
Static Load Rating (C0r)	6950 N
Limiting Speed (grease)	18,000 rpm
Reference Speed	20000 min-1
Operating Temperature Range	-30 degC to 120 C

4. Material & Construction

Ring & Ball Material	Chrome Steel (SAE 52100)
Cage Material	Pressed Steel
Seal Type	2RS (Rubber, Contact Type)
Lubricant	Lithium-based grease, NLGI 2

5. Compliance & Standards

Manufactured in accordance with ISO 15:2017 boundary dimensions. RoHS 2011/65/EU compliant. Material certification available on request. This product is not rated for use in explosive atmospheres (ATEX).

6. Packaging

Standard pack: 1 unit per box, 50 boxes per carton. Export packaging (VCI wrapped) available on request.

Note: Specifications subject to change without notice. Contact technical sales for application-specific load calculations.