

Veltrix Motors & Drives Pvt. Ltd.

Technical Data Sheet — Three-Phase Squirrel Cage Induction Motor

Model / Part No.	IM-100L-4P
Document No.	VMD/TDS/IM100L/2026
Revision	Rev. 1
Date	2026-05-02

1. General Description

TEFC (Totally Enclosed Fan Cooled) three-phase induction motor designed for continuous duty (S1) industrial applications including pumps, fans, and conveyor drives. Foot-mounted, aluminium frame construction.

2. Electrical Ratings

Parameter	Value
Rated Output	3 kW
Rated Voltage	415 V (+/-10%)
Frequency	50 Hz
Rated Current	6.2 A
Power Factor (cos phi)	0.82
Efficiency Class	
Insulation Class	F
Protection Rating	IP55

3. Mechanical Specifications

Frame Size	100L
Mounting	B3 (Foot Mounted)
Weight	18.5 kg
Shaft Diameter	28 mm
Noise Level	N/A

4. Operating Conditions

Ambient temperature: -15C to +40C. Altitude: up to 1000m above sea level without derating. Duty type: S1 (Continuous).

5. Compliance

Conforms to IEC 60034 series. CE marked. Efficiency tested per IEC 60034-2-1 (class rating pending certification update — see engineering bulletin EB-2026-07).