

Sentra Automation Systems

Technical Data Sheet — Inductive Proximity Sensor

Model / Part No.	IPS-18-M-DC-NO
Document No.	SAS-DS-IPS18-2026-v2
Revision	v2.0
Date	2026-06-18

1. Overview

M18 cylindrical inductive proximity sensor for non-contact detection of metallic objects. DC 3-wire, NPN/NO output. Designed for factory automation, packaging machinery, and material handling applications.

2. Electrical Characteristics

Parameter	Value
Operating Voltage	10-30 VDC
Sensing Range	8 mm (Sn, non-flush)
Output Type	NPN, Normally Open (NO)
Output Current (max)	200 mA
Switching Frequency	500 Hz
Response Time	1 ms
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes

3. Mechanical & Environmental

Housing Material	Nickel-plated Brass
Thread Size	M18 x 1
Connection Type	Cable, 2m PVC (3-wire)
Protection Rating	IP67
Operating Temperature	-25C to +70C
Vibration Resistance	55 Hz, amplitude 1mm

4. Compliance

CE, UKCA. RoHS compliant. Not certified for intrinsically safe / hazardous location use.

5. Ordering Information

Part Number	IPS-18-M-DC-NO
Variant (Flush Mount)	IPS-18-M-DC-NO-F (Sn 5mm)
Variant (NC Output)	IPS-18-M-DC-NC