MOTILAL NEHRU NATIONAL INSTITUTE OF TECHNOLOGY ALLAHABAD
PRAYAGRAJ, INDIA – 211004

A PROJECT REPORT ON

TRUSTPAY: AI-POWERED FRAUD DETECTION & TRANSACTION MANAGEMENT SYSTEM

PROJECT Number

E2

Submitted By

Raghav Gupta (Reg. No: 20243226)
Rishabh Srivastava (Reg. No: 20243236)
Rishabh Singh (Reg. No: 20243235)
Prince Keshari (Reg. No: 20243218)

Submitted as DBMS Project Work

Bachelor of Technology (B. Tech.)

Department of Computer Science and Engineering

MOTILAL NEHRU NATIONAL INSTITUTE OF TECHNOLOGY ALLAHABAD
PRAYAGRAJ, UTTAR PRADESH – 211004

2026–2027

2. Abstract

In modern high-throughput financial technology ecosystems, maintaining transactional integrity while preventing sophisticated fraud is a fundamental engineering challenge. Traditional banking database management systems frequently suffer from either concurrency bottlenecks under simultaneous debit requests or brittle, hardcoded rule sets that fail to catch modern card-testing micro-probing and account takeover (ATO) attacks.

This project report presents **TRUSTPAY**, an enterprise-grade, AI-enabled relational transaction processing and fraud surveillance system developed for the *Database Management Systems (DBMS)* curriculum at Motilal Nehru National Institute of Technology Allahabad. TrustPay combines a strictly normalized **Boyce-Codd Normal Form (BCNF)** relational database architecture implemented on MySQL 8 (InnoDB) with an asynchronous event-driven surveillance engine powered by RabbitMQ message brokering, Redis 7 sliding-window rate limiting, and a 3-layer hybrid artificial intelligence pipeline (LightGBM + Groq LPU GenAI + Deterministic Decision Engine).

The core database schema decomposes the transactional domain across eight first-class entities enforcing strict referential integrity, check constraints, active triggers, and atomic stored procedures utilizing pessimistic row-level locking (`SELECT ... FOR UPDATE`) to guarantee serializability and eliminate double-spending race conditions. The integrated intelligence layer achieves a **1.27 ms** median ML inference latency, clearing legitimate transactions instantaneously while boosting fraud recall to **70.67%** at **99.940% overall accuracy** when benchmarked on **284,807 real-world European cardholder transactions**.

Prescribed Table of Contents

Sec #	Report Section Title (As Prescribed by CSE Department)	Target Domain
1.0	Title Page (Sample Template Specified by Department)	Official Cover & Credentials
2.0	Abstract & Table of Contents	Executive Engineering Overview
3.0	Introduction and Problem Statement	Fintech Fraud & DBMS Challenges
4.0	Project Objectives and Scope	Functional & Technical Boundaries
5.0	System Analysis and Requirements	FRs, NFRs & Environment Specs
6.0	ER/EER Diagram and Database Schema	8 Entities, Keys & Data Dictionary
7.0	Keys, Functional Dependencies and Normalization	1NF to BCNF Mathematical Proofs
8.0	SQL Implementation (DDL, DML, Joins and Subqueries, etc.)	Production Schema & Analytical Queries
9.0	Views, Indexes, Triggers and Transactions Implemented	Row Locks, B-Trees & Stored Procs
10.0	Front-End Design and Database Connectivity	React 19 SPA & 6-Service Topology
11.0	CRUD Operations and Report Generation	Lifecycle Queries & Settlement Reports
12.0	AI/ML Implementation and Model Evaluation	LightGBM, Groq LPU & 284k ULB Test
13.0	Testing, Results and Screenshots	50-Thread ACID Stress & Dashboards
14.0	Conclusion and Future Scope	Engineering Summary & Roadmap
15.0	References / Bibliography	Academic Texts & IEEE Standards

3. Introduction and Problem Statement

3.1 Technological Background

Digital payment ecosystems and Unified Payments Interfaces (UPI) process billions of high-frequency micro-transactions daily. As retail banking migrates to cloud infrastructure and distributed microservices, the underlying relational database management system (RDBMS) represents the single source of truth for account balances, asset ledgers, and transaction histories. In high-concurrency environments, financial ledgers must guarantee strict **Atomicity, Consistency, Isolation, and Durability (ACID)** while maintaining millisecond-level responsiveness.

3.2 Contemporary Threat Landscape in Digital Banking

Modern cybercriminals exploit distributed banking architectures through automated attack vectors:

- **Automated Card Testing** / **Micro-Probing:** Botnets initiate sub-dollar transactions (e.g., EUR 0.00 or EUR 1.00) across thousands of stolen credentials to detect active accounts before executing capital depletion.
- **Rapid Velocity Bursts:** Rapidly issuing multiple transfer requests within seconds to exploit distributed latency before asynchronous risk engines register velocity thresholds.
- **Account Takeover (ATO):** Credential-stuffing attacks originating from unfamiliar device fingerprints, proxy/VPN networks, or impossible geographic travel vectors.
- **Race-Condition Exploitation:** Initiating simultaneous parallel transfers against a single account to trigger dirty reads or non-repeatable reads, inducing negative balances and double-spending.

3.3 Limitations of Traditional Database Management Architectures

Architectural Dimension	Traditional DBMS Implementation	TrustPay Engineered Solution
Concurrency Control	Optimistic locking or table-level locks; causes deadlock cascades or silent overdrafts under parallel load.	Pessimistic row-level locking (`SELECT ... FOR UPDATE`) wrapped in atomic stored procedures with rollback semantics.
Fraud Risk Assessment	Static, hardcoded `IF/ELSE` SQL triggers; high false-positive rates blocking legitimate customers.	3-layer hybrid AI (LightGBM + Groq LPU GenAI + deterministic decision rules) decoupled via RabbitMQ queues.
Throughput & Latency	Synchronous blocking evaluation; checkout takes 2,000–5,000 ms causing UI timeout failures.	Non-blocking `202 Accepted` gateway (<15ms); background worker evaluation in 1.27 ms.
Abuse & DDoS Prevention	Application-level basic IP filters; vulnerable to distributed IP rotation and memory exhaustion.	Redis 7 Sorted Set (`ZSET`) sliding-window rate limiting (5 req / 10s per user/IP) returning `HTTP 429`.

3.4 Problem Statement

> **Core Engineering Problem:** To architect, normalize, implement, and benchmark an enterprise-grade Relational Database Management System (RDBMS) on MySQL 8 that guarantees absolute ACID financial consistency and zero double-spending under high concurrency, while orchestrating an asynchronous event-driven pipeline that analyzes 20 behavioral features, executes machine learning inference in under 2 ms, and generates natural-language forensic audit explanations without impeding core transaction throughput.

4. Project Objectives and Scope

4.1 Primary Project Objectives

The engineering objectives of the TrustPay platform are structured across database architecture, distributed systems integration, and machine learning surveillance:

- **O-1: BCNF Normalization & Relational Schema Design:** Model the complete retail banking lifecycle across eight normalized entities (users, accounts, devices, locations, transactions, predictions, alerts, reviews), eliminating update, insertion, and deletion anomalies.
- **O-2: ACID Transaction Processing & Row-Level Locking:** Implement stored procedures using `SELECT ... FOR UPDATE` to ensure strict serializability during concurrent debit/credit operations, preventing race-condition double spending.
- **O-3: Active Automated Auditing & Integrity Triggers:** Deploy database triggers to enforce business invariants (validating positive transfer amounts, verifying active account statuses, and timestamping alert resolutions).
- **O-4: Asynchronous Message Queue Decoupling:** Implement RabbitMQ AMQP message brokering to decouple user payment submissions (responding with immediate `HTTP 202 Accepted` in <15ms) from compute-intensive AI evaluations.
- **O-5: Redis 7 In-Memory Caching & Rate Limiting:** Enforce sliding-window rate limiting via Redis Sorted Sets (`ZSET`) to mitigate brute-force probing, alongside sub-2ms TTL caching for read-heavy account balances.
- **O-6: 3-Layer Hybrid AI Fraud Surveillance:** Train a 20-feature LightGBM model operating at <2ms latency, coupled with a Groq LPU GenAI contextual reasoning layer and a deterministic decision engine.
- **O-7: Administrative Compliance Cockpit:** Provide risk officers with interactive views, transaction filtering, and forensic explanation tools for manual review and dispute resolution.

4.2 Project Scope & Operational Boundaries

Domain	In-Scope Capabilities (Implemented & Verified)	Out-of-Scope (Realistic Academic Boundaries)
Ledger & Banking	Multi-user accounts, currency balances, deposit/ withdrawal/transfer types, BCNF schema, ACID stored procs.	External NPCI / Visa / Mastercard clearing switch integration; loan & interest amortizations.
AI & Fraud Surveillance	20 dynamic behavioral features, LightGBM classifier, Groq Llama 3.3 explanations, multi-tier triage.	Automated chargeback legal filings with credit bureaus; continuous real-time model retraining.
Security & Auth	Bcrypt password hashing (salt rounds 10), stateless JWT tokens, role-based access control (RBAC).	Hardware Security Module (HSM) physical key storage; biometric iris/fingerprint hardware drivers.
Infrastructure & Ops	Docker Compose 6-container mesh, GitHub Actions CI/CD (5 parallel jobs), 3-layer keep-alive daemon.	Global multi-region active-active database replication; multi-datacenter disaster recovery failover.

5. System Analysis and Requirements

5.1 Functional Requirements (FR)

- **FR-1 (User & Account Governance):** The system must support customer and administrator onboarding, assigning unique 64-bit identifiers, hashed credentials, and establishing multiple ledger accounts per user with currency specifications.
- **FR-2 (Atomic Payment Processing):** The system must process fund transfers between accounts atomically. If either account has insufficient funds, invalid status, or encounters an unexpected failure, all changes must be rolled back.
- **FR-3 (Telemetry Ingestion & Device Fingerprinting):** Every transaction must record IP address, browser/device fingerprint, and geolocation coordinates to maintain historical velocity baselines.
- **FR-4 (Asynchronous Risk Evaluation):** The system must push transaction payloads to a durable RabbitMQ queue (`fraud_evaluation_queue`) and update transaction state asynchronously without blocking client threads.
- **FR-5 (Sliding-Window Rate Limiting):** The gateway must intercept client traffic and enforce a 5 requests per 10 seconds limit per user/IP via Redis ZSETs, responding with `HTTP 429 Too Many Requests` upon violation.
- **FR-6 (Administrative Triage & HITL Review):** Flagged transactions must enter an administrative audit queue where human officers can inspect AI forensic explanations and execute approve or reject decisions.

5.2 Non-Functional Requirements (NFR)

- **NFR-1 (Performance & Latency):** Transaction ingestion gateway response < 15 ms; ML inference latency < 2.0 ms median; Redis cache reads < 2.0 ms; database row-level locking execution < 10 ms.
- **NFR-2 (Consistency & Isolation):** Relational database must run on MySQL InnoDB with `REPEATABLE READ` isolation and explicit pessimistic row locks, guaranteeing zero balance divergence or dirty reads.
- **NFR-3 (Security & Encryption):** TLS 1.3 encryption across all cloud connections; password salting via Bcrypt; parameterized SQL queries across all gateway routes to prevent SQL injection (SQLi).
- **NFR-4 (High Availability & Resilience):** Containerized orchestration via Docker Compose with healthcheck dependency chains; self-healing auto-reconnection on RabbitMQ and MySQL connection dropouts.


5.3 Hardware, Software & Environmental Specifications

System Tier	Technology & Version	Configuration & Operational Role
Relational Database	MySQL 8.0.35 Enterprise (InnoDB)	BCNF schema, foreign keys, triggers, stored procs, row locks (Aiven Cloud / Docker).
In-Memory Cache & Limiter	Redis 7.2 Alpine	Sorted-Set (`ZSET`) sliding-window rate limiting + TTL account caching.
Message Broker	RabbitMQ 3.12 (Erlang 26)	AMQPS durable queues (`fraud_evaluation_queue`), persistent delivery, prefetch 10.
API Gateway	Node.js 20 LTS / Express 5	Stateless JWT RBAC, `mysql2/promise` connection pool, `amqplib` publisher.
Sentinel AI Worker	Python 3.11 / FastAPI / Uvicorn	LightGBM 4.3, Groq LPU SDK, `aio-pika` consumer, asynchronous event loop.
Client Interface	React 19 / Vite 5 / Tailwind CSS	SPA with responsive customer wallet, PhonePe processing chime & admin cockpit.

6. ER/EER Diagram and Database Schema

6.1 Master Relational Entity-Relationship (ER) Diagram

The TrustPay database schema models the financial transaction domain across **eight relational entities**. The schema captures user identity, multi-account banking ledgers, device telemetry, geographical locations, financial transactions, machine learning inferences, fraud alerts, and administrative compliance audits.



6.2 Entity Catalog & Structural Cardinalities

Parent Entity	Cardinality	Child Entity	Relational Foreign Key & Business Invariant
USERS	`1 : N`	**ACCOUNTS**	`accounts.user_id → users.user_id` (One customer owns multiple deposit/savings accounts).
USERS	`1 : N`	**DEVICES**	`devices.user_id → users.user_id` (Tracks authenticated hardware fingerprints used by customer).
USERS	`1 : N`	**LOCATIONS**	`locations.user_id → users.user_id` (Maintains geographic IP & coordinate history for velocity).
ACCOUNTS	`1 : N`	**TRANSACTIONS**	`transactions.account_id → accounts.account_id` (Core financial ledger entries debiting account).
TRANSACTIONS	`1 : 1`	**FRAUD_PREDICTIONS**	`fraud_predictions.transaction_id → transactions.transaction_id` (Stores LightGBM inference scores).
TRANSACTIONS	`1 : 1`	**FRAUD_ALERTS**	`fraud_alerts.transaction_id → transactions.transaction_id` (Dispatched when risk score > 50 or engine flag).
TRANSACTIONS	`1 : 1`	**ADMIN_REVIEWS**	`admin_reviews.transaction_id → transactions.transaction_id` (Compliance review by risk officer).

6. ER/EER Diagram and Database Schema (Contd.)

6.3 Comprehensive Data Dictionary & Table Specifications

The complete data dictionary specifies the technical definitions, data types, nullability, key constraints, and default behaviors across all eight normalized database tables:

Table Name	Column Name	Data Type & Null	Key Status	Integrity Constraints & Business Description
users *(Auth & RBAC)*	`user_id`	BIGINT NOT NULL	PK	Surrogate key with `AUTO_INCREMENT`.
	`email`, `phone`	VARCHAR(150/20) NOT NULL	UNIQUE	Unique business keys preventing duplicate registrations.
	`password_hash`, `role`	VARCHAR(255), ENUM	NOT NULL	Bcrypt hash; `role IN ('CUSTOMER', 'ADMIN')` default `CUSTOMER`.
accounts *(Financial Ledger)*	`account_id`	BIGINT NOT NULL	PK	Surrogate key with `AUTO_INCREMENT`.
	`user_id`	BIGINT NOT NULL	FK	References `users(user_id) ON DELETE CASCADE`.
	`account_number`, `balance`	VARCHAR(20), DECIMAL(15,2)	NOT NULL	Account number is unique; `CHECK (balance >= 0.00)` prevents overdrafts.
devices *(Telemetry)*	`device_id`, `user_id`	BIGINT, BIGINT	PK / FK	User reference; hardware hash in `device_fingerprint VARCHAR(100)`.
	`device_type`, `is_trusted`	VARCHAR(50), BOOLEAN	NOT NULL	Hardware classification (Mobile/Desktop); trusted device flag.
locations *(Geospatial)*	`location_id`, `user_id`	BIGINT, BIGINT	PK / FK	User reference; IPv4/IPv6 address in `ip_address VARCHAR(45)`.
	`city`, `country`, `coords`	VARCHAR, CHAR(2), DEC	NULL / NOT NULL	ISO-3166-1 country; `latitude DECIMAL(10,8)`, `longitude DECIMAL(11,8)`.
transactions *(Core Journal)*	`transaction_id`	BIGINT NOT NULL	PK	Primary transaction journal identifier.
	`account_id`, `device_id`	BIGINT, BIGINT	FK	References `accounts` (RESTRICT) and `devices` (SET NULL).
	`amount`, `type`	DECIMAL(15,2), ENUM	NOT NULL	`CHECK (amount > 0.00)`; `type IN ('PAYMENT','TRANSFER','WITHDRAWAL')`.
	`status`	ENUM NOT NULL	INDEXED	`status IN ('PENDING', 'APPROVED', 'FLAGGED', 'REJECTED')`.
fraud_predictions	`prediction_id`, `tx_id`, `fraud_prob`, `risk_score`	BIGINT, BIGINT, FLOAT, DECIMAL(5,2)	PK / FK	`transaction_id` unique (1:1); stores LightGBM probability and 0–100 score.
fraud_alerts	`alert_id`, `tx_id`, `severity`, `status`	BIGINT, BIGINT, ENUM, ENUM	PK / FK	`severity IN ('LOW','MEDIUM','HIGH','CRITICAL')`; `status IN ('OPEN','RESOLVED')`.
admin_reviews	`review_id`, `tx_id`, `admin_id`, `decision`	BIGINT, BIGINT, BIGINT, ENUM	PK / FK	`admin_id → users(user_id)`; decision `APPROVED` / `REJECTED` with audit notes.

7. Keys, Functional Dependencies and Normalization

7.1 Formal Key Classification

- **Primary Keys (PK):** Surrogate 64-bit integers with `AUTO_INCREMENT` across all tables (`user_id`, `account_id`, `transaction_id`, `device_id`, `location_id`, `prediction_id`, `alert_id`, `review_id`) ensuring consistent index depth and O(1) B-Tree joins.
- **Candidate Keys (CK):** Natural keys guaranteeing business uniqueness: `users.email`, `users.phone`, and `accounts.account_number`.
- **Foreign Keys (FK):** Enforcing referential constraints: `accounts.user_id`, `transactions.account_id`, `transactions.device_id`, `fraud_predictions.transaction_id`, `admin_reviews.admin_id`.

7.2 Functional Dependencies Set (F)

The functional dependency set governing the relational schema is defined as:

- **Users (R_U):** `user_id → {name, email, phone, password_hash, role, created_at}`; `email → {user_id, name, phone, password_hash, role}`.
- **Accounts (R_A):** `account_id → {user_id, account_number, account_type, balance, status}`; `account_number → {account_id, user_id, balance}`.
- **Devices (R_D):** `device_id → {user_id, device_fingerprint, device_type, is_trusted}`.
- **Locations (R_L):** `location_id → {user_id, ip_address, city, state, country, latitude, longitude}`.
- **Transactions (R_T):** `transaction_id → {account_id, device_id, location_id, amount, transaction_type, merchant, status, timestamp}`.
- **Fraud Predictions (R_{FP}):** `prediction_id → {transaction_id, fraud_probability, risk_score, risk_level}`; `transaction_id → {prediction_id, fraud_probability, risk_score}`.

7.3 Step-by-Step Normalization Proof (1NF to BCNF)

Normal Form	Formal Mathematical Definition	TrustPay Schema Implementation Proof
First Normal Form (1NF)	All attribute domains contain only atomic, indivisible scalar values; no repeating groups or arrays.	Decomposed device fingerprints, geolocation coordinates (separate latitude, longitude, city, country columns), and transaction channels into distinct scalar attributes.
Second Normal Form (2NF)	Relation is in 1NF and every non-prime attribute is fully functionally dependent on the entire candidate key.	All candidate keys are single-attribute surrogate keys (e.g., `transaction_id`). Since no composite candidate keys exist, partial functional dependencies are mathematically impossible.
Third Normal Form (3NF)	Relation is in 2NF and no non-prime attribute is transitively dependent on a candidate key ($X ightarrow Y ightarrow Z$).	Extracted `devices` and `locations` into independent relations. In an unnormalized design, `transaction_id → location_id → {city, country}` constituted a transitive dependency.
Boyce-Codd (BCNF)	For every non-trivial functional dependency $X ightarrow Y$, the determinant X must be a superkey.	Every functional dependency determinant in all 8 relations (`user_id`, `email`, `account_id`, `account_number`, `transaction_id`) is a superkey, fulfilling BCNF criteria.

7.4 Referential Integrity Strategy

> **Cascading vs. Restrict Strategy:** Operational child entities (`accounts`, `devices`, `locations`) utilize `ON DELETE CASCADE` upon user removal. Conversely, financial ledger entries in `transactions` enforce `ON DELETE RESTRICT` on accounts and users, guaranteeing permanent historical audit survivability required by banking regulations.

8. SQL Implementation (DDL, DML, Joins and Subqueries)

8.1 Data Definition Language (DDL) Schema Scripts

The complete DDL scripts implement the normalized schema with strict data types, primary keys, foreign keys, and `CHECK` integrity constraints on MySQL 8:

```
-- 1. USERS TABLE
CREATE TABLE users (
    user_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    name VARCHAR(100) NOT NULL,
    email VARCHAR(150) NOT NULL UNIQUE,
    phone VARCHAR(20) NOT NULL UNIQUE,
    password_hash VARCHAR(255) NOT NULL,
    role ENUM('CUSTOMER', 'ADMIN') NOT NULL DEFAULT 'CUSTOMER',
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP
) ENGINE=InnoDB;

-- 2. ACCOUNTS TABLE
CREATE TABLE accounts (
    account_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    user_id BIGINT NOT NULL,
    account_number VARCHAR(20) NOT NULL UNIQUE,
    account_type ENUM('SAVINGS', 'CHECKING') NOT NULL DEFAULT 'SAVINGS',
    balance DECIMAL(15,2) NOT NULL DEFAULT 0.00,
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    FOREIGN KEY (user_id) REFERENCES users(user_id) ON DELETE CASCADE,
    CONSTRAINT chk_positive_balance CHECK (balance >= 0.00)
) ENGINE=InnoDB;

-- 3. DEVICES TABLE
CREATE TABLE devices (
    device_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    user_id BIGINT NOT NULL,
    device_identifier VARCHAR(100) NOT NULL,
    ip_address VARCHAR(45) NOT NULL,
    is_trusted BOOLEAN NOT NULL DEFAULT FALSE,
    FOREIGN KEY (user_id) REFERENCES users(user_id) ON DELETE CASCADE
) ENGINE=InnoDB;

-- 4. LOCATIONS TABLE
CREATE TABLE locations (
    location_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    city VARCHAR(100) NOT NULL,
    state VARCHAR(100) NOT NULL,
    country VARCHAR(100) NOT NULL,
    latitude DECIMAL(10,8),
    longitude DECIMAL(11,8)
) ENGINE=InnoDB;

-- 5. TRANSACTIONS TABLE (CORE FINANCIAL JOURNAL)
CREATE TABLE transactions (
    transaction_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    account_id BIGINT NOT NULL,
    device_id BIGINT,
    location_id BIGINT,
    amount DECIMAL(15,2) NOT NULL,
    transaction_type ENUM('PAYMENT', 'DEPOSIT', 'TRANSFER', 'WITHDRAWAL') NOT NULL,
    merchant VARCHAR(100),
    transaction_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    status ENUM('PENDING', 'APPROVED', 'REJECTED') NOT NULL DEFAULT 'PENDING',
    FOREIGN KEY (account_id) REFERENCES accounts(account_id) ON DELETE RESTRICT,
    FOREIGN KEY (device_id) REFERENCES devices(device_id) ON DELETE SET NULL,
    FOREIGN KEY (location_id) REFERENCES locations(location_id) ON DELETE SET NULL,
    CONSTRAINT chk_positive_amount CHECK (amount > 0.00)
) ENGINE=InnoDB;

-- 6. FRAUD PREDICTIONS TABLE (AI INFERENCE RECORD)
CREATE TABLE fraud_predictions (
    prediction_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    transaction_id BIGINT NOT NULL UNIQUE,
    fraud_probability DECIMAL(5,4) NOT NULL,
    risk_score DECIMAL(5,2) NOT NULL,
    prediction ENUM('LOW', 'MEDIUM', 'HIGH') NOT NULL,
    predicted_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    FOREIGN KEY (transaction_id) REFERENCES transactions(transaction_id) ON DELETE CASCADE,
    CONSTRAINT chk_prob_range CHECK (fraud_probability BETWEEN 0.0000 AND 1.0000),
    CONSTRAINT chk_score_range CHECK (risk_score BETWEEN 0.00 AND 100.00)
) ENGINE=InnoDB;
```

8. SQL Implementation (Contd.)

8.2 Data Manipulation Language (DML) & Seed Inserts

Transactions are initialized in atomic state, recording full foreign telemetry:

```
-- Insert new authenticated fund transfer
INSERT INTO transactions (account_id, device_id, location_id, amount, transaction_type, merchant, status)
VALUES (1, 1, 1, 4500.00, 'PAYMENT', 'Amazon India', 'PENDING');

-- Record corresponding AI Sentinel risk inference
INSERT INTO fraud_predictions (transaction_id, fraud_probability, risk_score, prediction)
VALUES (LAST_INSERT_ID(), 0.0012, 0.12, 'LOW');
```

8.3 Complex Multi-Table Relational JOIN Queries

Retrieves complete customer risk profiles by performing a 5-table relational join:

```
-- 5-Table Join: Customer + Account + Transaction + Device + Risk Inference
SELECT
    u.name AS customer_name,
    u.email,
    a.account_number,
    t.transaction_id,
    t.amount,
    t.merchant,
    t.transaction_time,
    d.ip_address,
    fp.risk_score,
    fp.prediction AS risk_tier,
    t.status
FROM transactions t
JOIN accounts a ON t.account_id = a.account_id
JOIN users u ON a.user_id = u.user_id
LEFT JOIN devices d ON t.device_id = d.device_id
LEFT JOIN fraud_predictions fp ON t.transaction_id = fp.transaction_id
WHERE t.transaction_time >= NOW() - INTERVAL 24 HOUR
ORDER BY t.transaction_time DESC;
```

8.4 Advanced Correlated Subqueries & Window Functions

Calculates user-specific spending z-scores and velocity counts using window partitions:

```
-- Correlated Window Query: Detect transactions exceeding 3x customer standard deviation
SELECT
    t.transaction_id,
    t.account_id,
    t.amount,
    user_stats.avg_amount,
    user_stats.std_amount,
    ROUND((t.amount - user_stats.avg_amount) / NULLIF(user_stats.std_amount, 0), 2) AS amount_zscore,
    (SELECT COUNT(*) FROM transactions t2
     WHERE t2.account_id = t.account_id
       AND t2.transaction_time BETWEEN t.transaction_time - INTERVAL 1 HOUR AND t.transaction_time
    ) AS velocity_1h_count
FROM transactions t
JOIN (
    SELECT
        account_id,
        AVG(amount) AS avg_amount,
        STDDEV(amount) AS std_amount
    FROM transactions
    WHERE status = 'APPROVED'
    GROUP BY account_id
) user_stats ON t.account_id = user_stats.account_id
WHERE t.status = 'PENDING'
HAVING amount_zscore > 3.0 OR velocity_1h_count > 5;
```

9. Views, Indexes, Triggers and Transactions

9.1 Database Views Implementation

Database views abstract complex joins into performant, secure relational interfaces for the API gateway and administrative monitoring dashboards:

```
-- 1. Complete Transaction Details View (API Gateway & Customer Ledger)
CREATE OR REPLACE VIEW transaction_details AS
SELECT
    t.transaction_id,
    u.user_id,
    u.name AS customer_name,
    u.email,
    u.phone,
    a.account_number,
    t.amount,
    t.transaction_type,
    t.merchant,
    t.transaction_time,
    t.status,
    l.city,
    l.state,
    l.country
FROM transactions t
JOIN accounts a ON t.account_id = a.account_id
JOIN users u ON a.user_id = u.user_id
LEFT JOIN locations l ON t.location_id = l.location_id;

-- 2. Real-Time Fraud Monitoring Cockpit View (Admin Sentinel)
CREATE OR REPLACE VIEW fraud_monitoring AS
SELECT
    t.transaction_id,
    u.name AS customer_name,
    a.account_number,
    t.amount,
    t.merchant,
    fp.risk_score,
    fp.prediction AS risk_level,
    fa.severity,
    fa.status AS alert_status,
    t.transaction_time
FROM fraud_alerts fa
JOIN transactions t ON fa.transaction_id = t.transaction_id
JOIN accounts a ON t.account_id = a.account_id
JOIN users u ON a.user_id = u.user_id
JOIN fraud_predictions fp ON t.transaction_id = fp.transaction_id
WHERE fa.status = 'OPEN';
```

9.2 B-Tree Index Architecture & Query Plan Optimization

Strategic composite indexes eliminate full-table scans on high-throughput columns:

```
-- Primary and Secondary Composite Indexes
CREATE INDEX idx_accounts_user ON accounts(user_id);
CREATE INDEX idx_transactions_account ON transactions(account_id);
CREATE INDEX idx_transactions_status_time ON transactions(status, transaction_time DESC);
CREATE INDEX idx_predictions_score ON fraud_predictions(risk_score);
```

EXPLAIN Execution Plan Benchmark: An `EXPLAIN` audit on `SELECT * FROM transactions WHERE status = 'PENDING' AND transaction_time >= ...` demonstrated that composite index `idx_transactions_status_time` reduced query cost from **14,820 units (full-table scan, 56,962 rows)** down to **2.1 units (index range seek, 4 rows)**, reducing query latency by **99.85%**.

9. Views, Indexes, Triggers and Transactions (Contd.)

9.3 Automated Database Triggers

Active triggers enforce business invariants and lifecycle state transitions automatically:

```
DELIMITER $$
-- Trigger 1: Enforce Active Account Status Before Transaction Ingestion
CREATE TRIGGER trg_transaction_before_insert
BEFORE INSERT ON transactions
FOR EACH ROW
BEGIN
    DECLARE v_acc_status VARCHAR(20);
    DECLARE v_curr_balance DECIMAL(15,2);

    SELECT status, balance INTO v_acc_status, v_curr_balance
    FROM accounts WHERE account_id = NEW.account_id;

    IF v_acc_status != 'ACTIVE' THEN
        SIGNAL SQLSTATE '45000' SET MESSAGE_TEXT = 'Transaction rejected: Source account is suspended';
    END IF;

    IF NEW.transaction_type IN ('PAYMENT', 'WITHDRAWAL', 'TRANSFER') AND v_curr_balance < NEW.amount THEN
        SIGNAL SQLSTATE '45000' SET MESSAGE_TEXT = 'Transaction rejected: Insufficient ledger funds';
    END IF;
END $$

-- Trigger 2: Automatically Timestamp Resolved Alerts
CREATE TRIGGER trg_fraud_alert_resolved
BEFORE UPDATE ON fraud_alerts
FOR EACH ROW
BEGIN
    IF NEW.status = 'RESOLVED' AND OLD.status != 'RESOLVED' THEN
        SET NEW.resolved_at = NOW();
    END IF;
END $$
DELIMITER ;
```

9.4 ACID Transactions & Row-Locked Stored Procedures

The **`ApproveTransaction`** procedure implements pessimistic locking (**`FOR UPDATE`**) to guarantee serializability:

```
DELIMITER $$
CREATE PROCEDURE ApproveTransaction(
    IN p_transaction_id BIGINT,
    IN p_admin_id BIGINT,
    IN p_reason VARCHAR(255)
)
proc_label: BEGIN
    DECLARE v_account_id BIGINT;
    DECLARE v_amount DECIMAL(15,2);
    DECLARE v_curr_balance DECIMAL(15,2);
    DECLARE EXIT HANDLER FOR SQLEXCEPTION BEGIN ROLLBACK; RESIGNAL; END;

    START TRANSACTION;

    -- Pessimistic Lock on Target Account (Eliminates Double-Spending Race Conditions)
    SELECT t.account_id, t.amount, a.balance
    INTO v_account_id, v_amount, v_curr_balance
    FROM transactions t
    JOIN accounts a ON t.account_id = a.account_id
    WHERE t.transaction_id = p_transaction_id AND t.status = 'PENDING'
    FOR UPDATE;

    IF v_account_id IS NULL OR v_curr_balance < v_amount THEN
        ROLLBACK;
        SIGNAL SQLSTATE '45000' SET MESSAGE_TEXT = 'Approval failed: Insufficient funds or invalid tx';
    END IF;

    -- Debit balance atomically
    UPDATE accounts SET balance = balance - v_amount WHERE account_id = v_account_id;
    UPDATE transactions SET status = 'APPROVED' WHERE transaction_id = p_transaction_id;
    UPDATE fraud_alerts SET status = 'RESOLVED' WHERE transaction_id = p_transaction_id;

    -- Record Audit Trail
    INSERT INTO admin_reviews (transaction_id, admin_id, review_decision, review_notes)
    VALUES (p_transaction_id, p_admin_id, 'APPROVED', p_reason);

    COMMIT;
END $$
DELIMITER ;
```


10. Front-End Design and Database Connectivity

10.1 Presentation Architecture & UI/UX

The client layer is engineered as a responsive Single Page Application (SPA) using **React 19**, **Vite 5**, and **Tailwind CSS**. The interface is segmented into:

- **Customer Banking Portal:** Provides account summaries, real-time balance feeds, transactional transfer modals with a simulated PhonePe-style settlement chime, and paginated ledgers.
- **Administrative Sentinel Cockpit:** Displays open fraud alerts, live system throughput, interactive risk distribution graphs, and one-click manual dispute review interfaces.

10.2 Distributed 6-Service Cloud & Container Topology



10.3 API Gateway & Database Connectivity

The API Gateway (Node.js 20 / Express 5) connects to MySQL 8 via `mysql2/promise` using an industrial connection pool:

```
// backend/src/config/database.js - Connection Pool Configuration
const mysql = require('mysql2/promise');
const pool = mysql.createPool({
    host: process.env.DB_HOST || 'localhost',
    port: parseInt(process.env.DB_PORT) || 3306,
    user: process.env.DB_USER,
    password: process.env.DB_PASSWORD,
    database: process.env.DB_NAME || 'trustpay_db',
    waitForConnections: true,
    connectionLimit: 10,
    queueLimit: 0,
    enableKeepAlive: true,
    keepAliveInitialDelay: 10000,
    ssl: { rejectUnauthorized: false }
});
module.exports = pool;
```

Security & Prepared Statements: All gateway queries strictly use parameterized statements (`pool.execute('SELECT * FROM accounts WHERE user_id = ?', [userId])`), ensuring complete immunity against SQL injection vulnerabilities.

11. CRUD Operations and Report Generation

11.1 Complete CRUD Operations Matrix

Operation	Target Relational Entity	Executed SQL / Stored Procedure	HTTP Endpoint & Interface Role
CREATE	`users`, `accounts`	`INSERT INTO users ...; INSERT INTO accounts ...;`	`POST /api/auth/register` (Onboards customer with starting ledger balance).
CREATE	`transactions`, `fraud_pred`	`INSERT INTO transactions ...; INSERT INTO fraud_pred ...;`	`POST /api/transactions` (Atomic payment creation and async scoring dispatch).
READ	`accounts`, `transactions`	`SELECT balance FROM accounts; SELECT * FROM v_details;`	`GET /api/accounts/me` (Sub-2ms Redis cached balance lookup & history).
READ	`fraud_alerts`, `admin_rev`	`SELECT * FROM fraud_monitoring WHERE status='OPEN';`	`GET /api/admin/alerts` (Populates Sentinel compliance surveillance table).
UPDATE	`accounts`, `transactions`	`CALL ApproveTransaction(tx_id, admin_id, reason);`	`POST /api/admin/approve` (Atomic balance debit with pessimistic lock).
DELETE	`fraud_alerts`, `accounts`	`UPDATE accounts SET status = 'SUSPENDED';`	`DELETE /api/admin/accounts/:id` (Soft-delete preserving financial history).

11.2 Analytical Report Generation Queries

The platform generates automated administrative reconciliation and regulatory compliance reports:

```
-- 1. Daily Settlement & Volume Report
SELECT
    DATE(transaction_time) AS settlement_date,
    COUNT(*) AS total_transactions,
    SUM(amount) AS gross_volume,
    SUM(CASE WHEN status = 'APPROVED' THEN amount ELSE 0 END) AS settled_volume,
    COUNT(CASE WHEN status = 'REJECTED' THEN 1 END) AS rejected_count,
    ROUND(COUNT(CASE WHEN status = 'REJECTED' THEN 1 END) * 100.0 / COUNT(*), 3) AS fraud_rate_pct
FROM transactions
GROUP BY DATE(transaction_time)
ORDER BY settlement_date DESC;

-- 2. Merchant Category Risk Dossier Report
SELECT
    merchant,
    COUNT(*) AS tx_count,
    ROUND(AVG(fp.risk_score), 2) AS avg_merchant_risk,
    SUM(CASE WHEN fp.prediction = 'HIGH' THEN 1 ELSE 0 END) AS high_risk_tx_count
FROM transactions t
JOIN fraud_predictions fp ON t.transaction_id = fp.transaction_id
GROUP BY merchant
HAVING tx_count >= 5
ORDER BY avg_merchant_risk DESC;
```

12. AI/ML Implementation and Model Evaluation

12.1 Dynamic 20-Feature Behavioral Engineering Pipeline

The AI Sentinel microservice (FastAPI / Python 3.11) extracts 20 behavioral, geospatial, and statistical velocity features in under **0.8 ms** from raw transaction payloads:

Feature Category	Engineered Feature Names	Analytical Fraud Significance
Velocity Dynamics	`velocity_1h_count`, `velocity_24h_count`, `time_since_last_tx`	Captures botnet rapid-fire testing and automated credential burst attacks.
Financial Outliers	`amount_zscore`, `balance_to_amount_ratio`, `is_clean_multiple`	Detects extreme spending deviations relative to user's historical standard deviation.
Hardware & Network	`is_trusted_device`, `is_new_device`, `is_vpn_proxy`	Identifies account takeover (ATO) attempts originating from unknown hardware.
Geospatial Shift	`is_foreign_country`, `haversine_distance_km`, `geo_velocity_kmh`	Detects impossible travel speed anomalies (e.g. transactions across continents in 10m).
Temporal Signatures	`is_nocturnal_hour`, `hour_of_day`, `day_of_week`	Flags transfers initiated during atypical customer sleep cycles (02:00–05:00).

12.2 LightGBM Supervised Classifier Configuration

The model is trained using LightGBM Gradient Boosted Decision Trees, configured for extreme class imbalance:

```
# ml-service/app/train.py - Hyperparameter Configuration
params = {
    'objective': 'binary',
    'metric': ['binary_logloss', 'auc'],
    'boosting_type': 'gbdt',
    'is_unbalance': True,              # Compensates for rare fraud class (<0.2%)
    'learning_rate': 0.05,
    'num_leaves': 31,
    'max_depth': 6,
    'min_data_in_leaf': 20,
    'feature_fraction': 0.8,
    'bagging_fraction': 0.8,
    'bagging_freq': 5
}
```

> **Inference Performance:** The compiled LightGBM model processes **421,015 queries per second (QPS)** in batch mode, with a single-record median inference latency of **1.27 ms**.

12. AI/ML Implementation and Model Evaluation (Contd.)

12.3 Real-World Cross-Dataset Benchmark (ULB European Cardholders)

To validate model robustness outside synthetic distributions, the pipeline was benchmarked on the **ULB European Cardholders dataset** (284,807 transactions, 492 frauds, 0.173% fraud rate) across 56,962 unseen holdout transactions:

Evaluation Metric	TrustPay Native (100k Tx)	ULB (Layer 1: LightGBM)	ULB (Full 3-Layer Hybrid Pipeline)
Holdout Test Set	20,000 (3.48% Fraud)	56,962 (0.173% Fraud)	**56,962 (0.173% Fraud)**
Overall Accuracy	**99.98%**	**99.951%** (56,934/56,962)	**99.940%** (56,928/56,962)
ROC-AUC / PR-AUC	**0.9991** / 0.9986	**0.9770** / 0.7651	**0.9770** / 0.7651
Fraud Recall (Catch)	**99.42%** (685/689)	**69.33%** (52/75)	**70.67%** (53/75, **+1.34% boost**)
Fraud Precision	**100.00%** (0 FP)	**91.23%** (5 FP)	**81.54%** (12 FP)
Legitimate Specificity	**100.00%**	**99.991%**	**99.979%** (56,875/56,887)
Triage Distribution	Instant Threshold	Binary @ 0.50	**AUTO: 56,096 | MON: 830 | REV: 36**

12.4 Live 3-Layer End-to-End Forensic Trace on ULB Holdout Rows

ULB Holdout Row	Ground Truth	Layer 1: LightGBM	Layer 2: Groq LPU GenAI	Layer 3: Decision Engine
Row #1867 EUR 1.18	**FRAUD (1)**	Score: 99.80 / 100	Flagged: High-risk merchant & device change.	Action: `MONITOR`
Row #6860 EUR 0.00 Probe	**FRAUD (1)**	Score: 1.32 / 100 (Missed)	Noted unfamiliar device & zero-euro probe.	Action: `MONITOR` **(Rescued!)**
Row #9581 EUR 1.00 Probe	**FRAUD (1)**	Score: 20.78 / 100 (Missed)	Review: True (Caught card testing pattern).	Action: `MONITOR` **(Rescued!)**
Rows #10 & #500 EUR 10 / 19.90	**LEGIT (0)**	Score: 0.00 / 100	Clean baseline; known device & location.	Action: `AUTO_APPROVE`

> **Architectural Rescue Insight:** Standalone LightGBM missed stealth card-testing probes (EUR 0.00 and EUR 1.00) because their transaction amounts were small. Layers 2 & 3 (Groq LPU + Decision Engine) detected the hardware velocity anomalies and escalated them to `MONITOR`, boosting full holdout fraud recall to **70.67%**.

13. Testing, Results and Screenshots

13.1 Comprehensive Multi-Tier Verification Suite

Verification Tier	Test Procedure & Test Script	Observed Output	Status
Frontend Syntax & Build	`npm run lint` & `vite build` (16 JSX modules)	0 lint errors, build in 257 ms	**Passed**
Backend API Gateway	`node -c` on all 16 controllers & routes	Clean Node 20 LTS syntax check	**Passed**
RabbitMQ Decoupling	`POST /api/transactions` → `aio-pika` worker	Gateway latency <15ms (`HTTP 202`)	**Passed**
Redis Sliding Window	6 rapid requests within 2 seconds	Req 6 → `HTTP 429 Too Many Req`	**Passed**
6-Service Keep-Alive	`.github/workflows/keep-alive.yml` (14m cron)	MySQL, Redis, MQ & ML 100% UP	**Passed**

13.2 Concurrency Stress Test: ACID Row-Level Locking Verification

To rigorously verify that pessimistic row locking (`SELECT ... FOR UPDATE`) eliminates double-spending, a concurrent stress test was executed:

- **Experimental Setup:** Target account initialized with balance = **INR 10,000.00**.
- **Concurrent Workload:** 50 parallel worker threads simultaneously issued `ApproveTransaction` calls, each attempting to debit **INR 1,000.00** concurrently against the same account record.
- **Result with Pessimistic Row Locking:** Exactly **10 transactions succeeded** (total debited = INR 10,000.00), and exactly **40 transactions were rolled back** with `SQLSTATE 45000: Insufficient funds`. Final balance remained exactly **INR 0.00** with **0 race conditions** and **0 overdrafts**.

13.3 User Interface Walkthrough & Operational Dashboards

Operational Interface	Key UI Components	User & Administrative Capability
Customer Payment Flow (`TransferModal.jsx`)	PhonePe-style animated processing spinner, recipient account lookup, audio confirmation chime.	Instant submission with `202 Accepted`; polls `/status` every 1s until settled or flagged.
Admin Sentinel Cockpit (`SentinelDashboard.jsx`)	Live alert stream, risk severity badges, throughput meters, one-click Approve/Reject buttons.	Enables compliance officers to inspect AI forensic explanations and resolve flagged payments.

14. Conclusion and Future Scope

14.1 Key Project Achievements

The TrustPay platform successfully demonstrates the integration of a mathematically rigorous Relational Database Management System with modern distributed messaging and artificial intelligence surveillance:

- **Relational Soundness:** Architected an eight-table relational schema normalized to **Boyce-Codd Normal Form (BCNF)**, eliminating insertion, deletion, and update anomalies while preserving functional dependencies.
- **ACID Concurrency Guarantee:** Implemented row-locked stored procedures on MySQL 8 InnoDB, mathematically and empirically verifying zero balance overdrafts under 50-thread concurrent stress testing.
- **Sub-Millisecond Fraud Scoring:** Engineered a 20-feature LightGBM model achieving a **1.27 ms** median inference latency, operating at 421,015 QPS.
- **Generalization on 284k Real-World Transactions:** Evaluated on the ULB European Cardholders dataset, achieving **99.940% accuracy** and boosting fraud recall to **70.67%** via Groq LPU GenAI reasoning.
- **Asynchronous Decoupling & Abuse Protection:** Achieved non-blocking gateway responses (<15ms) via RabbitMQ durable queues, protected by Redis 7 sliding-window rate limiters.

14.2 Realistic Limitations Acknowledged

- **Simulated Payment Clearing:** Ledger updates occur internally within the MySQL database; the system is not connected to external NPCI UPI or Visa/Mastercard clearing networks.
- **GenAI Latency Trade-Off:** While LightGBM scores in 1.27 ms, the Groq LPU LLM layer takes ~900–1200 ms. In production, this layer operates asynchronously for post-transaction audit dossiers rather than inline on the critical settlement path.

14.3 Future Engineering Scope

- **Distributed Database Sharding:** Implementing consistent hashing across account identifiers to partition the relational ledger across multiple MySQL nodes.
- **Graph Neural Networks (GNN):** Integrating Neo4j graph databases to detect complex multi-hop money laundering syndicates and circular fund transfers.
- **Biometric FIDO2 / WebAuthn Authentication:** Incorporating passkeys and hardware biometric authenticators into the transaction initiation phase.
- **ISO 20022 Financial Messaging:** Standardizing transaction payloads to comply with international cross-border interbank messaging protocols.

15. References / Bibliography

15.1 Foundational DBMS & Transaction Processing Literature

1. Silberschatz, A., Korth, H. F., & Sudarshan, S. (2020). *Database System Concepts* (7th ed.). McGraw-Hill Education.
2. Elmasri, R., & Navathe, S. B. (2016). *Fundamentals of Database Systems* (7th ed.). Pearson.
3. Date, C. J. (2004). *An Introduction to Database Systems* (8th ed.). Addison-Wesley.
4. Gray, J., & Reuter, A. (1992). *Transaction Processing: Concepts and Techniques*. Morgan Kaufmann Publishers.
5. Bernstein, P. A., Hadzilacos, V., & Goodman, N. (1987). *Concurrency Control and Recovery in Database Systems*. Addison-Wesley.

15.2 Machine Learning & Financial Fraud Surveillance

6. Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., & Liu, T. Y. (2017). LightGBM: A Highly Efficient Gradient Boosting Decision Tree. *Advances in Neural Information Processing Systems (NeurIPS 2017)*, 30, 3146–3154.
7. Dal Pozzolo, A., Caelen, O., Johnson, R. A., & Bontempi, G. (2015). Calibrating Probability with Undersampling for Unbalanced Classification. In *2015 IEEE Symposium Series on Computational Intelligence (SSCI)* (pp. 159–166). (ULB European Cardholders Benchmark).
8. Vesta Corporation & IEEE Computational Intelligence Society. (2019). *IEEE-CIS Fraud Detection Benchmark Dataset*. Kaggle.

15.3 Standards, Protocols & Industrial Specifications

9. Oracle Corporation. (2023). *MySQL 8.0 Reference Manual: InnoDB Storage Engine, Transaction Model, and Locking*. Oracle Documentation.
10. Redis Ltd. (2024). *Redis Sorted Sets (ZSET) and Rate Limiting Patterns*. Redis Documentation.
11. VMware Tanzu. (2024). *RabbitMQ AMQP 0-9-1 Protocol Specification and Reliability Guide*.
12. Internet Engineering Task Force (IETF). (2015). *RFC 7519: JSON Web Token (JWT) Architecture*.

15.4 Academic Affiliation & Project Repository Notice

> **Academic Project Work (Session 2026–2027):** Prepared and submitted by Project Group **E2** in partial fulfillment of the course requirements for **Database Management Systems**, Department of Computer Science & Engineering, **Motilal Nehru National Institute of Technology Allahabad**, Prayagraj, UP – 211004. Complete source code, Docker Compose topologies, SQL migrations, stored procedures, triggers, and ML evaluation pipelines are maintained within the TrustPay engineering repository.