RAJALAKSHMI ENGINEERING COLLEGE

Rama Raghavi T 250701582-2025-CSE

R2

Started on	Sunday, 30 August 2026, 8:15 PM
State	Finished
Completed on	Sunday, 30 August 2026, 8:19 PM
Time taken	3 mins 45 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

// Function using Boyer-Moore Majority Voting Algorithm
int majorityElement(int* nums, int numsSize) {
    int candidate = 0;
    int count = 0;

    for (int i = 0; i < numsSize; i++) {
        if (count == 0) {
            candidate = nums[i];
        }
        if (nums[i] == candidate) {
            count++;
        } else {
            count--;
        }
    }

    return candidate;
}

int main() {
    int n;

    // Read the size of the array
    while (scanf("%d", &n) == 1) {
        int* nums = (int*)malloc(n * sizeof(int));
        if (nums == NULL) {
            return 1;
        }

        // Read the n elements of the array
        for (int i = 0; i < n; i++) {
```

```
35              scanf("%d", &nums[i]);
36          }
37
38          // Compute and print the result
39          printf("%d\n", majorityElement(nums, n));
40
41          // Free memory for the current test case
42          free(nums);
43      }
44
45      return 0;
46  }
47
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course