

CSA0503-DATABASE MANAGEMENT SYSTEMS

EXPERIMENT 18 - HIGH LEVEL LANGUAGE EXTENSION WITH CURSORS

1)

```
mysql> CREATE PROCEDURE build_email_list(
->     INOUT email_list VARCHAR(4000)
-> )
-> BEGIN
->     DECLARE v_finished INT DEFAULT 0;
->     DECLARE v_email VARCHAR(100) DEFAULT '';
->
->     -- Declare cursor
->     DECLARE email_cursor CURSOR FOR
->         SELECT email FROM employees;
->
->     -- Handler for end of cursor
->     DECLARE CONTINUE HANDLER FOR NOT FOUND
->         SET v_finished = 1;
->
->     -- Open cursor
->     OPEN email_cursor;
->
->     -- Fetch each email
->     get_email: LOOP
->
->         FETCH email_cursor INTO v_email;
->
->         -- Check whether all rows are fetched
->         IF v_finished = 1 THEN
->             LEAVE get_email;
->         END IF;
->
->         -- Build email list
->         SET email_list = CONCAT(email_list, v_email, ';');
->
->     END LOOP get_email;
->
->     -- Close cursor
->     CLOSE email_cursor;
->
-> END$$
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> -- Call the procedure
mysql> SET @email_list = '';
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> CALL build_email_list(@email_list);
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> -- Display email list
mysql> SELECT @email_list AS Email_List;
+-----+
| Email_List |
+-----+
| pharry@warnerbros.com;kclark@dccomics.com;stony@marvel.com; |
+-----+
1 row in set (0.00 sec)
```

RESULT:

Thus the Cursor program using MySQL is executed successfully