Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

RTX series packaged rooftop units, cooling, extended performance (SI)

Model	Nominal	Rated airflow (L/s)	AHRI rated gross TC / SHC (kW)
RTX-030	3	600	10.5 / 8.3
RTX-035	3.5	700	12.3 / 9.7
RTX-040	4	800	14.0 / 11.1
RTX-045	4.5	900	15.8 / 12.5
RTX-050	5	1000	17.5 / 13.8
RTX-055	5.5	1100	19.3 / 15.2
RTX-060	6	1200	21.0 / 16.6
RTX-070	7	1400	24.5 / 19.4
RTX-080	8	1600	28.0 / 22.1
RTX-090	9	1800	31.5 / 24.9
RTX-100	10	2000	35.0 / 27.7
RTX-110	11	2200	38.5 / 30.4
RTX-125	12.5	2500	43.8 / 34.6
RTX-140	14	2800	49.0 / 38.7
RTX-150	15	3000	52.5 / 41.5

Notes

1. TC = gross total capacity, SHC = gross sensible capacity, kW. Capacities are gross: they include no deduction for indoor fan motor heat. Motor heat is listed with each airflow, at 125 Pa external static pressure.
2. SHC is based on 26.7 C entering dry bulb. At other entering dry bulb temperatures, SHC = SHC(table) + 1.23 x (1 - BF) x airflow (L/s) x (EDB - 26.7) / 1000 kW, with BF the coil bypass factor listed with each airflow.
3. Where the corrected SHC exceeds TC, the coil is dry: use SHC = TC.
4. Interpolation within the tables is permissible. Do not extrapolate.
5. AHRI 340/360 rating conditions: 35.0 C outdoor, 26.7 C DB / 19.4 C WB entering, rated airflow.
6. Indoor fan arrangement: draw-through (fan downstream of the evaporator coil).
7. kW (input) = compressor and outdoor fan power.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-030, nominal 3 tons, rated airflow 600 L/s

Airflow 450 L/s, bypass factor BF 0.076, indoor fan motor heat 0.26 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	8.7	8.7 2.86	9.7	8.7 2.89	10.7	7.8 2.92	11.7	6.6 2.96
35.0	8.2	8.2 3.07	9.2	8.3 3.10	10.1	7.5 3.13	11.1	6.3 3.17
40.6	7.8	7.8 3.27	8.7	7.8 3.31	9.6	7.1 3.34	10.5	6.0 3.38
46.1	7.4	7.4 3.47	8.3	7.4 3.51	9.1	6.7 3.55	10.0	5.7 3.59

Airflow 600 L/s, bypass factor BF 0.090, indoor fan motor heat 0.49 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	9.0	9.0 2.86	10.0	9.5 2.89	11.0	8.7 2.92	12.1	7.5 2.96
35.0	8.5	8.5 3.07	9.5	9.1 3.10	10.5	8.3 3.13	11.5	7.2 3.17
40.6	8.1	8.1 3.27	9.0	8.6 3.31	10.0	7.9 3.34	10.9	6.8 3.38
46.1	7.7	7.7 3.47	8.6	8.2 3.51	9.4	7.4 3.55	10.3	6.4 3.59

Airflow 750 L/s, bypass factor BF 0.103, indoor fan motor heat 0.80 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	9.2	9.2 2.86	10.3	10.3 2.89	11.3	9.6 2.92	12.4	8.4 2.96
35.0	8.8	8.8 3.07	9.8	9.8 3.10	10.8	9.1 3.13	11.8	8.0 3.17
40.6	8.3	8.3 3.27	9.3	9.3 3.31	10.2	8.6 3.34	11.2	7.6 3.38
46.1	7.9	7.9 3.47	8.8	8.8 3.51	9.7	8.2 3.55	10.6	7.2 3.59

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-035, nominal 3.5 tons, rated airflow 700 L/s

Airflow 525 L/s, bypass factor BF 0.076, indoor fan motor heat 0.31 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	10.2	10.2 3.35	11.3	10.2 3.39	12.5	9.2 3.42	13.7	7.8 3.46
35.0	9.7	9.7 3.59	10.8	9.7 3.63	11.9	8.7 3.67	13.0	7.4 3.71
40.6	9.2	9.2 3.83	10.2	9.2 3.88	11.3	8.3 3.92	12.3	7.0 3.96
46.1	8.7	8.7 4.07	9.7	8.7 4.12	10.7	7.8 4.16	11.7	6.6 4.21

Airflow 700 L/s, bypass factor BF 0.090, indoor fan motor heat 0.58 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	10.5	10.5 3.35	11.7	11.2 3.39	12.9	10.2 3.42	14.2	8.8 3.46
35.0	10.0	10.0 3.59	11.2	10.6 3.63	12.3	9.7 3.67	13.5	8.4 3.71
40.6	9.5	9.5 3.83	10.6	10.1 3.88	11.7	9.2 3.92	12.8	7.9 3.96
46.1	9.0	9.0 4.07	10.0	9.5 4.12	11.0	8.7 4.16	12.1	7.5 4.21

Airflow 875 L/s, bypass factor BF 0.103, indoor fan motor heat 0.95 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	10.8	10.8 3.35	12.1	12.1 3.39	13.3	11.2 3.42	14.5	9.8 3.46
35.0	10.3	10.3 3.59	11.5	11.5 3.63	12.6	10.7 3.67	13.8	9.4 3.71
40.6	9.7	9.7 3.83	10.9	10.9 3.88	12.0	10.1 3.92	13.1	8.9 3.96
46.1	9.2	9.2 4.07	10.3	10.3 4.12	11.3	9.6 4.16	12.4	8.4 4.21

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-040, nominal 4 tons, rated airflow 800 L/s

Airflow 600 L/s, bypass factor BF 0.076, indoor fan motor heat 0.35 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	11.6	11.6 3.81	12.9	11.6 3.86	14.2	10.5 3.90	15.6	8.8 3.94
35.0	11.0	11.0 4.09	12.3	11.0 4.13	13.5	9.9 4.18	14.8	8.4 4.23
40.6	10.4	10.4 4.36	11.7	10.5 4.41	12.8	9.4 4.46	14.0	8.0 4.51
46.1	9.9	9.9 4.63	11.0	9.9 4.68	12.1	8.9 4.74	13.3	7.5 4.79

Airflow 800 L/s, bypass factor BF 0.090, indoor fan motor heat 0.66 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	12.0	12.0 3.81	13.4	12.7 3.86	14.7	11.6 3.90	16.1	10.0 3.94
35.0	11.4	11.4 4.09	12.7	12.1 4.13	14.0	11.1 4.18	15.3	9.5 4.23
40.6	10.8	10.8 4.36	12.1	11.5 4.41	13.3	10.5 4.46	14.5	9.0 4.51
46.1	10.2	10.2 4.63	11.4	10.9 4.68	12.6	9.9 4.74	13.8	8.6 4.79

Airflow 1000 L/s, bypass factor BF 0.103, indoor fan motor heat 1.08 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	12.3	12.3 3.81	13.7	13.7 3.86	15.1	12.8 3.90	16.6	11.2 3.94
35.0	11.7	11.7 4.09	13.1	13.1 4.13	14.4	12.2 4.18	15.7	10.7 4.23
40.6	11.1	11.1 4.36	12.4	12.4 4.41	13.6	11.5 4.46	14.9	10.1 4.51
46.1	10.5	10.5 4.63	11.7	11.7 4.68	12.9	10.9 4.74	14.1	9.6 4.79

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-045, nominal 4.5 tons, rated airflow 900 L/s

Airflow 675 L/s, bypass factor BF 0.076, indoor fan motor heat 0.39 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	13.0	13.0 4.30	14.6	13.1 4.35	16.1	11.8 4.40	17.6	10.0 4.45
35.0	12.4	12.4 4.61	13.9	12.4 4.67	15.3	11.2 4.72	16.7	9.5 4.77
40.6	11.8	11.8 4.92	13.1	11.8 4.98	14.5	10.6 5.03	15.9	9.0 5.09
46.1	11.1	11.1 5.23	12.4	11.2 5.29	13.7	10.1 5.34	15.0	8.5 5.40

Airflow 900 L/s, bypass factor BF 0.090, indoor fan motor heat 0.74 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	13.5	13.5 4.30	15.1	14.4 4.35	16.6	13.1 4.40	18.2	11.3 4.45
35.0	12.8	12.8 4.61	14.3	13.7 4.67	15.8	12.5 4.72	17.3	10.8 4.77
40.6	12.2	12.2 4.92	13.6	13.0 4.98	15.0	11.8 5.03	16.4	10.2 5.09
46.1	11.5	11.5 5.23	12.9	12.3 5.29	14.2	11.2 5.34	15.5	9.7 5.40

Airflow 1125 L/s, bypass factor BF 0.103, indoor fan motor heat 1.21 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	13.9	13.9 4.30	15.5	15.5 4.35	17.1	14.4 4.40	18.7	12.7 4.45
35.0	13.2	13.2 4.61	14.7	14.7 4.67	16.2	13.7 4.72	17.8	12.0 4.77
40.6	12.5	12.5 4.92	14.0	14.0 4.98	15.4	13.0 5.03	16.9	11.4 5.09
46.1	11.8	11.8 5.23	13.2	13.2 5.29	14.6	12.3 5.34	16.0	10.8 5.40

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-050, nominal 5 tons, rated airflow 1000 L/s

Airflow 750 L/s, bypass factor BF 0.076, indoor fan motor heat 0.44 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	14.5	14.5 4.77	16.1	14.5 4.82	17.8	13.1 4.87	19.5	11.0 4.93
35.0	13.7	13.7 5.11	15.4	13.8 5.17	16.9	12.4 5.22	18.5	10.5 5.28
40.6	13.0	13.0 5.45	14.6	13.1 5.51	16.0	11.8 5.57	17.6	10.0 5.64
46.1	12.3	12.3 5.79	13.8	12.4 5.86	15.2	11.2 5.92	16.6	9.4 5.99

Airflow 1000 L/s, bypass factor BF 0.090, indoor fan motor heat 0.83 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	15.0	15.0 4.77	16.7	15.9 4.82	18.4	14.5 4.87	20.2	12.5 4.93
35.0	14.2	14.2 5.11	15.9	15.1 5.17	17.5	13.8 5.22	19.2	11.9 5.28
40.6	13.5	13.5 5.45	15.1	14.4 5.51	16.6	13.1 5.57	18.2	11.3 5.64
46.1	12.8	12.8 5.79	14.3	13.6 5.86	15.7	12.4 5.92	17.2	10.7 5.99

Airflow 1250 L/s, bypass factor BF 0.103, indoor fan motor heat 1.36 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	15.4	15.4 4.77	17.2	17.2 4.82	18.9	16.0 4.87	20.7	14.0 4.93
35.0	14.6	14.6 5.11	16.3	16.3 5.17	18.0	15.2 5.22	19.7	13.3 5.28
40.6	13.9	13.9 5.45	15.5	15.5 5.51	17.0	14.4 5.57	18.7	12.6 5.64
46.1	13.1	13.1 5.79	14.7	14.7 5.86	16.1	13.6 5.92	17.7	12.0 5.99

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-055, nominal 5.5 tons, rated airflow 1100 L/s

Airflow 825 L/s, bypass factor BF 0.076, indoor fan motor heat 0.48 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	15.9	15.9 5.26	17.8	16.0 5.32	19.6	14.4 5.37	21.5	12.2 5.43
35.0	15.2	15.2 5.63	16.9	15.2 5.70	18.6	13.7 5.76	20.4	11.6 5.83
40.6	14.4	14.4 6.01	16.1	14.4 6.08	17.7	13.0 6.15	19.4	11.0 6.22
46.1	13.6	13.6 6.38	15.2	13.6 6.46	16.7	12.3 6.53	18.3	10.4 6.60

Airflow 1100 L/s, bypass factor BF 0.090, indoor fan motor heat 0.91 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	16.5	16.5 5.26	18.4	17.5 5.32	20.3	16.0 5.37	22.2	13.8 5.43
35.0	15.7	15.7 5.63	17.5	16.7 5.70	19.3	15.2 5.76	21.1	13.1 5.83
40.6	14.9	14.9 6.01	16.6	15.8 6.08	18.3	14.5 6.15	20.0	12.5 6.22
46.1	14.1	14.1 6.38	15.7	15.0 6.46	17.3	13.7 6.53	19.0	11.8 6.60

Airflow 1375 L/s, bypass factor BF 0.103, indoor fan motor heat 1.49 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	16.9	16.9 5.26	18.9	18.9 5.32	20.8	17.6 5.37	22.8	15.5 5.43
35.0	16.1	16.1 5.63	18.0	18.0 5.70	19.8	16.8 5.76	21.7	14.7 5.83
40.6	15.3	15.3 6.01	17.1	17.1 6.08	18.8	15.9 6.15	20.6	13.9 6.22
46.1	14.5	14.5 6.38	16.2	16.2 6.46	17.8	15.0 6.53	19.5	13.2 6.60

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-060, nominal 6 tons, rated airflow 1200 L/s

Airflow 900 L/s, bypass factor BF 0.084, indoor fan motor heat 0.53 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	17.3	17.3 5.72	19.4	17.4 5.78	21.3	15.7 5.85	23.4	13.2 5.91
35.0	16.5	16.5 6.13	18.4	16.5 6.20	20.3	14.9 6.27	22.2	12.6 6.34
40.6	15.6	15.6 6.54	17.5	15.7 6.62	19.2	14.1 6.69	21.1	11.9 6.76
46.1	14.8	14.8 6.95	16.5	14.8 7.03	18.2	13.4 7.10	19.9	11.3 7.18

Airflow 1200 L/s, bypass factor BF 0.100, indoor fan motor heat 0.99 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	18.0	18.0 5.72	20.1	19.1 5.78	22.1	17.4 5.85	24.2	15.0 5.91
35.0	17.1	17.1 6.13	19.1	18.2 6.20	21.0	16.6 6.27	23.0	14.3 6.34
40.6	16.2	16.2 6.54	18.1	17.2 6.62	19.9	15.7 6.69	21.8	13.6 6.76
46.1	15.3	15.3 6.95	17.1	16.3 7.03	18.9	14.9 7.10	20.7	12.8 7.18

Airflow 1500 L/s, bypass factor BF 0.114, indoor fan motor heat 1.62 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	18.4	18.4 5.72	20.6	20.6 5.78	22.7	19.2 5.85	24.8	16.8 5.91
35.0	17.5	17.5 6.13	19.6	19.6 6.20	21.6	18.2 6.27	23.6	16.0 6.34
40.6	16.6	16.6 6.54	18.6	18.6 6.62	20.5	17.3 6.69	22.4	15.2 6.76
46.1	15.7	15.7 6.95	17.6	17.6 7.03	19.4	16.4 7.10	21.2	14.4 7.18

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-070, nominal 7 tons, rated airflow 1400 L/s

Airflow 1050 L/s, bypass factor BF 0.084, indoor fan motor heat 0.62 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	20.2	20.2	6.67	22.6	20.3	6.75	24.9	18.3	6.82	27.3	15.5	6.90
35.0	19.2	19.2	7.15	21.5	19.3	7.23	23.7	17.4	7.31	25.9	14.7	7.40
40.6	18.3	18.3	7.63	20.4	18.3	7.72	22.4	16.5	7.80	24.6	13.9	7.89
46.1	17.3	17.3	8.11	19.3	17.3	8.20	21.3	15.6	8.29	23.3	13.2	8.38

Airflow 1400 L/s, bypass factor BF 0.100, indoor fan motor heat 1.16 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	20.9	20.9	6.67	23.4	22.3	6.75	25.8	20.4	6.82	28.2	17.5	6.90
35.0	19.9	19.9	7.15	22.3	21.2	7.23	24.5	19.4	7.31	26.8	16.7	7.40
40.6	18.9	18.9	7.63	21.1	20.1	7.72	23.2	18.4	7.80	25.4	15.8	7.89
46.1	17.9	17.9	8.11	20.0	19.0	8.20	22.0	17.4	8.29	24.1	15.0	8.38

Airflow 1750 L/s, bypass factor BF 0.114, indoor fan motor heat 1.90 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	21.5	21.5	6.67	24.0	24.0	6.75	26.5	22.4	6.82	29.0	19.6	6.90
35.0	20.5	20.5	7.15	22.9	22.9	7.23	25.2	21.3	7.31	27.6	18.7	7.40
40.6	19.4	19.4	7.63	21.7	21.7	7.72	23.9	20.2	7.80	26.1	17.7	7.89
46.1	18.4	18.4	8.11	20.5	20.5	8.20	22.6	19.1	8.29	24.7	16.8	8.38

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-080, nominal 8 tons, rated airflow 1600 L/s

Airflow 1200 L/s, bypass factor BF 0.084, indoor fan motor heat 0.70 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	23.1	23.1 7.63	25.8	23.2 7.71	28.4	20.9 7.80	31.2	17.7 7.88
35.0	22.0	22.0 8.17	24.6	22.0 8.27	27.0	19.9 8.36	29.6	16.8 8.45
40.6	20.9	20.9 8.72	23.3	20.9 8.82	25.7	18.9 8.92	28.1	15.9 9.02
46.1	19.7	19.7 9.26	22.1	19.8 9.37	24.3	17.9 9.47	26.6	15.1 9.58

Airflow 1600 L/s, bypass factor BF 0.100, indoor fan motor heat 1.32 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	23.9	23.9 7.63	26.7	25.5 7.71	29.4	23.3 7.80	32.2	20.1 7.88
35.0	22.8	22.8 8.17	25.4	24.2 8.27	28.0	22.1 8.36	30.7	19.1 8.45
40.6	21.6	21.6 8.72	24.1	23.0 8.82	26.6	21.0 8.92	29.1	18.1 9.02
46.1	20.4	20.4 9.26	22.8	21.7 9.37	25.1	19.9 9.47	27.5	17.1 9.58

Airflow 2000 L/s, bypass factor BF 0.114, indoor fan motor heat 2.16 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	24.6	24.6 7.63	27.5	27.5 7.71	30.2	25.6 7.80	33.1	22.4 7.88
35.0	23.4	23.4 8.17	26.1	26.1 8.27	28.8	24.3 8.36	31.5	21.3 8.45
40.6	22.2	22.2 8.72	24.8	24.8 8.82	27.3	23.1 8.92	29.9	20.2 9.02
46.1	21.0	21.0 9.26	23.5	23.5 9.37	25.8	21.8 9.47	28.3	19.1 9.58

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-090, nominal 9 tons, rated airflow 1800 L/s

Airflow 1350 L/s, bypass factor BF 0.084, indoor fan motor heat 0.79 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	26.0	26.0 8.58	29.1	26.1 8.68	32.0	23.5 8.77	35.0	19.9 8.87
35.0	24.7	24.7 9.20	27.6	24.8 9.30	30.4	22.4 9.40	33.3	18.9 9.51
40.6	23.5	23.5 9.81	26.2	23.5 9.93	28.9	21.2 10.03	31.6	17.9 10.15
46.1	22.2	22.2 10.42	24.8	22.3 10.54	27.3	20.1 10.66	29.9	17.0 10.77

Airflow 1800 L/s, bypass factor BF 0.100, indoor fan motor heat 1.49 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	26.9	26.9 8.58	30.1	28.6 8.68	33.1	26.2 8.77	36.3	22.6 8.87
35.0	25.6	25.6 9.20	28.6	27.2 9.30	31.5	24.9 9.40	34.5	21.5 9.51
40.6	24.3	24.3 9.81	27.1	25.8 9.93	29.9	23.6 10.03	32.7	20.4 10.15
46.1	23.0	23.0 10.42	25.7	24.5 10.54	28.3	22.3 10.66	31.0	19.3 10.77

Airflow 2250 L/s, bypass factor BF 0.114, indoor fan motor heat 2.43 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	27.7	27.7 8.58	30.9	30.9 8.68	34.0	28.7 8.77	37.3	25.2 8.87
35.0	26.3	26.3 9.20	29.4	29.4 9.30	32.4	27.3 9.40	35.4	24.0 9.51
40.6	24.9	24.9 9.81	27.9	27.9 9.93	30.7	25.9 10.03	33.6	22.8 10.15
46.1	23.6	23.6 10.42	26.4	26.4 10.54	29.1	24.5 10.66	31.8	21.5 10.77

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-100, nominal 10 tons, rated airflow 2000 L/s

Airflow 1500 L/s, bypass factor BF 0.093, indoor fan motor heat 0.88 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	28.9	28.9 9.53	32.3	29.0 9.64	35.6	26.1 9.75	38.9	22.1 9.85
35.0	27.5	27.5 10.22	30.7	27.5 10.33	33.8	24.9 10.45	37.0	21.0 10.56
40.6	26.1	26.1 10.90	29.1	26.1 11.03	32.1	23.6 11.15	35.1	19.9 11.27
46.1	24.7	24.7 11.58	27.6	24.7 11.71	30.4	22.3 11.84	33.2	18.9 11.97

Airflow 2000 L/s, bypass factor BF 0.110, indoor fan motor heat 1.65 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	29.9	29.9 9.53	33.4	31.8 9.64	36.8	29.1 9.75	40.3	25.1 9.85
35.0	28.5	28.5 10.22	31.8	30.3 10.33	35.0	27.7 10.45	38.3	23.8 10.56
40.6	27.0	27.0 10.90	30.1	28.7 11.03	33.2	26.2 11.15	36.4	22.6 11.27
46.1	25.5	25.5 11.58	28.5	27.2 11.71	31.4	24.8 11.84	34.4	21.4 11.97

Airflow 2500 L/s, bypass factor BF 0.126, indoor fan motor heat 2.70 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	30.7	30.7 9.53	34.3	34.3 9.64	37.8	31.9 9.75	41.4	28.0 9.85
35.0	29.2	29.2 10.22	32.6	32.6 10.33	35.9	30.4 10.45	39.4	26.7 10.56
40.6	27.7	27.7 10.90	31.0	31.0 11.03	34.1	28.8 11.15	37.3	25.3 11.27
46.1	26.2	26.2 11.58	29.3	29.3 11.71	32.3	27.3 11.84	35.4	23.9 11.97

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-110, nominal 11 tons, rated airflow 2200 L/s

Airflow 1650 L/s, bypass factor BF 0.093, indoor fan motor heat 0.97 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	31.8	31.8 10.48	35.5	31.9 10.60	39.1	28.7 10.72	42.8	24.3 10.84
35.0	30.2	30.2 11.24	33.8	30.3 11.37	37.2	27.3 11.49	40.7	23.1 11.62
40.6	28.7	28.7 12.00	32.0	28.7 12.13	35.3	25.9 12.26	38.6	21.9 12.40
46.1	27.2	27.2 12.74	30.3	27.2 12.88	33.4	24.5 13.02	36.6	20.7 13.17

Airflow 2200 L/s, bypass factor BF 0.110, indoor fan motor heat 1.82 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	32.9	32.9 10.48	36.8	35.0 10.60	40.5	32.0 10.72	44.3	27.6 10.84
35.0	31.3	31.3 11.24	35.0	33.3 11.37	38.5	30.4 11.49	42.2	26.2 11.62
40.6	29.7	29.7 12.00	33.2	31.6 12.13	36.5	28.8 12.26	40.0	24.9 12.40
46.1	28.1	28.1 12.74	31.4	29.9 12.88	34.6	27.3 13.02	37.9	23.5 13.17

Airflow 2750 L/s, bypass factor BF 0.126, indoor fan motor heat 2.97 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	33.8	33.8 10.48	37.8	37.8 10.60	41.6	35.1 10.72	45.5	30.8 10.84
35.0	32.1	32.1 11.24	35.9	35.9 11.37	39.5	33.4 11.49	43.3	29.3 11.62
40.6	30.5	30.5 12.00	34.1	34.1 12.13	37.5	31.7 12.26	41.1	27.8 12.40
46.1	28.9	28.9 12.74	32.2	32.2 12.88	35.5	30.0 13.02	38.9	26.3 13.17

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-125, nominal 12.5 tons, rated airflow 2500 L/s

Airflow 1875 L/s, bypass factor BF 0.093, indoor fan motor heat 1.09 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	36.2	36.2 11.93	40.4	36.2 12.06	44.5	32.7 12.20	48.7	27.6 12.33
35.0	34.4	34.4 12.79	38.4	34.5 12.93	42.3	31.1 13.07	46.3	26.3 13.22
40.6	32.6	32.6 13.65	36.4	32.7 13.80	40.1	29.5 13.95	44.0	24.9 14.11
46.1	30.9	30.9 14.49	34.5	31.0 14.66	38.0	27.9 14.82	41.6	23.6 14.98

Airflow 2500 L/s, bypass factor BF 0.110, indoor fan motor heat 2.06 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	37.4	37.4 11.93	41.8	39.8 12.06	46.1	36.4 12.20	50.4	31.4 12.33
35.0	35.6	35.6 12.79	39.8	37.9 12.93	43.8	34.6 13.07	48.0	29.8 13.22
40.6	33.8	33.8 13.65	37.7	35.9 13.80	41.5	32.8 13.95	45.5	28.3 14.11
46.1	32.0	32.0 14.49	35.7	34.0 14.66	39.3	31.1 14.82	43.1	26.8 14.98

Airflow 3125 L/s, bypass factor BF 0.126, indoor fan motor heat 3.37 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	38.5	38.5 11.93	43.0	43.0 12.06	47.3	40.0 12.20	51.8	35.1 12.33
35.0	36.6	36.6 12.79	40.9	40.9 12.93	45.0	38.0 13.07	49.3	33.4 13.22
40.6	34.7	34.7 13.65	38.8	38.8 13.80	42.7	36.1 13.95	46.7	31.6 14.11
46.1	32.8	32.8 14.49	36.7	36.7 14.66	40.4	34.1 14.82	44.2	30.0 14.98

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-140, nominal 14 tons, rated airflow 2800 L/s

Airflow 2100 L/s, bypass factor BF 0.093, indoor fan motor heat 1.23 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	40.5	40.5 13.34	45.2	40.6 13.50	49.8	36.6 13.64	54.5	30.9 13.80
35.0	38.5	38.5 14.31	43.0	38.6 14.47	47.3	34.8 14.63	51.8	29.4 14.79
40.6	36.5	36.5 15.27	40.8	36.6 15.44	44.9	33.0 15.61	49.2	27.9 15.78
46.1	34.6	34.6 16.21	38.6	34.6 16.40	42.5	31.2 16.58	46.5	26.4 16.76

Airflow 2800 L/s, bypass factor BF 0.110, indoor fan motor heat 2.31 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	41.9	41.9 13.34	46.8	44.5 13.50	51.5	40.7 13.64	56.4	35.1 13.80
35.0	39.8	39.8 14.31	44.5	42.4 14.47	49.0	38.7 14.63	53.7	33.4 14.79
40.6	37.8	37.8 15.27	42.2	40.2 15.44	46.5	36.7 15.61	50.9	31.7 15.78
46.1	35.8	35.8 16.21	40.0	38.0 16.40	44.0	34.8 16.58	48.2	30.0 16.76

Airflow 3500 L/s, bypass factor BF 0.126, indoor fan motor heat 3.77 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	43.0	43.0 13.34	48.1	48.1 13.50	52.9	44.7 13.64	58.0	39.2 13.80
35.0	40.9	40.9 14.31	45.7	45.7 14.47	50.3	42.5 14.63	55.1	37.3 14.79
40.6	38.8	38.8 15.27	43.4	43.4 15.44	47.7	40.3 15.61	52.3	35.4 15.78
46.1	36.7	36.7 16.21	41.0	41.0 16.40	45.2	38.2 16.58	49.5	33.5 16.76

See the notes on page 1.

Corvid Air Systems - RTX series catalogue, extended cooling performance, 2025 edition

Model RTX-150, nominal 15 tons, rated airflow 3000 L/s

Airflow 2250 L/s, bypass factor BF 0.093, indoor fan motor heat 1.32 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	43.4	43.4	48.4	43.4	53.3	39.2	58.4	33.1
35.0	41.2	41.2	46.1	41.3	50.7	37.3	55.5	31.5
40.6	39.1	39.1	43.7	39.2	48.1	35.4	52.7	29.9
46.1	37.0	37.0	41.4	37.1	45.5	33.5	49.9	28.3

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	14.30		14.46		14.62		14.78	
35.0	15.33		15.50		15.67		15.85	
40.6	16.36		16.54		16.72		16.91	
46.1	17.37		17.57		17.76		17.96	

Airflow 3000 L/s, bypass factor BF 0.110, indoor fan motor heat 2.48 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	44.9	44.9	50.1	47.7	55.2	43.6	60.5	37.6
35.0	42.7	42.7	47.7	45.4	52.5	41.5	57.5	35.8
40.6	40.5	40.5	45.2	43.1	49.8	39.3	54.5	33.9
46.1	38.3	38.3	42.8	40.8	47.1	37.2	51.6	32.1

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	14.30		14.46		14.62		14.78	
35.0	15.33		15.50		15.67		15.85	
40.6	16.36		16.54		16.72		16.91	
46.1	17.37		17.57		17.76		17.96	

Airflow 3750 L/s, bypass factor BF 0.126, indoor fan motor heat 4.05 kW

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	46.1	46.1	51.5	51.5	56.7	47.9	62.1	42.0
35.0	43.8	43.8	49.0	49.0	53.9	45.6	59.1	40.0
40.6	41.6	41.6	46.5	46.5	51.1	43.2	56.0	37.9
46.1	39.4	39.4	44.0	44.0	48.4	40.9	53.0	35.9

ODB C	EWB 13.9 C: TC	SHC kW	EWB 16.7 C: TC	SHC kW	EWB 19.4 C: TC	SHC kW	EWB 22.2 C: TC	SHC kW
29.4	14.30		14.46		14.62		14.78	
35.0	15.33		15.50		15.67		15.85	
40.6	16.36		16.54		16.72		16.91	
46.1	17.37		17.57		17.76		17.96	

See the notes on page 1.