

Lab Assignment 08



Inspiring Excellence

Course Code:	CSE111
Course Title:	Programming Language II
Topic:	Review and Polymorphism
Number of Tasks:	11

[NO SUBMISSION]

[You are not allowed to change the driver codes of any of the tasks]

Task 1

Design the **Vaccine** and **Person** class so that the following expected output is generated.

[N.B: Students will get vaccines on a priority basis. So, age doesn't matter for students. All **attributes of Vaccine** class should be **Private**.]

Driver Code	Output
<pre>public class VaccineTester { public static void main(String[] args) { Vaccine astra = new Vaccine("AstraZeneca", "UK", 60); Vaccine modr = new Vaccine("Moderna", "UK", 30); Vaccine sin = new Vaccine("Sinopharm", "China", 30); Person p1 = new Person("Bob", 21, "Student"); System.out.println("====="); p1.pushVaccine(astra); System.out.println("====="); p1.showDetail(); System.out.println("====="); p1.pushVaccine(sin, "2nd Dose"); System.out.println("====="); p1.pushVaccine(astra, "2nd Dose"); System.out.println("====="); p1.showDetail(); System.out.println("====="); p1.pushVaccine(astra, "2nd Dose"); System.out.println("====="); p1.showDetail(); System.out.println("====="); Person p2 = new Person("Carol", 23, "Actor"); System.out.println("====="); p2.pushVaccine(sin); System.out.println("====="); Person p3 = new Person("David", 34); System.out.println("====="); p3.pushVaccine(modr, "2nd Dose"); System.out.println("====="); p3.pushVaccine(modr, "1st Dose"); System.out.println("====="); p3.showDetail(); System.out.println("====="); p3.pushVaccine(modr, "2nd Dose"); } }</pre>	<pre>===== 1st dose done for Bob ===== Name: Bob Age: 21 Type: Student Vaccine name: AstraZeneca 1st dose: Given 2nd dose: Please come after 60 days ===== Sorry Bob, you can't take 2 different vaccines ===== 2nd dose done for Bob ===== Name: Bob Age: 21 Type: Student Vaccine name: AstraZeneca 1st dose: Given 2nd dose: Given ===== Sorry Bob, you already received both doses. ===== Name: Bob Age: 21 Type: Student Vaccine name: AstraZeneca 1st dose: Given 2nd dose: Given ===== Sorry Carol, Minimum age for taking vaccines is 25 years now. ===== ===== Sorry David, invalid dose request. ===== 1st dose done for David ===== Name: David Age: 34 Type: General Citizen Vaccine name: Moderna 1st dose: Given 2nd dose: Please come after 30 days ===== 2nd dose done for David</pre>

Task 2

We know that Nike has opened their official outlets in Bangladesh. So let's construct a **NikeBD** class so that they can keep track of their inventory and sales here.

[Hint: Only 3 types of products are available: “Jordan”, “Cortez” and “Kobe”]

Driver Code	Output
<pre> public class NikeTester { public static void main(String[] args) { System.out.println("=====1====="); NikeBD.status(); NikeBD dhaka = new NikeBD("Dhaka Banani"); NikeBD chittagong = new NikeBD("Chittagong GEC"); System.out.println("=====2====="); dhaka.details(); System.out.println("=====3====="); chittagong.details(); System.out.println("=====4====="); dhaka.restockProducts("Jordan", 200); System.out.println("=====5====="); String [] products = {"Jordan", "Cortez", "Kobe"}; int [] qty = {1200, 200, 200}; String [] products2 = {"Jordan", "Cortez", "Kobe"}; int [] qty2 = {1200, 250, 100}; dhaka.restockProducts(products, qty); System.out.println("=====6====="); chittagong.restockProducts(products2, qty2); System.out.println("=====7====="); NikeBD.status(); System.out.println("=====8====="); dhaka.details(); System.out.println("=====9====="); chittagong.details(); dhaka.productSold("Jordan", 760, "Cortez", 90); chittagong.productSold("Jordan", 520, "Kobe", 70); System.out.println("=====10====="); NikeBD.status(); System.out.println("=====11====="); chittagong.details(); } } </pre>	<pre> =====1===== Nike Bangladesh Status: Branches Opened: 0 Currently Stocked: Air Jordan: 0, Cortez: 0, Zoom Kobe: 0 Sold: 0 =====2===== Nike Dhaka Banani outlet: Products Currently Stocked: Air Jordan: 0, Cortez: 0, Zoom Kobe: 0 Sold: 0 =====3===== Nike Chittagong GEC outlet: Products Currently Stocked: Air Jordan: 0, Cortez: 0, Zoom Kobe: 0 Sold: 0 =====4===== =====5===== =====6===== =====7===== Nike Bangladesh Status: Branches Opened: 2 Currently Stocked: Air Jordan: 0, Cortez: 450, Zoom Kobe: 0 Sold: 0 =====8===== Nike Dhaka Banani outlet: Products Currently Stocked: Air Jordan: 0, Cortez: 200, Zoom Kobe: 0 Sold: 0 =====9===== Nike Chittagong GEC outlet: Products Currently Stocked: Air Jordan: 0, Cortez: 250, Zoom Kobe: 0 Sold: 0 =====10===== Nike Bangladesh Status: Branches Opened: 2 Currently Stocked: Air Jordan: 0, Cortez: 360, Zoom Kobe: 0 Sold: 90 =====11===== Nike Chittagong GEC outlet: Products Currently Stocked: Air Jordan: 0, Cortez: 250, Zoom Kobe: 0 Sold: 0 </pre>

Task 3

Design the child class **Striker** and **Defender** that inherits from the Football class so that the given output matches with the output generated by the driver code.

Parent Class		
<pre>public class Football { public String name; public int age; public int stamina; public Football(String name, int age, int stamina) { this.name = name; this.age = age; this.stamina = stamina; } public void display() { System.out.println("Name: " + name); System.out.println("Age: " + age); System.out.println("Stamina: " + stamina); } public void calculatePerformance() { System.out.println("Performance is not defined yet"); } }</pre>		
Driver Code	Output	
<pre>public class FootballTester { public static void main(String[] args) { Striker ronaldo = new Striker("Ronaldo", 39, 90, 901, 1000); Defender ramos = new Defender("Ramos", 38, 85, 1000, 100); System.out.println("1====="); ronaldo.display(); System.out.println("2====="); ronaldo.calculatePerformance(); System.out.println("3====="); ramos.display(); System.out.println("4====="); ramos.calculatePerformance(); } }</pre>	<pre>1===== Name: Ronaldo Age: 39 Stamina: 90 Goals: 901 Shots on target: 1000 2===== Performance: 0.901 3===== Name: Ramos Age: 38 Stamina: 85 Tackles: 1000 Interceptions: 100 4===== Performance: 0.1</pre>	

Task 4

Design the **Nokia** class derived from the Mobile class so that the following output is produced.

Parent Class

```
class Mobile {
    public String model;
    public String IMEICode;
    public boolean simCardStatus;

    public Mobile(String model, String IMEICode, boolean simCardStatus) {
        this.model = model;
        this.IMEICode = IMEICode;
        this.simCardStatus = simCardStatus;
        System.out.println("Model " + model + " is manufactured.");
    }

    public String getCountryName(String countryCode) {
        if (countryCode.equals("880")) {
            return "Bangladesh";
        } else if (countryCode.equals("455")) {
            return "USA";
        }
        return null;
    }

    public void activateSimCard() {
        if (!simCardStatus) {
            simCardStatus = true;
            System.out.println("SIM card is activated successfully.");
        }
    }

    @Override
    public String toString() {
        return "Mobile Phone Detail:\nModel: " + model + "\nIMEICode: " + IMEICode + "\nSIM Card Status: " +
simCardStatus;
    }
}
```

//Driver code below

Driver Code	Output
<pre> public class MobileTester { public static void main(String[] args) { Nokia N3110 = new Nokia("N3110", true, "IMEI-102", 0); System.out.println(N3110); System.out.println("1====="); Nokia N1100 = new Nokia("N1100", false, "IMEI-124", 100); System.out.println(N1100); System.out.println("2====="); System.out.println(N3110.dialCall("88017196xxxx")); System.out.println("3====="); N3110.rechargeSIMCard(200); N1100.rechargeSIMCard(300); System.out.println("4====="); System.out.println(N3110.dialCall("88017196xxxx")); System.out.println("5====="); System.out.println(N1100.dialCall("45517196xxxx")); System.out.println("6====="); N1100.activateSimCard(); System.out.println("7====="); System.out.println(N1100.dialCall("45517196xxxx")); System.out.println("8====="); System.out.println(N1100.dialCall("96617196xxxx")); } } </pre>	<pre> Model N3110 is manufactured. Mobile Phone Detail: Model: N3110 IMEIcode: IMEI-102 SIM Card Status: true Balance: 0.0 TK 1===== Model N1100 is manufactured. Mobile Phone Detail: Model: N1100 IMEIcode: IMEI-124 SIM Card Status: false Balance: 100.0 TK 2===== Insufficient balance! Please recharge. 3===== Recharge successful! Current balance 200.0 TK. Recharge successful! Current balance 400.0 TK. 4===== Dialing the number 88017196xxxx to Bangladesh region. 5===== No SIM card available! Please check the SIM card connectivity. 6===== SIM card is activated successfully. 7===== Dialing the number 45517196xxxx to USA region. 8===== Dialing is not allowed in this region. </pre>

Task 5

Design the **Dragon** class and **Phoenix** class derived from the **MagicalCreature** class so that the following output is produced.

Parent Class		
<pre>public class MagicalCreature { public String name; public int age; public MagicalCreature(String name, int age) { this.name = name; this.age = age; } public void makeSound() { System.out.println(name + " makes a magical sound."); } public void displayInfo() { System.out.println("Name: " + name + "\nAge: " + age); } public void performMagic() { System.out.println(name + " performs a generic magic."); } }</pre>		
Driver Code	Output	
<pre>public class MagicalTester { public static void main(String[] args) { Dragon drake = new Dragon("Drake", 500, 75); Phoenix fawkes = new Phoenix("Fawkes", 200, 5); drake.displayInfo(); drake.makeSound(); drake.performMagic(); drake.fly(); System.out.println("====="); fawkes.displayInfo(); fawkes.makeSound(); fawkes.performMagic(); fawkes.regenerate(); } }</pre>	<pre>Name: Drake Age: 500 Drake roars with a fiery breath! Drake breathes fire with power level: 75 Drake flies through the sky. ===== Name: Fawkes Age: 200 Fawkes sings an enchanting song. Fawkes is reborn with 5 rebirth cycles. Fawkes regenerates its body in a burst of flames.</pre>	

Task 6

Design the **Bondhus** class derived from the **SocialMedia** class so that the following output is produced.

Parent Class	
<pre> public class SocialMedia{ public String userName; public String email; public SocialMedia(String name, String mail){ userName = name; email = mail; } @Override public String toString() { return userName + "'s profile:" + "\nUser Name: " + userName + "\nEmail:" + email; } } </pre>	
Driver Code	Output
<pre> public class SocialMediaTester{ public static void main(String []args){ Bondhus f1 = new Bondhus("Sheldon", "sheldon@gmail.com"); Bondhus f2 = new Bondhus("Penny", "penny@gmail.com"); Bondhus f3 = new Bondhus("Leonard", "leonard@gmail.com"); System.out.println("1-----"); f1.showSentbox(); System.out.println("2-----"); f2.showSentbox(); System.out.println("3-----"); f2.sendMessage("Hi"); f2.sendMessage("Hello"); f2.sendMessage("NiHao"); f3.sendMessage("Hola"); f3.sendMessage("Sheldon, please."); System.out.println("4-----"); f2.showSentbox(); System.out.println("5-----"); f1.showSentbox(); System.out.println("6-----"); f1.sendMessage("Bazinga!"); f2.sendMessage("Well, duh!"); f3.showSentbox(); System.out.println("7-----"); f2.showSentbox(); f2.sendMessage("Bye."); f2.sendMessage("Oh! No"); System.out.println("8-----"); f1.showSentbox(); System.out.println("9-----"); System.out.println(f1); System.out.println("10-----"); System.out.println(f2); } } </pre>	<pre> 1----- Sheldon's Sentbox: No sent messages. 2----- Penny's Sentbox: No sent messages. 3----- 4----- Penny's Sentbox: Hi Hello NiHao 5----- Sheldon's Sentbox: No sent messages. 6----- Leonard's Sentbox: Hola Sheldon, please. 7----- Penny's Sentbox: Hi Hello NiHao Well, duh! Sentbox is full. 8----- Sheldon's Sentbox: Bazinga! 9----- Sheldon's profile: User Name: Sheldon Email:sheldon@gmail.com Messages Sent: 1 </pre>

}	10----- Penny's profile: User Name: Penny Email:penny@qmail.com Messages Sent: 5
---	--

Task 7

Write the **Mango** and the **Jackfruit** classes derived from Fruit class so that the following code generates the output below:

Parent Class	
<pre> public class Fruit{ private boolean formalin = false; private String name = ""; public Fruit(boolean formalin, String name){ this.formalin = formalin; this.name = name; } public String getName(){ return name; } public boolean hasFormalin(){ return formalin; } } </pre>	
Driver Code	Output
<pre> public class FruitTester{ public static void testFruit(Fruit f){ System.out.println("----Printing Detail-----"); if(f.hasFormalin()){ System.out.println("Do not eat the "+f.getName()+"."); System.out.println(f); }else{ System.out.println("Eat the "+f.getName()+"."); System.out.println(f); } } public static void main(String [] args){ Mango m = new Mango(); testFruit(m); Jackfruit j = new Jackfruit(); testFruit(j); } } </pre>	<pre> ----Printing Detail----- Do not eat the Mango. Mangos are bad for you ----Printing Detail----- Eat the Jackfruit. Jackfruits are good for you </pre>

Task 8

Write the **CSEStudent** and **CSE111Student** classes derived from Student class so that the following code generates the output below

Parent Class	
<pre>public class Student{ public String msg = "I love BU"; public String shout(){ return msg; } }</pre>	
Driver Code	Output
<pre>public class StudentTester{ public static void printShout(Student s){ System.out.println("-----"); System.out.println(s.msg); System.out.println(s.shout()); } public static void main(String [] args){ Student s = new Student(); CSEStudent cs = new CSEStudent(); CSE111Student cs111 = new CSE111Student(); System.out.println(s.msg); System.out.println(cs.msg); System.out.println(cs111.msg); printShout(s); printShout(cs); printShout(cs111); } }</pre>	<pre>I love BU I want to transfer to CSE I love Java Programming ----- I love BU I love BU ----- I love BU I want to transfer to CSE ----- I love BU I love Java Programming</pre>

Task 9

1	public class Trace {
2	public int sum, temp;
3	public Trace(int sum, int temp){
4	this.sum = sum;
5	this.temp = temp;
6	}
7	}
8	class Quiz5{
9	public int sum = 12, x = 2, y = 6;
10	public Trace trace;
11	public Quiz5(Trace t){
12	trace = t;
13	int x = trace.temp + y;
14	sum = sum + (t.sum--) + y;
15	System.out.println(trace.sum + " " + sum + " " + x);
16	sum -= 10;
17	}
18	public void methodA(int sum, int temp){
19	sum = 3 + sum - trace.sum;
20	x = sum + 12 + y;
21	y = trace.temp + temp + sum;
22	this.sum = y + methodB(trace.temp, trace) + trace.temp;
23	System.out.println(sum + " " + y + " " + this.sum);
24	}
25	public int methodB(int x, Trace temp){
26	int sum = x + temp.sum + this.x;
27	temp.temp = sum + this.sum;
28	System.out.println(x + " " + temp.temp + " " + sum);
29	return sum;
30	}
31	}

<pre>Trace p = new Trace(3, 4); Quiz5 q = new Quiz5(p); q.methodA(4, 8); q.methodA(5, 10);</pre>	Output		

Task 10

1	public class Test {
2	public static int a=3;
3	public int b=7, c;
4	public Test(){
5	methodA(a+4);
6	}
7	public void methodA(int a){
8	Tracing t = new Tracing(2,7);
9	a = Tracing.a+ Test.a;
10	c = b + a + t.methodB();
11	System.out.println(this.a+" "+this.b+" "+c);
12	}
13	}
14	class Tracing {
15	public static int a = 9, y = 5;
16	public int x, b;
17	public Tracing(int a, int b){
18	x += a;
19	y += b;
20	this.a = this.x;
21	this.b = this.y;
22	}
23	public int methodB(){
24	System.out.println(this.a+" "+this.b+" "+x);
25	b = y - this.b + Test.a;
26	x += this.b;
27	return this.b;
28	}
29	}

Tracing t2 = new Tracing(4, 3); Test ex = new Test(); t2.methodB(); ex.methodA(Test.a);	Output		

Task 11

1	public class A {
2	public static int temp = 3;
3	public int sum;
4	public int y;
5	public A(int x) {
6	y = A.temp - 1 + x;
7	sum = this.temp + 2;
8	A.temp -= 2;
9	}
10	public void methodA(int y, int[] n) {
11	int x = 0;
12	n[0] += 1;
13	this.y = this.y + y + temp;
14	A.temp += 1;
15	x = x + 2 + n[0];
16	n[0] = sum + 2;
17	System.out.println(x + " " + this.y + " " + this.sum);
18	}
19	}
20	public class B extends A {
21	public static int x = 1;
22	public B() {
23	super(5);
24	sum = 2;
25	y = A.temp + 1;
26	B.x = 3 + temp + B.x;
27	A.temp -= 2;
28	}
29	public B(B b) {
30	super(2);
31	sum = 3;
32	this.sum = sum + this.sum%2 + 2;
33	B.x = b.x + B.x;
34	}
35	public void methodB(int m, int n) {
36	int[] y = {2, 3};
37	this.y = y[0] + this.y + m;
38	B.x = this.y + 2 + A.temp - n;
39	methodA(B.x, y);
40	this.sum = B.x + y[1] + this.sum;
41	System.out.println(B.x + " " + (y[0]+y[1]) + " " + this.sum);
42	}
43	}

Write the output of the following tester code:

int[] n = {23};	Output		
A a1 = new A(3);	x	y	sum
B b1 = new B();			
B b2 = new B(b1);			
a1.methodA(1, n);			
b2.methodB(3, 2);			
a1.methodA(1, n);			