

A. Odd or Even?

Do you know how to tell if a number is Odd or Even? You are given T numbers, and for each of those numbers, you have to tell whether the number is odd or even.

Input

The first line will contain a single integer T ($1 \leq T \leq 100$). Each of the next T lines will contain a number N ($-105 \leq N \leq 105$).

Output

For each N , you have to print whether the number is odd or even.

Example

Input:

5
10
19
7
3
100

Output:

10 is an Even number.
19 is an Odd number.
7 is an Odd number.
3 is an Odd number.
100 is an Even number.

B. Can you solve Arithmetic Expressions?

Can you solve arithmetic expressions with your programming knowledge? Let's find it out. You will be given some arithmetic expressions, and you have to solve them.

Input

The first line will contain a number T ($1 \leq T \leq 1000$) representing the number of test cases. Then for each test case, you will be given an arithmetic expression. It is guaranteed that the numbers inside the arithmetic expression will be between 1 and 1000.

Output

For each test case, you have to print the result. Your answer might contain floating point numbers; it doesn't have to be exactly equal to the actual answer.

Example

Input:

15

calculate $67 + 41$

calculate $85 / 5$

calculate $13 - 56$

calculate $99 - 95$

calculate $3 / 10$

calculate $12 * 19$

calculate $14 - 6$

calculate $3 * 88$

calculate $45 * 68$

calculate $81 - 0$

calculate $77 + 40$

calculate $8 * 84$

calculate $73 - 22$

calculate $85 - 86$

calculate $28 * 58$

Output:

108.000000

17.000000

-43.000000

4.000000

0.300000

228.000000

8.000000

264.000000

3060.000000

81.000000

117.000000

672.000000

51.000000

-1.000000

1624.000000

C. Fast Sum

You are given T test cases. For each test case, you are given an integer N . You have to calculate the sum from 1 to N .

Input

The first line contains a single integer T ($1 \leq T \leq 104$) — the number of test cases.

The next T lines each contain a single integer N ($1 \leq N \leq 106$).

Output

For each test case, print a single integer — the summation from 1 to N .

Example

Input:

5
2
5
10
12
100

Output:

3
15
55
78
5050

D. Is Sorted?

You are given an array of N integers. Determine whether the array is in non-decreasing order.

Input

The first line contains a single integer T ($1 \leq T \leq 100$). Each test case has two lines:

- First line: integer N ($1 \leq N \leq 104$) — the number of elements.
- Second line: N integers a_1, a_2, \dots, a_n ($1 \leq a_i \leq 106$).

Output

For each test case, print YES if the array is in non-decreasing order, otherwise NO.

Example

Input:

3

4
1 2 3 3
4
1 5 2 6
1
5

Output:

YES
NO
YES

E. Reverse Sorting

You are given an array of N integers. You may select any subarray of length exactly 3 and reverse it. Determine whether it is possible to sort the array using only this operation.

Input

The first line: integer N ($1 \leq N \leq 1000$)

Second line: N integers a_1, a_2, \dots, a_n ($1 \leq a_i \leq 10^6$)

Output

Print YES if it is possible to sort the array using only the allowed operations, otherwise NO.

Example

Input:

4
2 3 1 1

Output:

YES

F. An Ancient Sorting Algorithm

Sort an array in non-decreasing order by swapping only adjacent elements with the same parity.

Input

The first line: integer N ($1 \leq N \leq 1000$)

Second line: N integers a_1, a_2, \dots, a_n ($1 \leq a_i \leq 10^6$)

Output

Print the final array after sorting as much as possible.

Example

Input:

7

4 2 4 7 1 6 1

Output:

2 4 4 1 7 6 1

G. Sorting Again??

Rank students by marks; in case of ties, lower ID gets priority. Minimize number of swaps.

Input

The first line: integer N ($1 \leq N \leq 1000$)

Second line: N integers, Student IDs

Third line: N integers, corresponding marks

Output

First line: Minimum swaps. Then lines of ID and mark sorted.

Example

Input:

7

7 4 9 3 2 5 1

40 50 50 20 10 10 10

Output:

Minimum swaps: 4

ID: 4 Mark: 50

ID: 9 Mark: 50

ID: 7 Mark: 40

ID: 3 Mark: 20

ID: 1 Mark: 10

ID: 2 Mark: 10

ID: 5 Mark: 10

H. Trains?

Sort train schedules lexicographically by train name. If names tie, later departure prioritized; if still tied, earlier input prioritized.

Input

First line: integer N ($1 \leq N \leq 100$)

Next N lines: each train schedule in the format:

`TrainName will departure for Destination at HH:MM`

Output

Print the sorted train schedules.

Example

Input:

8

ABCD will departure for Mymensingh at 00:30

DhumketuExpress will departure for Chittagong at 02:30

ABC will departure for Dhaka at 17:30

ABCD will departure for Chittagong at 01:00

ABC will departure for Khulna at 03:00

ABC will departure for Barisal at 03:00

ABCE will departure for Sylhet at 23:05

PadmaExpress will departure for Dhaka at 19:30

Output:

ABC will departure for Dhaka at 17:30

ABC will departure for Khulna at 03:00

ABC will departure for Barisal at 03:00

ABCD will departure for Chittagong at 01:00

ABCD will departure for Mymensingh at 00:30

ABCE will departure for Sylhet at 23:05

DhumketuExpress will departure for Chittagong at 02:30

PadmaExpress will departure for Dhaka at 19:30
