Queues (page 1)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 1)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 2)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 2)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 3)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 3)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 4)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 4)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 5)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 5)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 6)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 6)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 7)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 7)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 8)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 8)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 9)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 9)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 10)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 10)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 11)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 11)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 12)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 12)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 13)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 13)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 14)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 14)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 15)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 15)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 16)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 16)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 17)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 17)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 18)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 18)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 19)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 19)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 20)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 20)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 21)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 21)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 22)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 22)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 23)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 23)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 24)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 24)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 25)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 25)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 26)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 26)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 27)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 27)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 28)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 28)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 29)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 29)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 30)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 30)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 31)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 31)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 32)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 32)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 33)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 33)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 34)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 34)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 35)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 35)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 36)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 36)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 37)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 37)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 38)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 38)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 39)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 39)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 40)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 40)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 41)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 41)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 42)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 42)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 43)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 43)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 44)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 44)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 45)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 45)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 46)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 46)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 47)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 47)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 48)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 48)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 49)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 49)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 50)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 50)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 51)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 51)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 52)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 52)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 53)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 53)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 54)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 54)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 55)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 55)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 56)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 56)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 57)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 57)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 58)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 58)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 59)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 59)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 60)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 60)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 61)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 61)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 62)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 62)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 63)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 63)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 64)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 64)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 65)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 65)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 66)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 66)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 67)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 67)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 68)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 68)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 69)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 69)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 70)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 70)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 71)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 71)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 72)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 72)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 73)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 73)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 74)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 74)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 75)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 75)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 76)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 76)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 77)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 77)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 78)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 78)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 79)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 79)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 80)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 80)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 81)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 81)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 82)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 82)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 83)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 83)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 84)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 84)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 85)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 85)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 86)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 86)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 87)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 87)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 88)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 88)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 89)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 89)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 90)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 90)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 91)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 91)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 92)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 92)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 93)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 93)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 94)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 94)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 95)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 95)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 96)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 96)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 97)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 97)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 98)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 98)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 99)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 99)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 100)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 100)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 101)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 101)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 102)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 102)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 103)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 103)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 104)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 104)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 105)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 105)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 106)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 106)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 107)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 107)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 108)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 108)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 109)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 109)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 110)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 110)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 111)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 111)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 112)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 112)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 113)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 113)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 114)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 114)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 115)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 115)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 116)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 116)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Queues (page 117)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 117)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Visibility (page 118)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 118)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Dead letters (page 119)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 119)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Topics (page 120)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 120)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.