Queues (page 1)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 2)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 3)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 4)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 5)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 6)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 7)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 8)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 9)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 10)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 11)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 12)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 13)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 14)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 15)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 16)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 17)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 18)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 19)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 20)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 21)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 22)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 23)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 24)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 25)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 26)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 27)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 28)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 29)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 30)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 31)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 32)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 33)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 34)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 35)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 36)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 37)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 38)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 39)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 40)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 41)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 42)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 43)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 44)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 45)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 46)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 47)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 48)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 49)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 50)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 51)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 52)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 53)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 54)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 55)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 56)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 57)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 58)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 59)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 60)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 61)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 62)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 63)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 64)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 65)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 66)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 67)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 68)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 69)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 70)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 71)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 72)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 73)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 74)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 75)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 76)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 77)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 78)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 79)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 80)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 81)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 82)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 83)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 84)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 85)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 86)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 87)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 88)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 89)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 90)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 91)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 92)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 93)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 94)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 95)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 96)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 97)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 98)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 99)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 100)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 101)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 102)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 103)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 104)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 105)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 106)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 107)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 108)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 109)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 110)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 111)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 112)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 113)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 114)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 115)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 116)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 117)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 118)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 119)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 120)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 121)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 122)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 123)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 124)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 125)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 126)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 127)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 128)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 129)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 130)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 131)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 132)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 133)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 134)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 135)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 136)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 137)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 138)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 139)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 140)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 141)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 142)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 143)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 144)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 145)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 146)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 147)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 148)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 149)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 150)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 151)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 152)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 153)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 154)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 155)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 156)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 157)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 158)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 159)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 160)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 161)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 162)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 163)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 164)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 165)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 166)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 167)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 168)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 169)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 170)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 171)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 172)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 173)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 174)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 175)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 176)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 177)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 178)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 179)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 180)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 181)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 182)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 183)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 184)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 185)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 186)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 187)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 188)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 189)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 190)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 191)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 192)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 193)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 194)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 195)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 196)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 197)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 198)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 199)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 200)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 201)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 202)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 203)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 204)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 205)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 206)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 207)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 208)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 209)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 210)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 211)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 212)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 213)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 214)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 215)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 216)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 217)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 218)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 219)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 220)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 221)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 222)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 223)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 224)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 225)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 226)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 227)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 228)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 229)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 230)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 231)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 232)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 233)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 234)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 235)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 236)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 237)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 238)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 239)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 240)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 241)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 242)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 243)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 244)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 245)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 246)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 247)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 248)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 249)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 250)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 251)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 252)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 253)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 254)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 255)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 256)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 257)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 258)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 259)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 260)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 261)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 262)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 263)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 264)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 265)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 266)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 267)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 268)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 269)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 270)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 271)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 272)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 273)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 274)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 275)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 276)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 277)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 278)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 279)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 280)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 281)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 282)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 283)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 284)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 285)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 286)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 287)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 288)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 289)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 290)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 291)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 292)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 293)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 294)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 295)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 296)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 297)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 298)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 299)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 300)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 301)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.