Queues (page 1)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 1)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 1)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 1)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Visibility (page 2)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.

Dead letters (page 2)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 2)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 2)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Dead letters (page 3)

Messages that fail repeatedly can be moved to a separate queue after a configured number of receives. Operators inspect that queue, fix the cause, and send the messages back for processing.

Topics (page 3)

A topic pushes every published message to all of its subscribers. Combining a topic with one queue per subscriber gives each consumer its own buffered copy of every message.

Queues (page 3)

A message queue lets a producer hand work to a consumer without waiting for it. The queue stores each message until a consumer receives it and deletes it, so short bursts of traffic do not overload the workers behind it.

Visibility (page 3)

When a consumer receives a message it becomes invisible to other consumers for a while. If the consumer does not delete it before that period ends, the message becomes visible again and another consumer may process it, so handlers should be idempotent.