

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	All-in-One Controller	Brand: Not specified in catalogue Model: VX400 Product Type: All-in-One LED Controller Country of Origin: China Country of Manufacturer: China Key Features • Integrates video processing and LED video control in one unit. • Supports Video Controller, Fiber Converter and ByPass working modes. • 4 Gigabit Ethernet outputs with loading capacity up to 2.6 million pixels. • Maximum output width 10,240 pixels and maximum height 8,192 pixels. • Low latency, 2-layer display, output synchronization and stepless image scaling. • Supports automatic screen brightness, hot backup, presets and pixel-level brightness/chroma calibration. Input & Processing Specifications • Inputs: 1 x HDMI 1.3 (IN & LOOP), 1 x HDMI 1.3, 1 x DVI (IN & LOOP), 1 x 3G-SDI (IN & LOOP) and 1 x OPT 1. • Mosaic input source supported; up to 4 units can be cascaded for image mosaic. • SuperView III processing supports stepless output scaling, one-click full screen and free input cropping. • Color adjustment includes brightness, contrast, saturation, hue and Gamma. Output & Control Specifications • Outputs: 4 x Gigabit Ethernet ports, 2 x fiber outputs and 1 x HDMI 1.3 monitoring/video output. • OPT 1 is self-adaptive for video input or sending-card output; OPT 2 supports copy/backup of Ethernet output. • Audio input accompanies HDMI source; audio output via multifunction card with adjustable output volume. • Low-latency mode with ByPass can reduce input-to-receiving-card delay to 20 lines. Electrical & Physical Specifications • Power Input: 100-240 V~, 1.5 A, 50/60 Hz; Rated Power Consumption: 28 W. • Dimensions: 483.6 x 301.2 x 50.1 mm; Net Weight: 4 kg. • Operating: 0°C to 45°C / 20%-90% RH, non-condensing. • Storage: -20°C to +70°C / 10%-95% RH, non-condensing. • Packing Size: 550.0 x 175.0 x 400.0 mm; Gross Weight: 6.8 kg; Typical Noise: 45 dB(A).

