

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	LED Module	Brand: Lampro Model: LC1.538P Product Type: Indoor LED Display Module Series: LC Series Country of Origin: China Country of Manufacturer: China Key Features • 320 x 160 mm universal module size. • Bottom case texture design with high-quality lamp beads. • New PCB board design for improved reliability. • Lightweight module assembly reduces screen weight and structural load. • Excellent visual experience and good compatibility with the LC indoor series. • Supports coating process, 45° tangent angle and up to 7680 Hz refresh (optional/configuration dependent). Display & Optical Performance • Pixel Pitch: 1.538 mm; LED Type: SMD1212 • Module Resolution: 208 x 104 = 21,632 pixels; Pixel Density: 422,500 pixels/m² • Brightness: 500 cd/m²; Single-dot Brightness Calibration: Supported • Viewing Angle: Horizontal 140° / Vertical 140°; Contrast Ratio: 5,000:1 • Color Temperature: 2,000K-9,300K adjustable; Brightness/Color Uniformity: ≥98% Electrical & Processing Specifications • Input Power: Maximum 488 W/m² / Typical 163 W/m² • Power Input: AC 90-132 V / AC 186-264 V; Frequency: 47-63 Hz • Frame Frequency: 60 Hz; Refresh Rate: 3840 Hz standard / 7680 Hz optional • Processing Depth: 12-14 bit; Video Support: 2K HD, 4K UHD; HUB: HUB75 Physical & Environmental Specifications • Module Size: 320 x 160 x 16.6 mm; Module Weight: 0.49 ± 0.02 kg • Protection Class: IP30 (indoor lamp face) • Life Span: 100,000 hours • Working Temperature/Humidity: -20°C to 45°C / 10%-50% RH (No Condensation) • Storage Temperature/Humidity: -20°C to 50°C / 10%-60% RH (No Condensation) • Certification: BIS / CE / CB / ROHS / EAC

