

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	LED Module	Brand: Lampro Model: LC3P Product Type: Indoor LED Display Module Series: LC Series Country of Origin: China Country of Manufacturer: China Key Features • Bottom case texture design for improved module construction. • High-quality lamp beads designed to resist falling off. • New PCB board design for improved reliability. • Lightweight module assembly reduces screen weight and structural load. • Excellent visual experience with good compatibility. • Supports coating process and up to 7680 Hz refresh rate (optional/configuration dependent). Display & Optical Performance • Pixel Pitch: 3 mm; LED Type: SMD2121 • Module Resolution: 64 x 64 = 4,096 pixels; Pixel Density: 102,400 pixels/m² • Brightness: ≥ 500 cd/m²; Single-dot Brightness Calibration: Supported • Viewing Angle: Horizontal 140° / Vertical 140°; Contrast Ratio: 5,000:1 • Color Temperature: 2,000K-9,300K adjustable; Brightness/Color Uniformity: $\geq 98\%$ Electrical & Processing Specifications • Input Power: Maximum 543 W/m² / Typical 180 W/m² • Power Input: AC 90-132 V / AC 186-264 V; Frequency: 47-63 Hz • Frame Frequency: 60 Hz; Refresh Rate: 3840 Hz standard / 7680 Hz optional • Processing Depth: 12-14 bit; Video Support: 2K HD, 4K UHD; HUB: HUB75 Physical & Environmental Specifications • Module Size: 192 x 192 x 14 mm; Module Weight: 0.23 $\pm$ 0.02 kg • Life Span: 100,000 hours • Working Temperature/Humidity: -20°C to 45°C / 10%-50% RH (No Condensation) • Storage Temperature/Humidity: -20°C to 50°C / 10%-60% RH (No Condensation) • Certification: BIS / CE / CB / ROHS / EAC