

Full Technical Specification

Sl. No	Item Name	Technical Specification
6	SMD LED Module	Brand: Leyard Model: LUS0300 Product Type: Indoor SMD LED Display Module Series: LUS Series Country of Origin: China Country of Manufacturer: China Key Features • Lightweight and high-strength module with efficient load-bearing performance. • Screwless design improves overall flatness and supports direct component servicing. • High refresh rate provides smooth visuals, vibrant colors and seamless motion. • Supports automatic adjustment of brightness and color temperature. Display & Optical Performance • Pixel Pitch: 3.076 mm; LED Configuration: SMD • Module Resolution: 104 x 52 pixels; Pixel Density: 105,625 dots/m² • Module Size: 320 x 160 mm; Module Area: 0.0512 m²; Weight: 0.39 ± 0.05 kg • White Balance Brightness: 500-550 nits; Contrast Ratio: 5000:1 • Viewing Angle: Horizontal 160° / Vertical 140° • Color Temperature: 3000-38000 K adjustable; Brightness Uniformity: ≥97% • LED Luminance Center Deviation: <3% Electrical & Processing Specifications • Peak Power Consumption: ≤308 W/m²; Average Power Consumption: ≤103 W/m² • Drive Mode (Constant Current Drive): 52S • Frame Rate: 50 & 60 Hz; Refresh Rate: ≥3840 Hz Physical & Environmental Specifications • Lifetime: 100,000 hours • Operating Temperature/Humidity: -10°C to 40°C / 10%-80% RH, no condensation • Storage Temperature/Humidity: -20°C to 60°C / 10%-85% RH, no condensation

