

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	LED Module	Brand: Lampro Model: LC2.5PO Product Type: Outdoor LED Display Module Series: LC Series Country of Origin: China Country of Manufacturer: China Key Features • 320 x 160 mm universal module size. • Enhanced bottom-case texture design with high-protection-class LED lamps. • Waterproof and moisture-proof front-side treatment with gluing. • High brightness and efficient heat dissipation for outdoor applications. • High refresh rate and high grayscale for smooth, detailed visual performance. • Good compatibility across the LC outdoor P2.5-P8 series; supports 45° tangent angle (optional). Display & Optical Performance • Pixel Pitch: 2.5 mm; LED Type: SMD1415 • Module Resolution: 128 x 64 = 8,192 pixels; Pixel Density: 160,000 pixels/m² • Brightness: 4,000-4,500 cd/m²; Single-dot Brightness Calibration: Supported • Viewing Angle: Horizontal 140° / Vertical 140°; Contrast Ratio: 5,000:1 • Color Temperature: 6,500K (1,000K-9,500K adjustable); Brightness/Color Uniformity: ≥98% Electrical & Processing Specifications • Input Power: Maximum 879 W/m² / Typical 293 W/m² • Power Input: AC 90-132 V / AC 186-264 V; Frequency: 47-63 Hz • Frame Frequency: 60 Hz; Refresh Rate: 3840 Hz • Processing Depth: 12-14 bit; Video Support: 2K HD, 4K UHD; HUB: HUB75 Physical & Environmental Specifications • Module Size: 320 x 160 x 17.5 mm; Module Weight: 0.46 ± 0.02 kg • Life Span: 100,000 hours • Working Temperature/Humidity: -20°C to 50°C / 10%-80% RH (No Condensation) • Storage Temperature/Humidity: -20°C to 55°C / 10%-85% RH (No Condensation) • Certification: BIS / CE / CB / ROHS / EAC

