

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	LED Module	Brand: Lampro Model: LR3.91O Product Type: Outdoor Rental LED Display Module Module Format: 250 x 250 mm Country of Origin: China Country of Manufacturer: China Key Features • 250 x 250 mm universal module size; suitable for 500 x 500 mm / 500 x 1000 mm rental cabinets. • High-protection-class LED lamp with waterproof and moisture-proof front-side gluing. • High brightness and high heat dissipation for outdoor event applications. • High refresh and high grayscale for smooth visual performance. • Supports 45° tangent angle and 7680 Hz refresh rate. • Enhanced bottom-case texture and reliable PCB design. Display & Optical Performance • Pixel Pitch: 3.91 mm; LED Type: SMD1921 • Module Resolution: 64 x 64 = 4,096 pixels; Pixel Density: 68,267 pixels/m² • Brightness: 4,500 cd/m²; Single-dot Brightness Calibration: Supported; Mask: Supported • Viewing Angle: Horizontal 140° / Vertical 120°; Contrast Ratio: 5,000:1 • Color Temperature: 6,500K (1,000K-9,500K adjustable); Uniformity: ≥98% Electrical & Processing Specifications • Module Power Consumption: ≤31.5 W; Input Power: Max. 630 W/m² / Typical 189 W/m² • Power Input: AC 90-132 V / AC 186-264 V; Frequency: 47-63 Hz • Frame Frequency: 60 Hz; Refresh Rate: 7680 Hz • Processing Depth: 12-14 bit; Video Support: 2K, 4K; HUB: HUB75 Physical & Environmental Specifications • Module Size: 250 x 250 x 15.6 mm; Module Weight: 0.49 ± 0.02 kg • Life Span: 100,000 hours • Working Temperature/Humidity: -20°C to 50°C / 10%-80% RH (No Condensation) • Storage Temperature/Humidity: -20°C to 55°C / 10%-85% RH (No Condensation)

