

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	LED Module	Brand: Leyard Model: LVS0500 Product Type: Outdoor LED Display Module Series: LVS Series Country of Origin: China Country of Manufacturer: China Key Features • High-performance outdoor full-color LED module with reliable and durable construction. • Single-pixel calibration and universal HUB interface support. • $\geq 100\%$ NTSC color gamut with wide 160° horizontal viewing angle. • Color temperature and brightness are adjustable for different outdoor conditions. • ≥ 7680 Hz super-high refresh rate for smooth, flicker-free dynamic content. • Automatic brightness/color-temperature adjustment supports viewing comfort and energy saving. Display & Optical Performance • Pixel Structure: SMT 3 in 1; Pixel Pitch: 5 mm • Module Resolution: 64 x 32 pixels; Pixel Density: 40,000 dots/m² • White Balance Brightness: ≥ 5000 nits • Color Temperature: 3000K-38000K adjustable • Viewing Angle: Horizontal 160° / Vertical 140° • Brightness Uniformity: $\geq 97\%$; Contrast Ratio: 5000:1; Color Luminous Center Deviation: $< 3\%$ Electrical & Processing Specifications • Peak Power Consumption: ≤ 660 W/m²; Average Power Consumption: ≤ 220 W/m² • Power Supply: DC 4.5 V; Single Module Current: 7.5 A • Drive Mode: Constant current drive 8S • Frame Rate: 50 & 60 Hz; Refresh Rate: ≥ 7680 Hz Physical & Environmental Specifications • Module Size: 320 x 160 mm; Module Weight: 0.41 ± 0.05 kg; Unit Area: 0.0512 m² • Typical Lifespan: 100,000 hours • Working Temperature: -20°C to 40°C; Storage Temperature: -20°C to 60°C • Working Humidity: 10%-80% RH, no condensation • Storage Humidity: 10%-85% RH, no condensation