

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	2-in-1 LED Controller	Brand: Huidu Model: HD-VP1640A Product Type: 2-in-1 LED Controller Country of Origin: China Country of Manufacturer: China Key Features • 2-in-1 LED video processor with 16 Gigabit Ethernet output ports. • Maximum LED loading capacity: 10.4 million pixels. • Supports 4K@60Hz synchronous signal input and point-to-point display. • Supports four-screen display with flexible window layout. • Standard Wi-Fi with mobile APP wireless control. • Supports 8 scene presets, brightness adjustment, key lock and wireless projection. Input & Processing Specifications • Inputs: DP/Type-C shared input, 1 x HDMI 2.0, up to 2 x HDMI 1.4 and up to 2 x DVI; optional SDI. • DP / Type-C: DP 1.2 compatible, up to 3840 x 2160 @ 60 Hz. • HDMI 2.0: up to 3840 x 2160 @ 60 Hz; HDMI 1.4: up to 3840 x 2160 @ 30 Hz. • DVI: DVI 1.0 / HDMI 1.3 compatible; PC up to 1920 x 1080, HD up to 1080p. • Audio Input: 1 x TRS 3.5 mm two-channel input; HDMI/DP embedded audio supported. Output & Control Specifications • LED Outputs: 16 x Gigabit Ethernet ports; 650,000 pixels loading capacity per port. • Maximum Load: 10.4 million pixels; max width 16,000 pixels / max height 4,000 pixels. • Audio Output: 1 x TRS 3.5 mm two-channel output; optional SDI loop output. • Control Interfaces: USB-B, RS232, Wi-Fi, IR extension; optional 4G antenna and SIM. • Wireless projection supports up to 1080p / 1920 x 1200 at max 30 fps. Electrical & Physical Specifications • Power Supply: AC 100-240 V, 50/60 Hz; Power Consumption: 50 W. • Chassis: 2U; Size: 482 x 88 x 297 mm; Net Weight: 4.4 kg. • Operating Temperature/Humidity: -10°C to 60°C / 20%-90% RH, no condensation. • Storage Temperature/Humidity: -20°C to 60°C / 10%-95% RH, no condensation.