

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	All-in-One LED Controller	Brand: Huidu Model: HD-VP210H Product Type: All-in-One LED Controller Country of Origin: China Country of Manufacturer: China Key Features • Three-in-one design integrating video processor, 2-way Gigabit network output and U-disk playback. • Supports 5 synchronous signal inputs plus USB playback for video and image content. • Maximum LED control capacity: 1.3 million pixels; up to 3840 pixels wide and 2500 pixels high. • Supports pixel-to-pixel display, non-rectangular load, signal switching, cropping and scaling. • Supports 16 scene presets, brightness/color-temperature adjustment and mobile APP wireless control. • Supports RS232 central control, Wi-Fi AP/STA modes and optional infrared remote control. Input & Output Specifications • Video Inputs: 2 x HDMI 1.4, 1 x DVI, 1 x VGA, 1 x CVBS; USB 2.0 playback input. • HDMI/VGA Resolution: up to 1920 x 1080p @ 60 Hz; USB video playback up to 1920 x 1080 @ 30 Hz. • LED Outputs: 2 x Gigabit Ethernet ports, each supporting up to 650,000 pixels. • Audio: 1 x TRS 3.5 mm stereo input and 1 x TRS 3.5 mm stereo output. Control & Processing Specifications • Control Interfaces: USB-B, Wi-Fi antenna interface and RJ45 central-control interface. • Supports U-disk plug-and-play, limited conversion/full output and one-click freeze. • Supports common USB video formats including MP4, AVI, MPG, MKV, MOV, VOB and RMVB. • Image formats: JPG, JPEG, PNG and BMP. Electrical & Physical Specifications • Power Supply: AC 100-240 V, 50/60 Hz; Power Consumption: 14 W. • Chassis: 1U standard; Size: 482 x 44 x 240 mm; Net Weight: 2.6 kg. • Working Temperature/Humidity: -20°C to 55°C / 20%-90% RH, no condensation. • Storage Temperature/Humidity: -20°C to 60°C / 10%-95% RH, no condensation.

