

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	All-in-One LED Controller	Brand: Huidu Model: HD-VP410H Product Type: All-in-One LED Controller Country of Origin: China Country of Manufacturer: China Key Features • Three-in-one design integrating video processor, 4-way Gigabit LED output and U-disk playback. • Supports 5 synchronous signal inputs plus USB playback for videos and images. • Maximum LED control capacity: 2.6 million pixels. • Pixel-to-pixel display, non-rectangular loading, signal switching, cropping and scaling. • Supports 16 scene presets, brightness/color-temperature adjustment and mobile APP wireless control. • RS232 central control support; infrared remote, 4G and SDI options available. Input & Processing Specifications • Video Inputs: 2 x HDMI 1.4, 1 x DVI, 1 x VGA and 1 x CVBS. • USB Input: USB 2.0; supports direct playback up to 1920 x 1080 @ 30 Hz. • HDMI/VGA Input Resolution: up to 1920 x 1080p @ 60 Hz; DVI supports 1080p. • Audio Input: 1 x TRS 3.5 mm two-channel plus HDMI embedded audio. • Optional SDI Input: SD-SDI / HD-SDI / 3G-SDI up to 1920 x 1080 @ 60 Hz. Output & Control Specifications • LED Outputs: 4 x Gigabit network ports; 650,000 pixels per port. • Maximum Load: 2.6 million pixels; max horizontal 3840 pixels / vertical 2500 pixels. • Audio Output: 1 x TRS 3.5 mm two-channel output. • Control Interfaces: USB-B, Wi-Fi and RJ45 for central control equipment. • Wi-Fi Modes: Station, AP and Station + AP; supports mobile phone APP control. Electrical & Physical Specifications • Power Supply: AC 100-240 V, 50/60 Hz; Power Consumption: 14 W. • Chassis: 1U standard; Size: 482 x 44 x 240 mm; Net Weight: 2.6 kg. • Working Temperature/Humidity: -20°C to 55°C / 20%-90% RH, no condensation. • Storage Temperature/Humidity: -20°C to 60°C / 10%-95% RH, no condensation.

