

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	All-in-One Video Processor	Brand: Huidu Model: HD-VP830 Product Type: All-in-One Video Processor Country of Origin: China Country of Manufacturer: China Key Features • 2-in-1 architecture integrating a video processor with 8-way Gigabit LED network output. • Supports 4 signal inputs with arbitrary source switching: 2 x HDMI, 1 x DVI and 1 x SDI. • Maximum LED loading capacity: 5.2 million pixels. • Supports three-window display with PIP and POP functions. • Built-in Wi-Fi for mobile APP wireless operation and IR wireless control. • Brightness adjustment, key lock, RS232 centralized control and 8 user preset templates. Input & Processing Specifications • Video Inputs: 2 x HDMI, 1 x DVI and 1 x SDI. • HDMI: HDMI 1.3 backward compatible, up to 1920 x 1080 @ 60 Hz; supports audio input. • DVI: DVI 1.0; PC resolution up to 1920 x 1200 and HD up to 1080p. • SDI: SD-SDI / HD-SDI / 3G-SDI, up to 1920 x 1080 @ 60 Hz. • Audio Input: 1 x TRS 3.5 mm audio input plus HDMI embedded audio. Output & Control Specifications • LED Outputs: 8 x Gigabit Ethernet ports; 655,360 pixels loading capacity per port. • Maximum Load: 5.2 million pixels; max width 8192 pixels / max height 4096 pixels. • Audio Output: 1 x TRS 3.5 mm dual-channel output. • Control Interfaces: USB-B for PC debugging, RS232 for centralized control and Wi-Fi antenna interface. • Display Functions: Three-window display, PIP/POP, screen freeze and preset scenario recall. Electrical & Physical Specifications • Power Supply: AC 100-240 V, 50/60 Hz; Power Consumption: 50 W. • Chassis: 1.5U; Size: 482 x 65 x 270 mm; Net Weight: 3.35 kg. • Operating Temperature/Humidity: -20°C to 55°C / 20%-90% RH, no condensation. • Storage Temperature/Humidity: -20°C to 60°C / 10%-95% RH, no condensation.