

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	All-in-One Controller	Brand: NovaStar Model: DSP1000 Pro Product Type: All-in-One LED Controller Country of Origin: China Country of Manufacturer: China Key Features • Combines LED video processing and video control functions in one device. • Supports Video Controller, Fiber Converter and ByPass working modes. • 10 Gigabit Ethernet outputs with total loading capacity up to 6.5 million pixels. • Maximum output width 10,240 pixels and maximum height 8,192 pixels. • Supports up to 4K x 2K @ 60 Hz video input and 6-layer display processing. • Provides output scaling, low latency and pixel-level brightness/chroma calibration. Input & Processing Specifications • Inputs: 1 x HDMI 2.0 (IN & LOOP), 2 x HDMI 1.3, 1 x 10G optical fiber port (OPT 1), 1 x 3G-SDI (IN & LOOP) and 1 x USB 3.0. • Maximum video input resolution: 4K x 2K @ 60 Hz. • Supports multiple video inputs, 6 layers, output scaling and low-latency processing. Output & Interface Specifications • Outputs: 10 x Gigabit Ethernet ports, 2 x fiber outputs, 1 x HDMI 1.3 monitoring output and 1 x 3D connector. • OPT 1 sends the output on Ethernet ports 1-10; OPT 2 copies or backs up the output on Ethernet ports 1-10. • OPT 1 is self-adaptive for either video input or sending-card output. Electrical & Physical Specifications • Power Input: 100-240 V~, 50/60 Hz; Rated Power Consumption: 43 W. • Dimensions: 482.6 x 302.2 x 50.1 mm; Net Weight: 3.9 kg; Total Weight: 6.5 kg. • Operating: 0°C to 50°C / 5%-85% RH, non-condensing. • Storage: -10°C to +60°C / 5%-95% RH, non-condensing. • Carrying Case: 545 x 425 x 145 mm; Packing Box: 565 x 450 x 175 mm; Typical Noise: 45 dB(A).

