

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	LED Playback Control Processor	Brand: NovaStar Model: TU40 Pro Product Type: LED Playback Control Processor Document Version: V1.0.0 Country of Origin: China Country of Manufacturer: China Key Features - Integrates Android 13.0 system, sending card and video processing functions into one unit. - Supports third-party apps with powerful interaction, display and playback control capabilities. - Maximum load capacity up to 13 million pixels. - Wireless screen mirroring from Windows, macOS, iOS and Android. - Playback of 2 streams of 4K, 6 streams of 1080p, 10 streams of 720p, or 20 streams of 360p video. - Four display modes: Standard, Meeting, Vivid and Skin. - Supports HDR10, Image Booster, image quality enhancement, eye comfort mode and low-power standby. Input & Output Specifications - Inputs: 1 x HDMI 1.3, 2 x HDMI 2.0, 2 x USB 2.0, 1 x USB 3.0. - Outputs: 20 x Gigabit Ethernet, 2 x 10G OPT outputs, 1 x HDMI 1.3 monitoring output. - Audio Outputs: 1 x SPDIF digital, 1 x 3.5 mm, 1 x HDMI eARC, 1 x Phoenix audio output. - HDMI 1.3 max input resolution: 1920 x 1080 @ 60 Hz. - HDMI 2.0 max input resolution: 3840 x 2160 @ 60 Hz. - Output image scaling: Width 64-16384 px; Height 64-8192 px; total load capacity <= 13 million pixels. Control & Processing Specifications - Android 13.0 desktop UI with 8 GB RAM and 128 GB internal storage. - Processor: Quad-core A73 + quad-core A53 ARM processor @ 2.2 GHz. - Control via front panel LCD, remote control, ViPlex Handy and VNNOX Care mobile app. - Dual Wi-Fi modes, Bluetooth 5.1 and Gigabit Ethernet control port with TCP/IP support. - Supports screen drawing/commenting, reverse control, camera, sound system and infrared touch frame peripherals. Electrical & Physical Specifications - Power Input: 100-240V~, 50/60 Hz, 2.5A Max. - Rated Power Consumption: 53.9 W. - Dimensions: 445.0 x 383.0 x 49.9 mm. - Net Weight: 4.54 kg. - Operating Environment: -20 C to +50 C / 5%-85% RH, non-condensing. - Storage Environment: -20 C to +70 C / 5%-95% RH, non-condensing. Certifications - CQC, SRRC, CE, FCC, IC.

