

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	All-in-One Controller	Brand: NovaStar Model: VX2000 Pro Product Type: All-in-One LED Controller Country of Origin: China Country of Manufacturer: China Key Features • Integrated video processing and LED control with Video Controller, Fiber Converter and ByPass modes. • 20 Gigabit Ethernet outputs with total loading capacity up to 13 million pixels. • Maximum output width 16,384 pixels and maximum height 8,192 pixels. • Supports 12 x 2K layer resources, up to 256 user presets, OSD, 3D, HDR10/HLG and image scaling. • Supports HDMI mosaic, fiber input mosaic, low latency down to 0 frame in ByPass mode and Genlock synchronization. • Pixel-level brightness/chroma calibration, end-to-end backup, device restoration and power-failure data saving. Input & Processing Specifications • Inputs: 1 x DP 1.2, 2 x HDMI 2.0, 4 x HDMI 1.3, 1 x 12G-SDI (IN & LOOP), 2 x 10G OPT and 1 x USB 3.0. • DP 1.2 / HDMI 2.0: Maximum 4096 x 2160 @ 60 Hz; supports 8/10/12-bit input and frame rates up to 240 Hz. • HDMI 1.3: Maximum 1920 x 1080 @ 60 Hz; frame rates up to 240 Hz; 12G-SDI supports up to 4096 x 2160 @ 60 Hz. • USB Playback: H.264 up to 4K@30fps; H.265 up to 4K@60fps; decoded image resolution up to 3840 x 2160. Output & Control Specifications • Outputs: 20 x Gigabit Ethernet, 4 x 10G optical fiber, 1 x HDMI monitoring output and 1 x 3D connector. • Single Ethernet Port Capacity: Up to 650,000 pixels at 8-bit color depth. • Audio: 1 x 3.5 mm input and 1 x 3.5 mm output; audio sampling rate up to 48 kHz. • Control: 2 x Ethernet, USB 2.0, RS232, Genlock IN-LOOP and light sensor; supports NovaLCT, Unico and VICP. Electrical & Physical Specifications • Power Input: 100-240 V AC, 50/60 Hz, 2.5 A-1.0 A; Rated Power Consumption: 83 W. • Dimensions: 482.6 x 493.0 x 94.6 mm; Net Weight: 7.4 kg. • Operating: 0°C to 50°C / 5%-85% RH, non-condensing. • Storage: -10°C to 60°C / 5%-95% RH, non-condensing; Typical Noise Level: 45 dB(A). • Certifications: CE, FCC, IC, PSE, RCM, EAC, UL, CB, KC, RoHS.