

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	Control Card	Brand: Huidu Model: HD-C16L Product Type: LED Display Asynchronous Control System Country of Origin: China Country of Manufacturer: China Key Features - Integrates sending card, receiving card and playback terminal in one control card. - Supports video, image, GIF, text, WPS documents, tables, clocks and timing programs. - Standard 2.4 GHz Wi-Fi with LedArt mobile APP wireless control. - Supports XiaoHui Cloud remote cluster management; optional 4G networking. 60 Hz frame-rate output with smooth content playback and remote power control. - Onboard receiver and 12 HUB75E interfaces for direct LED module connection. Display Control & Interface Specifications - Maximum Control Range: 650,000 pixels; onboard card load: up to 200,000 pixels. - Maximum Width: 8,192 pixels (width >1,920 triggers discount); maximum height: 1,920 pixels. - Outputs: 1 x Gigabit LED network port, 12 x HUB75E, 1 x TRS 3.5 mm audio output. - Inputs/Communication: 1 x 100M LAN, USB, Wi-Fi, UART; optional RS-232/RS-485. - Sensor Interfaces: Temperature, universal environmental sensor and GPS interfaces. - Onboard Relay: Remote power control; max load AC 250 V/3 A or DC 30 V/3 A. Hardware & Media Specifications - CPU/GPU: 1.5 GHz quad-core CPU with Mali-G31 GPU. - Video: Supports up to 2 channels of 1080P playback; 1080P@60fps hardware decoding. - Internal Storage: 4 GB (approximately 2 GB available). - Video Formats: AVI, WMV, MPG, RM/RMVB, VOB, MP4, FLV and other common formats. - Image Formats: BMP, GIF, JPG/JPEG, PNG, PBM, PGM, PPM and other common formats. - System Software: Linux 4.4 operating system and FPGA software. Electrical & Physical Specifications - Input Power: DC 5 V (4.6-5.5 V), 3 A; Maximum Power Consumption: 8 W. - Size: 174.9 x 101.4 mm; Net Weight: 0.14 kg. - Working Temperature/Humidity: -40°C to 80°C / 0%-80% RH, no condensation. - Storage Temperature/Humidity: -40°C to 80°C / 0%-80% RH, no condensation.

