

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	Receiving Card	Brand: Huidu Model: HD-R712 Product Type: LED Display Receiving Card Version: V2.1 Country of Origin: China Country of Manufacturer: China Key Features • Supports both synchronous and asynchronous LED display control systems; no HUB adapter board required. • 12 onboard HUB75E interfaces for direct connection to LED modules. • Compatible with common IC modules and most PWM IC modules. • Supports scan modes from static scan up to 1/128 scan. • Dual Gigabit Ethernet ports are interchangeable and support flexible multi-card cascading. • Integrated screen test function for checking brightness uniformity and module flatness. Control & Interface Specifications • Maximum Loading Capacity: 262,144 pixels (512 x 512) according to the parameter table. • Recommended Loading: 128 x 1024 pixels for conventional chips; 256 x 1024 pixels for PWM chips. • Gray Scale: 256-65,536; Smart Setting supported. • Communication: Gigabit Ethernet; Super Cat5/Cat6 cable distance up to 80 m. • Ports: 2 x DC 5V power, 2 x 1 Gbps Ethernet, 12 x HUB75E. Electrical & Physical Specifications • Input Voltage: DC 4.0-5.5 V; Power Consumption: 5 W. • Working Temperature: -40°C to 80°C; Working Humidity: 0-90% RH. • Storage Humidity: 0-90% RH. • Dimensions: approximately 142 x 91.21 mm; Net Weight: approximately 91 g.

