

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	Receiving Card	Brand: Huidu Model: HD-R732 Product Type: LED Display Receiving Card Version: V0.1 Country of Origin: China Country of Manufacturer: China Key Features • Designed for fine-pixel-pitch LED screens with direct module connection. • 8 x onboard HUB320 interfaces; no separate HUB adapter board required. • Compatible with common IC modules and most PWM IC modules. • Supports scan modes from static scan up to 1/128 scan. • Dual Gigabit Ethernet ports support flexible cascading and interchangeable use. • Integrated screen test function checks brightness uniformity and module flatness. Control & Interface Specifications • Maximum Recommended Loading Capacity: 262,144 pixels (256 x 1024). • P1.538 and P1.25 modules can be fully loaded using all 8 HUB320 ports. • Gray Scale: 256-65,536; Smart Setting and flexible multi-card connection supported. • Communication: Gigabit Ethernet; Super Cat5/Cat6 cable distance up to 80 m. • Ports: 2 x 5 V DC power, 2 x 1 Gbps Ethernet, 8 x HUB320. Electrical & Physical Specifications • Input Voltage: DC 4.0-5.5 V; Power Consumption: 5 W. • Working Temperature: -40°C to +75°C; Storage Temperature: -40°C to +105°C. • Working Humidity: 0-95% RH. • Dimensions: approximately 141.5 x 91.21 mm; Net Weight: 0.104 kg. • Certifications: CE, FCC, RoHS.

