

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	Receiving Card	Brand: NovaStar Model: NV3210 Product Type: LED Receiving Card Country of Origin: China Country of Manufacturer: China Key Features • 10 standard HUB320F connectors for stable module communication. • Supports up to 40 groups of RGB real-pixel data, 40 groups of 3-LED sub-pixel data, or 30 groups of 4-LED sub-pixel data. • Supports Color Management, 18bit+, HDR10/HLG and pixel-level brightness/chroma calibration. • Quick adjustment of dark/bright lines and multi-batch brightness adjustment. • Supports low latency, 3D, individual RGB Gamma adjustment and 90° image rotation. • Built-in monitoring and reliability functions including temperature/voltage monitoring, bit-error detection and multiple backup mechanisms. Performance & Interface Specifications • PWM Driver IC Load: up to 512 x 512 @ 60 Hz; 12-bit sources up to 512 x 384 @ 60 Hz. • Common Driver IC Load: up to 512 x 384 @ 60 Hz; 10/12-bit sources with M3 controllers up to 256 x 384 @ 60 Hz. • Module Interface: 10 x HUB320F connectors; line decoding supports A, B and C signals. • Network: Gigabit Ethernet ports for sending-card connection and receiving-card cascading. • Maintenance: Self-test, stored-image settings, firmware/configuration readback and module flash management. Electrical Specifications • Input Voltage: DC 3.8 V to 5.5 V; Rated Current: 0.5 A. • Rated Power Consumption: 2.5 W. Physical & Environmental Specifications • Dimensions: 146.0 x 91.5 x 19.2 mm; Net Weight: 99.5 g. • Operating Temperature/Humidity: -20°C to +70°C / 10%-90% RH, non-condensing. • Storage Temperature/Humidity: -25°C to +125°C / 0%-95% RH, non-condensing. • Certifications: RoHS, EMC Class A.

