

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	Receiving Card	Brand: NovaStar Model: DH7512 Product Type: LED Receiving Card Country of Origin: China Country of Manufacturer: China Key Features • General receiving card for full-color LED display systems. • Maximum loading capacity: 512 x 512 pixels per receiving card. • 12 HUB75 outputs supporting up to 24 groups of parallel RGB data. • Supports Color Management and 18Bit+ for improved color and grayscale performance. • Supports pixel-level brightness and chroma calibration and quick dark/bright line adjustment. • Supports individual Gamma adjustment for RGB, 3D and 90° image rotation. • Loop backup and dual backup of configuration parameters/application program improve reliability. Performance & Interface Specifications • Maximum Loading Capacity: 512 x 512 pixels (NovaLCT V5.3.1 or later required). • Module Outputs: 12 x HUB75; Parallel RGB Data: up to 24 groups. • Monitoring: receiving-card temperature and voltage monitoring; bit-error-rate monitoring supported. • Maintainability: Mapping, pre-stored image, firmware readback and configuration-parameter readback. Electrical Specifications • Input Voltage: DC 3.3 V to 5.5 V • Rated Current: 0.5 A; Rated Power Consumption: 2.5 W Physical & Environmental Specifications • Dimensions: 145.7 x 91.5 x 18.4 mm; Net Weight: 93.1 g • Operating: -20°C to +70°C / 10% RH to 90% RH, non-condensing • Storage: -25°C to +125°C / 0% RH to 95% RH, non-condensing • Certifications: RoHS, EMC Class A

