

Full Technical Specification

Sl. No	Item Name	Technical Specification
1	Receiving Card	Brand: NovaStar Model: A5s Plus Product Type: LED Display Receiving Card Country of Origin: China Country of Manufacturer: China Key Features • Compact receiving card with high-density connectors for LED display systems. • Supports both PWM driver IC and common driver IC loading configurations. • PWM driver IC loading up to 512 x 384 @ 60 Hz for 8-bit video sources. • Common driver IC loading up to 384 x 384 @ 60 Hz for 8-bit video sources. • Built-in power and running indicators for operating-status monitoring. Loading Capacity Specifications • PWM Driver IC: 512 x 384 @ 60 Hz (8-bit); 256 x 384 @ 60 Hz (10-bit and 12-bit). • Common Driver IC: 384 x 384 @ 60 Hz (8-bit); 192 x 384 @ 60 Hz (10-bit and 12-bit). Electrical Specifications • Input Voltage: DC 3.8 V to 5.5 V. • Rated Current: 0.6 A; Rated Power Consumption: 3.0 W. Physical & Environmental Specifications • Dimensions: 70.0 x 45.0 x 8.3 mm; Net Weight: 16.2 g. • Operating Temperature/Humidity: -20°C to +70°C / 10%-90% RH, non-condensing. • Storage Temperature/Humidity: -25°C to +125°C / 0%-95% RH, non-condensing. • Packing: Blister pack; 80 receiving cards per box; box size 392.0 x 200.0 x 123.0 mm.

