LVS Series
Outdoor LED Display Module

Durable, Flexible Displays for Every Outdoor Need

The LVS series outdoor full-color module is an excellent high-performance display product compatible with mainstream control systems in the market. Its manufacturing process,and material management strictly follow the highest standards to ensure the product reliability and durability. LVS series is available in two sizes: 320x160mm and 80x320mm. It has flexible design, which allows for easy installation and maintenance. It is widely used in various outdoor scenarios such as commercial centers, sports venues, and city squares.

- High Performance Kit
- Universal HUB Interface
- 160° Wide Viewing Angle
- Single Pixel Calibration
- ≥100% NTSC Color Gamut
- Color Temperature and Brightness Adjustable

7680Hz Super High Refresh Rate

< Smooth, flicker-free visuals for enhanced viewing experience.
< Crisp motion clarity, perfect for dynamic content display.

Automatic Adjustment

< Automatic adjustment of brightness and color temperature.
< Bringing comfort, realizing power saving.

45° Edge Cut Module

< 80x320mm size.
< Can be used for right angle splicing, concave and convex splicing.

Item	LVS0200	LVS0250	LVS0307	LVS0400	LVS0500	LVS0592	LVS0800	LVS1000
Pixel Structure	SMT 3 in 1							
Pixel Pitch (mm)	2	2.5	3.076	4	5	5.925	8	10
Module Resolution (WxH)	160x80	128x64	104x52	80x40	64x32	52x27	40x20	32x16
Module Size (mm) (WxH)	320x160							
Module Weight (Kg)	0.46±0.05	0.45±0.05	0.45±0.05	0.43±0.05	0.41±0.05	0.42±0.05	0.42±0.05	0.42±0.05
Unit Area (m^2)	0.0512							
Pixel Density (dots/m^2)	250000	160000	105625	62500	40000	27216	15625	10000
White Balance Brightness (nits)	≥4500	≥5000						
Color Temperature (K)	3000~38000 adjustable							
Horizontal Viewing Angle (°)	160							
Vertical Viewing Angle (°)	140							
Deviation from the Color Luminous Center	<3%							
Brightness Uniformity	≥97%							
Contrast Ratio	5000:1							
Peak Power Consumption (W/m^2)	781	≤660						
Average Power Consumption (W/m^2)	260	≤220						
Power Supply Requirements (V)	DC:4.5							
Single Module Current (A)	7.5A							
Drive Mode (Constant current drive)	20S	16S	13S	10S	8S	7S	4S	2S
Frame Rate (Hz)	50&60							
Refresh Rate (Hz)	≥7680							
Typical Lifespan (hours)	100,000							
Working Temperature Range (℃)	-20 ~ 40							
Storage Temperature Range (℃)	-20 ~ 60							
Working Humidity Range (RH)	10~80% no condensation							
Storage Humidity Range (RH)	10~85% no condensation							

Item	LVS0250R	LVS0307R	LVS0400R	LVS0500R	LVS0592R	LVS0800R	LVS1000R
Pixel Structure	SMT 3 in 1						
Pixel Pitch (mm)	2.5	3.076	4	5	5.9	8	10
Module Resolution (WxH)	32x128	26x104	20x80	16x64	13x54	10x40	8x32
Module Size (mm) (WxH)	80x320						
Module Weight (Kg)	0.29±0.01	0.29±0.01	0.29±0.01	0.28±0.01	0.29±0.01	0.29±0.01	0.29±0.01
Unit Area (m^2)	0.0256						
Pixel Density (dots/m^2)	160000	105625	62500	40000	27216	15625	10000
White Balance Brightness (nits)	≥5000						
Color Temperature (K)	3000~38000 adjustable						
Horizontal Viewing Angle (°)	160						
Vertical Viewing Angle (°)	140						
Deviation from the Color Luminous Center	<3%						
Brightness Uniformity	≥97%						
Contrast Ratio	5000:1						
Peak Power Consumption (W/m^2)	≤660						
Average Power Consumption (W/m^2)	≤220						
Power Supply Requirements (V)	DC:4.5						
Single Module Current (A)	3.8A						
Drive Mode (Constant current drive)	16S	13S	10S	8S	7S	4S	2S
Frame Rate (Hz)	50&60						
Refresh Rate (Hz)	≥7680						
Typical Lifespan (hours)	100,000						
Working Temperature Range (℃)	-20 ~ 40						
Storage Temperature Range (℃)	-20 ~ 60						
Working Humidity Range (RH)	10~80% no condensation						
Storage Humidity Range (RH)	10~85% no condensation						

Remark: The product parameters, descriptions and images are subjest to change without prior notice.

LEYARD

LEYARD HONG KONG INTERNATIONAL CO., LIMITED

Leyard Southern LED Industrial Park, No.6, Guanhe Rd, Longhua District, Shenzhen, China | intlmarketing@leyard.com | www.leyardhk.com