

Transitive Closure of a Graph using DFS

Difficulty Level : Medium • Last Updated : 11 May, 2021

Given a directed graph, find out if a vertex v is reachable from another vertex u for all vertex pairs (u, v) in the given graph. Here reachable mean that there is a path from vertex u to v . The reach-ability matrix is called transitive closure of a graph.

For example, consider below graph

Transitive closure of above graphs is

```
1 1 1 1
1 1 1 1
1 1 1 1
0 0 0 1
```

We have discussed a $O(V^3)$ solution for this [here](#). The solution was based on [Floyd Warshall Algorithm](#). In this post a $O(V^2)$ algorithm for the same is discussed.

Below are abstract steps of algorithm.

1. Create a matrix $tc[V][V]$ that would finally have transitive closure of given graph. Initialize all entries of $tc[][]$ as 0.
2. Call DFS for every node of graph to mark reachable vertices in $tc[][]$. In recursive calls to DFS, we don't call DFS for an adjacent vertex if it is already marked as reachable in $tc[][]$.

reachable from u.

C++

```
// C++ program to print transitive closure of a graph
#include<bits/stdc++.h>
using namespace std;

class Graph
{
    int V; // No. of vertices
    bool **tc; // To store transitive closure
    list<int> *adj; // array of adjacency lists
    void DFSUtil(int u, int v);
public:
    Graph(int V); // Constructor

    // function to add an edge to graph
    void addEdge(int v, int w) { adj[v].push_back(w); }

    // prints transitive closure matrix
    void transitiveClosure();
};

Graph::Graph(int V)
{
    this->V = V;
    adj = new list<int>[V];

    tc = new bool* [V];
```



Related Articles

```
// A recursive DFS traversal function that finds
// all reachable vertices for s.
void Graph::DFSUtil(int s, int v)
{
    // Mark reachability from s to t as true.
    if(s==v){
        if(adjList[v].contains(v))
```

```

    // Find all the vertices reachable through v
    list<int>::iterator i;
    for (i = adj[v].begin(); i != adj[v].end(); ++i)
        if (tc[s][*i] == false)
            DFSUtil(s, *i);
}

// The function to find transitive closure. It uses
// recursive DFSUtil()
void Graph::transitiveClosure()
{
    // Call the recursive helper function to print DFS
    // traversal starting from all vertices one by one
    for (int i = 0; i < V; i++)
        DFSUtil(i, i); // Every vertex is reachable from self.

    for (int i=0; i<V; i++)
    {
        for (int j=0; j<V; j++)
            cout << tc[i][j] << " ";
        cout << endl;
    }
}

// Driver code
int main()
{
    // Create a graph given in the above diagram
    Graph g(4);
    g.addEdge(0, 1);
    g.addEdge(0, 2);
    g.addEdge(1, 2);
    g.addEdge(2, 0);
    g.addEdge(2, 3);
    g.addEdge(3, 3);
    cout << "Transitive closure matrix is \n";
    g.transitiveClosure();
    return 0;
}

```

Java

// JAVA program to print transitive

```

// A directed graph using
// adjacency list representation
public class Graph {

    // No. of vertices in graph
    private int vertices;

    // adjacency list
    private ArrayList<Integer>[] adjList;

    // To store transitive closure
    private int[][] tc;

    // Constructor
    public Graph(int vertices) {

        // initialise vertex count
        this.vertices = vertices;
        this.tc = new int[this.vertices][this.vertices];

        // initialise adjacency list
        initAdjList();
    }

    // utility method to initialise adjacency list
    @SuppressWarnings("unchecked")
    private void initAdjList() {

        adjList = new ArrayList[vertices];
        for (int i = 0; i < vertices; i++) {
            adjList[i] = new ArrayList<>();
        }
    }

    // add edge from u to v
    public void addEdge(int u, int v) {

        // Add v to u's list.
        adjList[u].add(v);
    }

    // The function to find transitive
    // closure. It uses
    // recursive DFSUtil()
    public void transitiveClosure() {

```

```

    for (int i = 0; i < vertices; i++) {
        dfsUtil(i, i);
    }

    for (int i = 0; i < vertices; i++) {
        System.out.println(Arrays.toString(tc[i]));
    }
}

// A recursive DFS traversal
// function that finds
// all reachable vertices for s
private void dfsUtil(int s, int v) {

    // Mark reachability from
    // s to v as true.
    if(s==v){
        if(adjList[v].contains(v))
            tc[s][v] = 1;
    }
    else
        tc[s][v] = 1;

    // Find all the vertices reachable
    // through v
    for (int adj : adjList[v]) {
        if (tc[s][adj]==0) {
            dfsUtil(s, adj);
        }
    }
}

// Driver Code
public static void main(String[] args) {

    // Create a graph given
    // in the above diagram
    Graph g = new Graph(4);

    g.addEdge(0, 1);
    g.addEdge(0, 2);
    g.addEdge(1, 2);
    g.addEdge(2, 0);
    g.addEdge(2, 3);
    g.addEdge(3, 3);
    System.out.println("Transitive closure " +
        "matrix is");
}

```

```
}
```

```
// This code is contributed  
// by Himanshu Shekhar
```

Python

```
# Python program to print transitive closure of a graph  
from collections import defaultdict  
  
# This class represents a directed graph using adjacency  
# list representation  
class Graph:  
  
    def __init__(self,vertices):  
        # No. of vertices  
        self.V= vertices  
  
        # default dictionary to store graph  
        self.graph= defaultdict(list)  
  
        # To store transitive closure  
        self.tc = [[0 for j in range(self.V)] for i in range(self.V)]  
  
    # function to add an edge to graph  
    def addEdge(self,u,v):  
        self.graph[u].append(v)  
  
    # A recursive DFS traversal function that finds  
    # all reachable vertices for s  
    def DFSUtil(self,s,v):  
  
        # Mark reachability from s to v as true.  
        if(s==v){  
            if(adjList[v].contains(v))  
                tc[s][v] = 1;  
        }  
    else  
        self.tc[s][v] = 1  
  
        # Find all the vertices reachable through v  
        for i in self.graph[v]:  
            if self.tc[s][i]==0:  
                self.DFSUtil(s,i)
```

```

        # Call the recursive helper function to print DFS
        # traversal starting from all vertices one by one
        for i in range(self.V):
            self.DFSUtil(i, i)
        print self.tc

# Create a graph given in the above diagram
g = Graph(4)
g.addEdge(0, 1)
g.addEdge(0, 2)
g.addEdge(1, 2)
g.addEdge(2, 0)
g.addEdge(2, 3)
g.addEdge(3, 3)

print "Transitive closure matrix is"
g.transitiveClosure();

# This code is contributed by Neelam Yadav

```

C#

```

// C# program to print transitive
// closure of a graph.
using System;
using System.Collections.Generic;

// A directed graph using
// adjacency list representation
public class Graph
{
    // No. of vertices in graph
    private int vertices;

    // adjacency list
    private List<int>[] adjList;

    // To store transitive closure
    private int[,] tc;

    // Constructor
    public Graph(int vertices)
    {

```

```

    // initialise adjacency list
    initAdjList();
}

// utility method to initialise adjacency list
private void initAdjList()
{
    adjList = new List<int>[vertices];
    for (int i = 0; i < vertices; i++)
    {
        adjList[i] = new List<int>();
    }
}

// add edge from u to v
public void addEdge(int u, int v)
{
    // Add v to u's list.
    adjList[u].Add(v);
}

// The function to find transitive
// closure. It uses
// recursive DFSUtil()
public void transitiveClosure() {

    // Call the recursive helper
    // function to print DFS
    // traversal starting from all
    // vertices one by one
    for (int i = 0; i < vertices; i++) {
        dfsUtil(i, i);
    }

    for (int i = 0; i < vertices; i++) {
        for(int j = 0; j < vertices; j++)
            Console.Write(tc[i, j] + " ");
        Console.WriteLine();
    }
}

// A recursive DFS traversal
// function that finds
// all reachable vertices for s

```



```

    if(s==v){
        if(adjList[v].contains(v))
            tc[s][v] = 1;
        }
    else
        tc[s, v] = 1;

    // Find all the vertices reachable
    // through v
    foreach (int adj in adjList[v])
    {
        if (tc[s, adj] == 0) {
            dfsUtil(s, adj);
        }
    }
}

// Driver Code
public static void Main(String[] args) {

    // Create a graph given
    // in the above diagram
    Graph g = new Graph(4);
    g.addEdge(0, 1);
    g.addEdge(0, 2);
    g.addEdge(1, 2);
    g.addEdge(2, 0);
    g.addEdge(2, 3);
    g.addEdge(3, 3);
    Console.WriteLine("Transitive closure " +
                      "matrix is");
    g.transitiveClosure();
}

// This code is contributed by Rajput-Ji

```

Output:

```

Transitive closure matrix is
1 1 1 1
1 1 1 1
1 1 1 1
- - - -

```

References:

<http://www.cs.princeton.edu/courses/archive/spr03/cs226/lectures/digraph.4up.pdf>

This article is contributed by **Aditya Goel**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Like 0

Previous

Next

RECOMMENDED ARTICLES

Page : 1 2 3

01 Transitive closure of a graph
04, Dec 12

02 Check for transitive property in a given Undirected Graph
09, Feb 21

03 Check if a graph is strongly connected | Set 1 (Kosaraju using DFS)
02, Jun 13

05 Check if a given graph is Bipartite using DFS
03, Aug 18

06 Minimum number of edges between two vertices of a graph using DFS
29, Jan 19

07 Depth First Search or DFS for a Graph

1 (DFS of Unweighted and Undirected)

19, Jan 17

08

represented as adjacency list

22, Sep 17

Article Contributed By :



GeeksforGeeks

Vote for difficulty

Current difficulty : [Medium](#)

Easy

Normal

Medium

Hard

Expert

Improved By : [csecec1702556](#), [Rajput-Ji](#), [easeit](#)

Article Tags : [Graph](#)

Practice Tags : [Graph](#)

Improve Article

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#)

Got It !

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

[About Us](#)
[Careers](#)

[Privacy Policy](#)

[Contact Us](#)

[Copyright Policy](#)

Learn

[Algorithms](#)
[Data Structures](#)

[Languages](#)

[CS Subjects](#)

[Video Tutorials](#)

Practice

[Courses](#)

[Company-wise](#)

[Topic-wise](#)

[How to begin?](#)

Contribute

[Write an Article](#)

[Write Interview Experience](#)

[Internships](#)

[Videos](#)

@geeksforgeeks , Some rights reserved