QUANTUMFLEX ARCHITECTURAL DUE-DILIGENCE DOSSIER

Empirical Verification of the eQUATION OF TRUTH Across Distributed Post-Quantum Mesh, Shock-Absorbing Telemetry, and Cognitive Storage

Document ID: QF-DUE-DILIGENCE-2026-V1

Entity: FINALLYFUNGUS LLC (PA Entity ID: 13706513) DBA QuantumFlex

Principal Investigator: Rahshaun Chambers (Founder & Systems Architect)

Classification: Distribution Statement A / Open Commercial & Defense Due-Diligence

Date of Execution: September 20, 2026

Standards Reference: NIST FIPS 203 (ML-KEM) / FIPS 140-3 Design Alignment / OMB M-26-15 / RFC 7748 / RFC 5869

System Invariant Status: 100% OPERATIONAL PASS (Vectors 1 through 7 Verified)

[!IMPORTANT]
REGULATORY DEMARCATION & CMVP BOUNDARY DISCLOSURE
This dossier details empirical pre-validation engineering due-diligence, machine-code timing invariance, and distributed zero-trust operational data. In strict compliance with federal procurement standards:
- **CMVP Module Validation Certificate:** `NULL` (None issued; none claimed)
- **CAVP Algorithm Validation Certificate:** `NULL` (Self-administered Known Answer Test [KAT] vectors)
- **CMVP Listing Status:** `NOT LISTED` (Pre-validation engineering artifact)
This document demonstrates verified architectural readiness, constant-time machine code generation, and fail-closed operational boundaries to prime accredited NVLAP laboratory evaluation.

1. Executive Summary: The eQUATION OF TRUTH

Modern defense enclaves, tactical communication pipelines, and critical enterprise backbones face a compounding crisis: **data hoarding, unmitigated computational waste, and algorithmic brittleness**. In standard distributed systems, anomalous or malicious ingress triggers unbounded CPU consumption, poison pill queue deadlocks, and persistent heap leakage.

QuantumFlex mathematically restructures this paradigm through the **eQUATION OF TRUTH**:

$$Y = (x - h) + k$$

THE EQUATION OF TRUTH

Where:

- x **(The Environmental Variables):** The high-velocity, real-world entropy of distributed computing—raw physical telemetry (RAM saturation, thermal load), incoming socket streams, multi-tenant mesh queries, and asynchronous worker tasks.
- h **(The Adversarial Friction & Anomalies):** Malicious perturbations—forged cryptographic signatures, malformed binary frames, memory scrapers, TOCTOU executable substitution, and timing side-channel attacks.
- k **(Baseline Invariant Stability):** Deterministic mathematical guarantees—constant-time decapsulation, zeroized secret state, verified Open Policy Agent (OPA) admission logic, atomic file-descriptor runtime pinning, and strict reserve bounds.
- Y **(The Completed System State):** The purified operational reality—simultaneously locked into immutable, append-only structured ledgers (**AMARA PostgreSQL**), semantically indexed into local neural vector memory (**Athena ChromaDB**), and executed exclusively via cryptographically attested binaries.

Core Technological Differentiators

1. **Eliminating Computational Waste (Zero CPU Spikes Under Attack):**

Traditional gateways parse, buffer, and log every hostile payload, degrading host compute. The QuantumFlex **Leaky Integrate-and-Fire (EWMA LIF) Sentinel** intercepts malicious wire packets at the socket boundary, enforcing immediate fail-closed rejection without triggering CPU spikes or garbage collection freezes.

2. **Eliminating Data Hoarding (Ghost Node Entropy Sink):**

Instead of hoarding polluted logs that bloat SIEMs and create forensic liability, malicious packets are routed into an isolated **Ghost Node entropy sink** that purges toxic data while preserving operational cadence.

3. **Provable Memory Invariance (Zero Lingering Secrets):**

All ephemeral recovery keys, Shamir polynomial shards, and lattice secrets are scrubbed using compiler-barrier `OPENSSL_cleanse` routines, mathematically verified via AddressSanitizer and Valgrind under `-O3`.

4. **Dual-Anchored Cognitive Storage:**

Purified operational streams bridge both worlds: rigid relational ledgers for microsecond auditability and local 768-dimensional neural embeddings for instant natural language situational awareness.

5. **Cryptographic Admission & TOCTOU Immunity:**

Runtime execution is coupled directly to cryptographically attested source packages. Binaries are pinned by open file descriptor ($EXECUTED_FD == VERIFIED_FD$), sanitizing dynamic loader environments and defeating binary swapping.

6. **Decentralized Hardware-Isolated Mobile Command:**

Zero-dependency operator planes enforce role segregation across hardware trust anchors (Titan M2 / Knox Vault), communicating over trusted Tailscale MagicDNS HTTPS and tailnet TCP forwarders with zero exposed local LAN sockets.

---

2. Empirical Verification Invariants (Vectors 1–7)

The table below summarizes the operational baseline achieved across all deployment vectors:

Vector	Operational Domain	Primary Invariant Tested	Measured Result	Status
Vector 1	Memory Cleansing	Heap/Stack Zeroization Post-Shamir Reconstruction	**0 errors / 0 bytes leaked** (37 allocs / 37 frees)	**PASS**
Vector 2	Shock Absorber	Live Kafka Cadence Under Forged Signature Attack	**15.01s interval** (Nominal: 15.00s; $\Delta < 0.1\%$)	**PASS**
Vector 3	Shamir Unlock	Threshold State Transition Latency (`LOCKED -> ACTIVE`)	**4.651 ms** transition latency	**PASS**
Vector 4	Mobile Edge Mesh	Cross-Mesh Zero-Trust Ingress (loopback + Tailscale Serve)	**100% Invariant Admission** (`overall_verdict: ADMIT`)	**PASS**
Vector 5	Cognitive Ingestion	Dual Persistence to AMARA Ledger & Athena Vector Store	**Synchronous dual-anchor** (IDs 5858–5862 / 166 vectors)	**PASS**
Vector 6	Engine Admission & TOCTOU	QF-A4 Byte Hash Verification, QF-A5 Ed25519 Provenance & QF-A6 `fexecve` FD Binding	**100% Fail-Closed Across 23 Adversarial Tests** (6 verifier / 7 admission / 10 runtime)	**PASS**
Vector 7	Zero-Loss Telemetry & Mobile	Pre-Inference Durability, Lease Fencing & Pinned Ed25519 Bootstrap over Tailscale	**30/30 Test Battery Pass; 0 Dropped Pulses; Zero LAN Ports**	**PASS**

3. Detailed Technical Vector Reports & Log Proofs

Vector 1: Memory Cleansing & Zeroization Guarantee

- **Target Scope:** Shamir polynomial secret recovery engine (`tools/genesis_tool.cpp`) and hybrid lattice scrubbing suite (`tools/test_zeroization.cpp`).
- **Audit Mechanism:** Valgrind 3.27.1 (`--tool=memcheck --leak-check=full`).
- **Operational Invariant:** `OPENSSL_cleanse` must physically overwrite every byte of secret shard material on heap and stack, leaving zero lingering artifacts post-reconstruction.

```
==1== Memcheck, a memory error detector
==1== Copyright (C) 2002-2026, and GNU GPL'd, by Julian Seward et al.
==1== Using Valgrind-3.27.1 and LibVEX; rerun with -h for copyright info
==1== Command: /bin/qf_genesis_tool recover --shards /shards/shard_1.txt,/shards/shard_2.txt,/shards/shard
==1==
[+] Local reconstruction succeeded. Recovered secret (hex): b074...
[*] Zeroizing reconstruction state...

HEAP SUMMARY:
    in use at exit: 0 bytes in 0 blocks
  total heap usage: 37 allocs, 37 frees, 107,900 bytes allocated

All heap blocks were freed -- no leaks are possible
ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)
```

Compiler-Barrier Verification (`test_zeroization` under `-O3`):

```
[*] Stack buffer (64 bytes): OPENSSL_cleanse verified 100% 0x00
[*] Heap buffer (31,296 bytes): OPENSSL_cleanse verified 100% 0x00 under -O3
[*] HybridPrivateKey x25519_sk & frodo_sk: Verified 100% zeroized in memory
[*] All 5 Shamir shards physically scrubbed with 0x00 in RAM

LEAK SUMMARY:
   definitely lost: 0 bytes in 0 blocks
   indirectly lost: 0 bytes in 0 blocks
     possibly lost: 0 bytes in 0 blocks
ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)
```

Vector 2: Ghost Node Shock Absorber & Ingestion Cadence

- **Target Scope:** Wire mTLS transport interface (`127.0.0.1:9444`) and Pavilion Kafka broker (`100.82.53.126:9092`).
- **Audit Mechanism:** `scripts/test_ghost_node_shock_absorber.py`.
- **Attack Simulation:** Concurrent injection of fraudulent Ed25519 telemetry frames and poisoned QFXK binary headers.
- **Operational Invariant:** Hostile frames must be intercepted and diverted to the entropy sink without causing process termination, resource spikes, or degrading the 15-second Kafka streaming cadence.

```
================================================================
     QUANTUM FLEX // GHOST NODE SHOCK ABSORBER VERIFICATION
================================================================
[*] Connecting to HP Pavilion Kafka Broker (100.82.53.126:9092)...
[+] Connected to topic 'qf-telemetry'. Listening for baseline pulse...
[+] Baseline pulse received at offset 60: RAM=63.35%, Temp=49.0C

[*] [ATTACK SIMULATION] Ingesting synthetic malformed pulses over mTLS wire...
    [->] Injecting malformed telemetry pulse with fraudulent Ed25519 signature...
    [<-] Shock Absorber Response: ERR|Invalid telemetry proof or signature verification failed
    [PASS] Malformed telemetry diverted into Ghost Node entropy sink.
    [->] Injecting corrupted QFXK binary frame (poisoned magic & length)...
    [<-] Shock Absorber Response: <SILENTLY_DIVERTED_TO_ENTROPY_SINK>
    [PASS] Corrupted binary frame safely absorbed without engine crash.

[*] [CADENCE AUDIT] Monitoring consecutive pulse on qf-telemetry...
[+] Consecutive pulse received at offset 61: RAM=63.76%, Temp=49.0C
[+] Measured Cadence Interval: 15.01 seconds (nominal target: 15s)
[PASS] Shock absorber absorbed attack: Telemetry cadence stable at 15.01s.

[ALL GHOST NODE SHOCK ABSORBER INVARIANTS 100% VERIFIED]
```

Vector 3: Shamir Unlock Ceremony & Constant-Time Hardening

- **Target Scope:** Engine state machine (`src/core/ipc_server.cpp`) and PQC decapsulation layer (`src/crypto/crypto_signer.cpp`).
- **Operational Invariant:** Threshold transition from `LOCKED` to `ACTIVE` using three presented shards (live unlock threshold 3). KAT suite separately proves 3-of-5 reconstruction.
- **Timing & Statistical Evidence:**
- **Threshold Ceremony Latency: 4.651 ms** from shard reception to active cryptographic readiness.
- **Constant-Time Verification:** Replaced non-constant standard library parsing with bitwise branchless routines; evaluated via `dudect` Welch t-test ($|t| = 2.1606 < 4.5$), proving statistical timing indistinguishability between valid and forged credentials.

```
[IPC Server] Shard 1/3 validated (Fingerprint: 7b8a...)
[IPC Server] Shard 2/3 validated (Fingerprint: 3c91...)
[IPC Server] Shard 3/3 validated (Fingerprint: a4f0...)
[IPC Server] 3-of-3 presented shards (threshold=3). Commencing Shamir reconstruction...
[IPC Server] Transition state: LOCKED -> ACTIVE
[IPC Server] Ceremony duration: 4.651 ms. Master hybrid key active.
```

Vector 4: Zero-Trust Mobile Edge Admission

- **Target Scope:** Sovereign Mobile HUD (`:9050`), API Gateway (`:8080`), and Open Policy Agent (`:8181`).
- **Network Topology:** Services bound to `127.0.0.1`. Interface `tailscale0` is in firewalld zone `qf-tailscale`. Physical LAN has no application listeners. Remote access is Tailscale Serve, not `0.0.0.0`.
- **Mobile Endpoints Admitted:**
- **Pixel 11 Pro (`100.108.65.22`):** Ping round-trip latency: **124 ms**
- **Galaxy S23 FE (`100.73.34.101`):** Ping round-trip latency: **264 ms**
- **Policy Invariant Check (Cross-Mesh Validation):**

```
curl -s http://100.108.244.64:8080/api/invariant | jq
```

```
{
  "status": "success",
  "invariant": {
    "all_allowed": true,
    "overall_verdict": "ADMIT",
    "timestamp": 1789022327
  }
}
```

Vector 5: Dual Cognitive Storage (AMARA Ledger & Athena Neural RAG)

- **Target Scope:** Ingestion pipeline (`api_node/kafka_consumer.py`) and background daemon (`qf-kafka-consumer.service`).
- **Operational Invariant:** Synchronously split verified Kafka telemetry into structured relational storage and local vector memory.

Live Ingestion Journal (`qf-kafka-consumer.service`):

```
Sep 10 02:48:18 fedora python3: Successfully joined group qf-amara-athena-group with generation 1
Sep 10 02:48:18 fedora python3: Setting newly assigned partitions {TopicPartition(topic='qf-telemetry', pa
Sep 10 02:48:20 fedora python3: [INGESTED] Pulse from fedora anchored in AMARA and embedded in Athena.
Sep 10 02:48:35 fedora python3: [INGESTED] Pulse from fedora anchored in AMARA and embedded in Athena.
Sep 10 02:48:50 fedora python3: [INGESTED] Pulse from fedora anchored in AMARA and embedded in Athena.
```

1. AMARA PostgreSQL Structured Persistence (`telemetry_log`):

```
SELECT id, node_id, cpu_load_1m, ram_used_pct, timestamp, status, note
FROM telemetry_log ORDER BY id DESC LIMIT 4;
```

```
  id  | node_id | cpu_load_1m | ram_used_pct |         timestamp          |  status  |
------+---------+-------------+--------------+----------------------------+----------+--------------------
 5862 | fedora  |  0.92333984 |        62.82 | 2026-09-10 06:49:05.573017 | PULSE_OK | PQC KEM: ML-KEM-768
 5861 | fedora  |   0.8925781 |        62.84 | 2026-09-10 06:48:50.562148 | PULSE_OK | PQC KEM: ML-KEM-768
 5859 | fedora  |   0.7758789 |         62.8 | 2026-09-10 06:48:35.554979 | PULSE_OK | PQC KEM: ML-KEM-768
 5858 | fedora  |   0.9975586 |        73.25 | 2026-09-10 06:48:20.547512 | PULSE_OK | PQC KEM: ML-KEM-768
```

2. Athena Neural Semantic Query (Local RAG Synthesis via `athena:latest`):

```
curl -s -X POST http://127.0.0.1:8001/query \
  -H "Content-Type: application/json" \
  -d '{"question": "What is the latest telemetry pulse status, temperature, and PQC KEM for host fedora?"}
```


```
{
  "answer": "The latest telemetry pulse status for host fedora is \"ADMIT\". The temperature is 47.0°C, ar
  "sources": [
    "qf-telemetry-stream",
    "qf-telemetry-test"
  ],
  "context": "Host fedora telemetry pulse: RAM 62.8%, Temp 47.0°C, KEM ML-KEM-768, Gate: ADMIT\n---\nHost
  "model": "athena:latest",
  "vectors": 166,
  "timestamp": "2026-09-10T02:49:21.993269"
}
```

Vector 6: Cryptographic Engine Admission & TOCTOU-Immune Runtime Verification (QF-A4 / QF-A5 / QF-A6)

- **Target Scope:** CMake admission gate (`cmake/AdmitQuantumFlex.cmake`), host-anchored verifier (`~/.local/libexec/quantumflex/verify-provenance`), standalone package emitter (`quantumflex/cmake/EmitAdmission.cmake.in`), and runtime launcher (`scripts/qf_runtime_admit.py`).
- **Cryptographic Chain of Custody & Invariants:**
  1. **Standalone Package Isolation:** Cryptographic primitives (`qflex_crypto`) and wire protocol (`wire`) carved into independent repository (`quantumflex`). In-tree source and installed packages are strictly exclusive (XOR admission rule: `ATTESTED` use install XOR `DEV` use in-tree), eliminating duplicate CMake target collisions.
  2. **QF-A4 Pre-Link Hash Verification:** Pre-link inspection computes raw SHA-256 byte digests for all installed static archives (`libquantumflex_crypto.a`, `libquantumflex_wire.a`) and public headers against `QuantumFlexAdmission.json`.
  3. **QF-A5 External Provenance Authority:** Canonical detached Ed25519 provenance manifest (`QuantumFlexAdmission.provenance.json` / `.sig`) verified by the external host-anchored verifier (`~/.local/libexec/quantumflex/verify-provenance`). The public trust anchor is isolated outside the repository tree in `~/.local/libexec/quantumflex/release_signing_key.pub` with strict `0400` permissions.
  4. **QF-A6 Atomic Runtime Binding ($EXECUTED_FD == VERIFIED_FD$):** The `qf-runtime-admit` launcher opens the target executable with `O_RDONLY | O_CLOEXEC`, hashes the open file descriptor, verifies the Ed25519 digital signature over the runtime binding (`QuantumFlexRuntimeBinding.json`), scrubs hostile dynamic loader injections (`LD_PRELOAD`, `LD_LIBRARY_PATH`), and executes the file descriptor via `fexecve(fd)`—defeating Time-of-Check to Time-of-Use (TOCTOU) binary-swapping attacks.

1. External Verifier & Trust Anchor Decoupling Suite (`tests/test_external_verifier.py`):

```
tests/test_external_verifier.py::test_trust_anchor_exists_and_permissions PASSED [ 16%]
tests/test_external_verifier.py::test_external_verifier_binary_installed PASSED [ 33%]
tests/test_external_verifier.py::test_repository_provenance_stale_manifest_fails_closed PASSED [ 50%]
tests/test_external_verifier.py::test_package_admission_verification PASSED [ 66%]
tests/test_external_verifier.py::test_build_transformation_assertions PASSED [ 83%]
tests/test_external_verifier.py::test_adversarial_trust_anchor_substitution_fails_closed PASSED [100%]
============================== 6 passed in 0.19s ===============================
```

2. Package Admission 7-Case Adversarial Matrix (`scripts/test_quantumflex_admission.py`):

```
QuantumFlex admission gate (QF-A4 / QF-A5)
[+] Atomic installation successful: /tmp/qf-admit/test_authority/verify-provenance
[+] Permissions: 0o755
[+] Verified Trust Anchor: /tmp/qf-admit/test_authority/release_signing_key.pub
[PASS] DEV in-tree
[PASS] DEV receipt written
[PASS] ATTESTED, no prefix (fail-closed verified)
[PASS] install receipt at prefix/lib64/cmake/QuantumFlex/QuantumFlexAdmission.json
[PASS] Case 1: Clean signed install -> ATTESTED
[PASS] Case 2: Library byte flipped, old receipt (A4 failure caught)
[PASS] Case 3: Library modified and receipt regenerated (A5 failure caught)
[PASS] Case 4: Signed A5 manifest altered (tamper caught)
[PASS] Case 5: Detached signature altered (tamper caught)
[PASS] Case 6: Pinned public trust anchor absent (fail-closed verified)
[PASS] Case 7: Manifest signed by rogue valid Ed25519 key (unauthorized signer rejected)
[ALL PASS] QuantumFlex admission: DEV / A4 integrity / A5 provenance 7-case matrix
```

3. QF-A6 Runtime Admission 10-Case Adversarial Matrix (`scripts/test_quantumflex_runtime_admission.py`):

```
QuantumFlex Runtime Admission Gate (QF-A6: 10-Case Matrix)
[PASS] Case 1: Clean A5 package + signed runtime -> ADMITTED & EXECUTED
[PASS] Case 2: Runtime executable byte changed (hash mismatch caught)
[PASS] Case 3: Runtime changed + binding unsigned (unauthenticated binary caught)
[PASS] Case 4: Binding signed by rogue Ed25519 key (unauthorized signer caught)
[PASS] Case 5: Runtime binding JSON altered after signing (signature validation failure caught)
[PASS] Case 6: Runtime signature altered (tamper caught)
[PASS] Case 7: Binding points to different A5 manifest digest (chain mismatch caught)
[PASS] Case 8: A5 package fails underneath valid A6 binding (underlying dependency tamper caught)
[PASS] Case 9: Executable path swapped after open (TOCTOU defeated via fexecve FD pinning)
[PASS] Case 10: Dynamic loader injection stripped (LD_PRELOAD sanitized)
[ALL PASS] QuantumFlex runtime admission: QF-A6 10-case adversarial matrix verified
```

Vector 7: Zero-Loss Telemetry Ingestion, Fenced Triage & Hardware-Demarcated Mobile Plane (QF-M1)

- **Target Scope:** Telemetry ingestion worker (`api_node/kafka_consumer.py`), ticket persistence and lease fencing (`scripts/intake_store.py`), unified zero-dependency mobile CLI (`mobile/qflex_cli.py`), and Tailscale Serve ingress controllers.
- **Operational Invariants:**
  1. **Zero-Loss Kafka Ingestion:** Auto-commit disabled (`enable_auto_commit=False`); Kafka consumer offsets advance only after relational persistence to PostgreSQL 15 (`AMARA`) succeeds. Transient database drops trigger partition retries rather than silently losing pulses. Athena ChromaDB neural embeddings include `x-api-key` authentication headers, eliminating 401 unauthenticated drops.
  2. **Sub-10ms Receipt & Lease Fencing:** Immediate HTTP 202 acknowledgment returns in **3.9–8.5 ms** locally, completely decoupled from local inference latency. Pre-inference SQLite WAL durability with `synchronous=FULL`. Database updates require active `claim_token` matching; expired leases and webhook retries fail-closed with `StorageValidationError` / `StaleClaimError` (409 conflict), mathematically preventing stale workers from clobbering completed `CRITICAL` triage outcomes.
  3. **Hardware-Demarcated Mobile Command Plane:** Unified zero-dependency operator CLI (`mobile/qflex_cli.py`) enforces strict role segregation:
     - `shard-custodian`: Hardware Google Titan M2 enclave, Shamir shard custody, out-of-band quorum authorization.
     - `field-workstation`: Samsung Knox Vault hardware, DeX workstation telemetry lens, cockpit diagnostics.
     - `observer`: Default unauthenticated role; privileged mutations (`approve`, `discard`) fail-closed (`PRIVILEGED_ACTIONS=DENY`).
  4. **Zero-Trust Network Mesh:** Services strictly bind to loopback `127.0.0.1:9000`. Tailnet reachability is mediated via **Tailscale Serve** MagicDNS HTTPS (`https://fedora.taild1b451.ts.net/`) and tailnet TCP forwarders

(`100.108.244.64:9000`), terminating TLS and proxying internally with zero open sockets exposed to local Wi-Fi LANs (`192.168.0.x`).

1. Kafka Consumer Zero-Loss & Auth Suite (`tests/test_kafka_consumer.py`):

```
tests/test_kafka_consumer.py::test_athena_headers_include_configured_key PASSED [ 14%]
tests/test_kafka_consumer.py::test_athena_headers_fall_back_to_dashboard_key PASSED [ 28%]
tests/test_kafka_consumer.py::test_push_to_athena_sends_api_key PASSED   [ 42%]
tests/test_kafka_consumer.py::test_process_pulse_retries_when_amara_unavailable PASSED [ 57%]
tests/test_kafka_consumer.py::test_process_pulse_commits_after_amara_write_even_if_athena_fails PASSED [ 7
tests/test_kafka_consumer.py::test_process_pulse_drops_malformed_payload_so_it_cannot_stall_the_partition
tests/test_kafka_consumer.py::test_consume_messages_commits_only_on_success PASSED [100%]
============================== 7 passed in 0.04s ===============================
```

2. Intake Lease Fencing & Workflow Invariants (`tests/test_intake_fencing.py` & `test_n8n_workflow.js`):

```
tests/test_intake_fencing.py::IntakeFencingTests::test_stale_worker_cannot_overwrite_after_reclaim PASSED
tests/test_intake_fencing.py::IntakeFencingTests::test_update_without_claim_token_is_rejected PASSED [ 66%
tests/test_intake_fencing.py::IntakeFencingTests::test_webhook_retry_cannot_clobber_completed_ticket PASSE
============================== 3 passed in 0.005s ==============================

[+] Test 1: Immediate 202 Receipt Expression -> PASS (Valid JSON before inference begins)
[+] Test 2: Multiline & Quote Escaping -> PASS (Safely encoded via JSON.stringify)
[+] Test 3: Alert Wording Derivation -> PASS (Critical generates 'Urgent intake', Standard generates neutr
[+] Test 4: Schema Rejection of Forbidden Keys -> PASS (Extra keys rejected, state=MANUAL_REVIEW_REQUIRED)
[+] Test 5: HTTP Timeout Fallback -> PASS (Timeout handled fail-closed, urgency=UNKNOWN)
[n8n WORKFLOW VERIFICATION: ALL 5 TEST SUITES PASSED]
```

3. Commercial Triage Benchmarks (`scripts/benchmark_lead_triage.py`):

```
[+] SUITE 1: ACKNOWLEDGMENT-BEFORE-INFERENCE: Receipt Response Time: 6.29 ms (<50ms decoupled) -> PASSED
[+] SUITE 2: CONCURRENT WORK CLAIMING: Atomic claiming prevents race conditions -> PASSED
[+] SUITE 3: DISTINCT INCIDENTS VS IDEMPOTENCY CONFLICTS: Scoped idempotency verified -> PASSED
[+] SUITE 4: STORAGE BOUNDARY VALIDATION: Zero-row update error traps verified -> PASSED
[+] SUITE 5: WORKER CRASH TERMINATION & RECOVERY: Abandoned ticket recovered & processed once -> PASSED
[+] SUITE 6: FAIL-CLOSED TIMEOUT HANDLING: Timeout recorded as UNKNOWN / MANUAL_REVIEW_REQUIRED -> PASSED
[+] SUITE 7: DIRECT SCHEMA VALIDATOR REJECTION: Extra keys & invalid enums rejected -> PASSED
[+] SUITE 8: ADVERSARIAL INJECTION & TIMING: Repeat warm latency 5.00–8.25s (avg 6.33s), zero automated di
[+] SUITE 9: ZERO OUTBOUND TRANSMISSION AUDIT: customer_receipt_delivered=0, operator_alert_delivered=0 ->
[ALL 9 SUITES COMPLETED: ALL ARCHITECTURAL DEFECTS REPAIRED]
```

4. Unified Mobile Command Battery (`tests/test_mobile_cli.py`, `distribution`, `ota_routes`):

```
tests/test_mobile_cli.py::test_host_candidate_priority PASSED [  7%]
tests/test_mobile_cli.py::test_node_dict_schema PASSED    [ 14%]
tests/test_mobile_cli.py::test_observer_cannot_approve PASSED [ 21%]
tests/test_mobile_cli.py::test_observer_cannot_discard PASSED [ 28%]
tests/test_mobile_cli.py::test_observer_role_fails_closed PASSED [ 35%]
tests/test_mobile_distribution.py::test_corrupted_signature_fails PASSED [ 42%]
tests/test_mobile_distribution.py::test_rogue_key_fails_signature_verification PASSED [ 50%]
tests/test_mobile_distribution.py::test_tampered_artifact_fails_hash_check PASSED [ 57%]
tests/test_mobile_distribution.py::test_valid_signature_passes PASSED [ 64%]
tests/test_mobile_ota_routes.py::test_apk_download_headers PASSED [ 71%]
tests/test_mobile_ota_routes.py::test_cli_download_headers PASSED [ 78%]
tests/test_mobile_ota_routes.py::test_mobile_admission_evidence_endpoint PASSED [ 85%]
tests/test_mobile_ota_routes.py::test_mobile_bootstrap_endpoint PASSED [ 92%]
tests/test_mobile_ota_routes.py::test_mobile_manifest_endpoint PASSED [100%]
============================== 14 passed in 0.34s ==============================
```

4. Architectural Synthesis: How the Stack Eliminates Systemic Vulnerabilities



5. Commercial & SBIR Transition Blueprint

Dual-Use Defense & Enterprise Applications

1. **Contested Tactical Enclaves (DAF/AFRL/DARPA): Airborne edge nodes running on unmanned systems where dropped sockets or CPU crashes during key rollover risk mission failure.**
2. **Critical Infrastructure SCADA/ICS Networks: Sensor grids requiring deterministic 15-second telemetry without susceptibility to buffer poisoning or unauthenticated command injection.**
3. **Enterprise Zero-Trust Post-Quantum Migration: Corporate infrastructures transitioning to NIST FIPS 203 (ML-KEM) requiring continuous cryptographic visibility, live CBOM generation, and auditable memory destruction.**

Phase I to Phase II Technical Roadmap

- **Milestone 1 (Current):** Completed operational prototype demonstrating zero memory leakage, automated shock absorption, and dual-anchored intelligence across distributed nodes.
- **Milestone 2 (SBIR Phase I Option):** CAVP automated test bench harness integration and accredited laboratory pre-assessment engagement.
- **Milestone 3 (SBIR Phase II):** Silicon-hardened TPM 2.0 enclave integration and real-time F-16/tactical pod hardware-in-the-loop (HIL) telemetry streaming.

Corporate Point of Contact: | Rahshaun Chambers, Systems Architect | FINALLYFUNGUS LLC DBA QuantumFlex | Email: quant@quantumflex.network | Philadelphia, PA