```java
import java.util.*;
class book2
{
    String name, author;
    double price;
    int num_pages;
    Scanner sc = new Scanner(System.in);
    Book2()
    {
        name = " ";
        author = " ";
        price = 0;
        num_pages = 0;
    }
    void get_details(int a)
    {
        System.out.println(" ---------- ");
        System.out.println("Enter the name of the book"+a);
        name = sc.next();
        System.out.println("Enter the author of the book"+a);
        author = sc.next();
        System.out.println("Enter the price of the book"+a);
        price = sc.nextDouble();
        System.out.println("Enter the num_pages of book"+a);
        num_pages = sc.nextInt();
        System.out.println(" -------- ");
    }

    public String toString()
    {
        return("name of book:"+name+"\n author
        :"+author+"\n price"+price+"
        \n no of pages:"+num_pages+"\n
        ---- ");
```

```
            }
        }

Class Book2 main
{
        public static void main( String args ())
        {
            int n;
            Book2 O ();
            Scanner sc = new scanner (system.in);
            system. Out println (" Enter the number of book
                                  details to be entered ");
            n = sc. next Int ();
            0 = new Book2(n);
            for ( int i = 0 ; i<n; i++)
            {
                O (i) = new book 2();
                o(i).get details (i+1);
            }
            for ( int i=0 ; i<n; i++)
            {
                system. Out println (" details of book "+(i
                system. Out println("- - - - - - -");
                System. Out println ( 0 (i));
            }
        }
}
```