



5 MP IP DOME VARIFOCAL CAMERA

BW-I120-V5DW-SV

1/2.8" 5 Megapixel progressive Scan WDR Sensor

2,590x1,920

BLC/WDR (120DB)

POE

Mic Inbuilt, IP 67

	DESCRIPTION
Sensor type	1/28-inch CMOS
Total Sensor pixels	2590 (H) x 1920 (V)
Sensitivity	Color 0.5 lx, With IR 0,0 lx (Measured
	according to IEC 62676 Part 5)
WDR	120 dB WDR
True day/Night	Auto, Color, Monochrome
Functions	3DNR, Defog, deblur, watermark
Video resolution	1920P
Video compression	H.265 / H.264 / M-JPEG
Frame rate	30 fbs, 20fbs
IR Range	Minimum 30m
Lens type	Automatic Varifocal 2.8 to 12mm
Lens adjustment	Motorized zoom/focus
Ethemet	10/100 Base-T,auto-sensing,half/full duplex
Ethemet connector	PoE
Connectivity	ONVIF Profile S, ONVIF Profile G & ONVIF Profile
Memory card slot	Upto 256 GB support
	UPnP, Bonjour, SIP, PPPoE, VI.AN , 802.1x, QoS,
Protocols	IGMP, ICMP, SSI., RTCP, RTP, RTSP,RTMP, HTTP.
	HTTPS, DNS, IPv4/Ipv6, ARP, TCP. UDP, DDMS, DHCP,
	FTP, NTP SMTP, SNMP
Operating temperature	-30 °C to +60 °C
Humidity	0% to 90% non-condensing
Ingress protection	IP67
Impect protection	IK10





