D Series

Installation Series Professional Amplifier Class - D



The D Series amplifier is a multi-channel professional Class-D amplifier, meticulously engineered to deliver exceptional reliability and performance. Its high efficiency is achieved through a combination of automatic temperature control and unique limiting functions, ensuring the amplifier operates efficiently by minimizing power loss and heat generation. Designed for long-term use, the D Series amplifiers offer consistent performance and durability, making them a reliable choice for professional audio installations. The innovative features and robust design make them an excellent choice for various settings, ensuring exceptional sound quality and ease of use.



Key Features

- o Clip limiters
- o Over temperature protections
- o Short circuit protection
- o Light weight and Portable

Parameter Mo	del D4200	D4300
Power @8Ω per channel	200W×4	300W×4
Power $@4\Omega$ per channel	350W×4	500W×4
Bridge/8 Ω	650W×2	900W×2
Bridge/4 Ω	900Wx2 (Not recommended)	1150x2 (Not recommended)
Frequency Response	20HZ~20KHZ(0.5dB/-0.5dB)	
THD+N	<0.05%@8Ω 1KHz	
S/N Ratio	>98dB (A-weighted)	
Damping Factor	>500 (1 kHz @ 8 Ω)	
Crosstalk	>80dB	
Input Sensitivity	0.775V/1.44V	
Input Impedance (Bal/Unbal)	20ΚΩ/10ΚΩ	
Product Dimension (W x D x H) mm	482 × 330 × 88	
Net Weight (Kg)	4.8	5

Safety Instructions

- Do not use this product near water.
- o Clean only with a dry cloth.
- o Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers)that produce heat.
- Do not block any ventilation openings. Install following the manufacturer's instructions.
- Protect the power cord from being walked on or pinched, particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.
- $\circ\quad$ Unplug the unit during lightning storms or when unused for long periods.
- Refer all servicing to qualified service personnel. Servicing is required periodically and when the unit is damaged, either mechanically or electrically, or is used in the smoky/dusty environment.