

S-SERIES

PROFESSIONAL SUBWOOFER



S-218, Dual 18" Passive Subwoofer



Key Features

- Portable & Fixed Installations
- 2000W True RMS Power
- Front Loaded design
- 18" high excursion driver 4.5" voice coil
- Birch Plywood Construction
- Applications: Night Clubs, Auditorium, Sport Complex, Multi-functional Hall etc.

The S-218 has dual 18" driver with 4.5" voice coil and high-performance, front-loaded passive subwoofer engineered for exceptional sound quality and reliability. Powered by a premium European driver, it delivers deep, impactful low-frequency reproduction with precision and consistency.

Crafted from multi-layer, birch plywood, the enclosure offers outstanding rigidity and acoustical integrity, ensuring durability and long-term performance. Designed to meet the rigorous demands of both installation and rental markets, the S-218 stands as a robust and dependable solution for audio professionals seeking uncompromising performance.


S-SERIES

PROFESSIONAL SUBWOOFER




Technical Specifications

Type	Passive Subwoofer
Frequency Response (-10 dB)	35 Hz – 120 Hz
Drivers	2 x 18" High performance driver 4.5" voice coil
Power (RMS / Program / Peak)	2000W / 4000W / 8000W
Sensitivity (1W/1m)	99 dB
Max SPL (Continuous/1m)	136 dB
Max SPL (Peak/1m)	139 dB
Nominal Impedance	4 ohms
Dispersion	Omnidirectional
Cabinet Material	Birch Plywood with Polyurea Paint
Size (mm)	580 x 1160 x890mm (H x W x D)
Weight (Kg)/Lbs	78/171.9



Front View



Rear View



Side View



Top View

S-SERIES

PROFESSIONAL SUBWOOFER



Safety Instructions

- When flying speakers, appropriate hardware and techniques must be employed for safely suspending the enclosures.
- All speaker hardware and flying apparatus must be regularly inspected for any visual or mechanical failure.
- Leave adequate distance between speakers and the audience. Refer to your local authority for Health and Safety guidance when using loudspeaker systems.
- The Louis Martin digital controller should only be programmed by an authorized technician. Do not use Louis loudspeaker systems without the correct controller and the program. If a system fails due to incorrect controller use, warranty is void.
- Protect your speakers and electronics from exposure to humidity, water or rain.
- The loudspeakers and electronics are covered against defects in workmanship or materials for a period of two years from the original date of purchase. The warranty does not cover any item which in Louis's opinion has failed due to user abuse, accident, modifications.
- The defective item will be repaired/replaced with no charge for materials or labour. However, the item should be adequately packed and dispatched, pre-paid, to a Louis authorized distributor/service