# **F** Series



### F - 15

#### **General Information**

The F-15 has one powerful 15" (381 mm) LF driver with 1.75" (44 mm) HF. It is a high-performance, versatile, passive speaker system designed for unmatched sound reinforcement. Featuring a passive crossover, two-way full-range configuration, it is ideal for install & portable use including Main FoH, Night Clubs, lounges, Multipurpose Hall, Live Setup etc. With flat frequency response, the cabinet offers uncoloured, transparent sound quality. Crafted from high density plywood, it is suitable for both installation and portable use. The cabinet's design emphasizes vocal clarity, fidelity, and minimal distortion without compromising transient response.



### **System Applications**

- o Lounge
- o Pub/Bar
- o Main FoH
- o Multi-functional Room
- o Live portable setup
- o Night Clubs

#### **Features**

- o Unique wooden design
- o 15" LF driver with 1.75" HF driver
- o Easy mounting options available
- o 90°(H) x 50 °(V) Horn design

# **F** Series



Technical Specifications	
Туре	Two-way full range passive loudspeaker
Frequency Response (-10 dB)	50 Hz – 19 kHz
LF Drivers	1x 15" (381 mm) LF Driver with 3" Voice coil
HF Drivers	1 x 1.75" (44 mm) HF Driver
RMS Power	500W
Program Power	1000W
Peak Power	2000W
Sensitivity (1W/1m)	99 dB
Max SPL (Continuous/1m)	129 dB
Max SPL (Peak/1m)	132 dB
Nominal Impedance	8 Ohms
Crossover Mode	Passive
Dispersion	90° (H) x 50° (V)
Cabinet Material	High density plywood
Size (mm)	690 x 470 x 443mm (H x W x D)
Weight (Kg)/Lbs	30/66.1

#### Safety Instructions

- o When flying speakers, appropriate hardware and techniques must be employed for safely suspending the enclosures
- o All speaker hardware and flying apparatus must be regularly inspected for any visual or mechanical failure.
- o Leave adequate distance between speakers and the audience. Refer to your local authority for Health and Safety guidance when using loudspeaker systems.
- o The Louis Martin digital controller should only be programmed by an authorized technician. Do not use Louis loudspeaker systems without the correct controller and the program. If a system fails due to incorrect controller use, warranty is void.
- o Protect your speakers and electronics from exposure to humidity, water or rain.
- The loudspeakers and electronics are covered against defects in workmanship or materials for a period of two years from the original date of purchase. The warranty does not cover any item which in Louis's opinion has failed due to user abuse, accident, modifications.
- o The defective item will be repaired/replaced with no charge for materials or labour. However, the item should be adequately packed and dispatched, pre-paid, to a Louis authorized distributor/service