



IIT Madras BSc Degree

Copyright and terms of use

IIT Madras is the sole owner of the content available in this portal - onlinedegree.iitm.ac.in and the content is copyrighted to IIT Madras.

- Learners may download copyrighted material for their use for the purpose of the online program only.
- Except as otherwise expressly permitted under copyright law, no use other than for the purpose of the online program is permitted.
- No copying, redistribution, retransmission, publication or exploitation, commercial or otherwise of material will be permitted without the express permission of IIT Madras.
- Learner acknowledges that he/she does not acquire any ownership rights by downloading copyrighted material.
- Learners may not modify, publish, transmit, participate in the transfer or sale, create derivative works, or in any way exploit, any of the content, in whole or in part.

Testing

Application Testing

- Why?
- What?
- When?
- How?
- Pytest

Why?

Does *something* work *as intended*

- Requirements - specifications
- Respond correctly to inputs
- Respond within reasonable time
- Installation and environment
- Usability and Correctness

Static vs. Dynamic

Static Testing:

- Code review, correctness proofs

Dynamic Testing:

- Functional tests
- Apply suitable inputs

White-box testing

- Detailed knowledge of implementation
- Can examine internal variables, counters
- Tests can be created based on knowledge of internal structure
- Pro:
 - More detailed information available, better tests
- Con:
 - Can lead to focusing on less important parts because code is known
 - Does not encourage clean abstraction
 - Too much information?

Black-box testing

- Only interfaces are available, not the actual code
- Tests based on how it would look from outside
- Pro:
 - Closer to real usage scenario
 - Encourages (enforces) clean abstraction of interface
- Con:
 - May miss corner cases that would have been obvious if internal structure was known
 - Debugging is harder - even if it failed, why did it fail?

Grey-box testing

- Hybrid approach between white-box and black-box
- Enforce interface as far as possible
- Internal structure mainly used for debugging, examining variables etc.

Regressions

- Maintain series of tests starting from basic development of code
 - Each test is for some specific feature or set of features
- **Regression:** loss of functionality introduced by some change in the code
- Future modifications to code should not break existing code
- Sometimes necessary
 - Update tests
 - Update API versions etc.

Coverage

- How much of the code is covered
 - Every line is executed at least once - 100% code coverage
 - Does not guarantee “correctness” in all conditions
 - There may be more complex paths or other conditions that can cause failure
- Branch coverage, condition coverage, function coverage ...

Example

```
int foo (int x, int y)
{
    int z = 0;
    if ((x > 0) && (y > 0))
    {
        z = x;
    }
    return z;
}
```

Src: Wikipedia

Example

```
int foo (int x, int y)
{
    int z = 0;
    if ((x > 0) && (y > 0))
    {
        z = x;
    }
    return z;
}
```

Src: Wikipedia

Function coverage

- Test invokes foo() at least once

Example

```
int foo (int x, int y)
{
    int z = 0;
    if ((x > 0) && (y > 0))
    {
        z = x;
    }
    return z;
}
```

Src: Wikipedia

Statement coverage

- Example: foo(1,1)
 - All statements in code will be executed

Example

```
int foo (int x, int y)
{
    int z = 0;
    if ((x > 0) && (y > 0))
    {
        z = x;
    }
    return z;
}
```

Src: Wikipedia

Branch coverage

- At least two tests needed:
- foo(1,1)
 - Branch taken
- foo(1,0)
 - Branch not taken

Example

```
int foo (int x, int y)
{
    int z = 0;
    if ((x > 0) && (y > 0))
    {
        z = x;
    }
    return z;
}
```

Src: Wikipedia

Condition coverage

- At least two tests needed:
- foo(0,1)
 - First condition fails, second succeeds
- foo(1,0)
 - First condition succeeds, second fails
- Note: does not guarantee branch coverage

Summary

- Requirements specified by user
- Creating suitable tests can itself be challenging
- How much knowledge of the code internals should the tester have?
- Separation of concerns:
 - ideally tester should be able to generate test cases based only on spec and without knowing code
- Code coverage useful metric
 - Does not guarantee all scenarios actually tested!

Levels of Testing

Example: Onlinedegree dashboard

Initial requirements gathering

- Who are the stakeholders?
 - Students - log in and see courses
 - Admins - manage students
 - Teachers - update / manage course material ?
- Functionality
 - Each group has different needs
- Non-functional requirements
 - Page colour, font, logo



MY DASHBOARD

- Latest Updates
- Exam Cities and Hall Tickets
- My Current Courses
- **Completed & Pending Courses**
- Academic Calendar
- Documents for Download
- Submitted Documents

Reporting harassment: IITM BSc Degree
Team is committed to ensuring that
everyone is equally valued.... [Read
More](#)

Foundational Level Courses

COMPLETED COURSES

OTHER COURSES

Example: Student page

Functional

- Latest updates
- Register exam hall preferences
- Download hall ticket
- Update course registration
- View completed courses
- ...

Example: Student page

Functional

- Latest updates
- Register exam hall preferences
- Download hall ticket
- Update course registration
- View completed courses
- ...

Non-functional

- Header / Footer colours
- Copyright notice and extra information
- Logo
- Fonts
- ...

Requirements gathering

- Extensive discussions with end-users required
- Avoid language ambiguity
- Capture use cases and *examples*
- Start thinking about test cases and how the requirements will be validated

Units of Implementation

- Break functional requirements down to small, implementable *units*
- Examples:
 - view course list
 - edit course status
 - edit exam preferences
 - download completion certificate
- Each one may become a single controller
 - May also combine multiple into a single controller

Unit Testing

- Test each individual unit of implementation
- May be single controllers
 - May even be part of a controller
- Clearly define inputs and expected outputs
- Testable in isolation?
 - Can each unit be tested without the entire system?
 - Create artificial data set to check whether a single update works

Example: Unit tests

Student registers for a course

- Create dummy DB:
 - One student
 - One course
- Test
 - Controller to add course for student
 - Form to be displayed
 - Invalid student ID, course ID - error codes?
 - Add student more than once?

Integration

- Application consists of multiple modules:
 - Student management
 - Course management
 - Payment interfaces
 - Admin interface

Integration Testing

- Example of integration:
 - Student + Payment gateway
 - Student + Course + Admin
 - All of the above . . .
- Potential problems:
 - Individual units work - combined system does not
 - Dependencies violations in server - redesign?
- Continuous integration
 - Combined with version control systems: CI
 - Each commit to main branch triggers a re-evaluation of integration tests
 - Multiple times a day possible

System-level Testing

- One step beyond integration
- Includes server, environment
- Mainly black-box: should validate final usage

Example: onlinedegree

- Deploy on final environment: Google app-engine
- Test domains used
- Confirm all aspects of behaviour
- Non-functional tests:
 - Performance under load
 - Number of instances, scaling
 - Cost!

System testing Automation

- Has to simulate actual user interaction
- Browser automation frameworks
 - Selenium (example)
- Includes database, persistent connections etc.
- Typically a complete secondary system

User Acceptance Testing

- Deploy final system
- Tested by restricted set of users - pilot
- “Beta” testing
 - Beta- software: pre-production

Test generation

API-based testing

- Application Programming Interface: abstraction for system design
- Standard representations for APIs
 - OpenAPI, Swagger etc.
- Can they also generate test cases?



SMARTBEAR

Swagger InspectorSM

DEFINITION ▼

GET ▼

https://swapi.co/api/people

^ Request

Parameters

Authentication & Headers

Body

CLEAR REQUEST

query parameter

value

ADD NEW PARAMETER

^ Response

Status: Error Time: 550 ms

SHOW HEADERS ☐DARK THEME ☒

The request has been terminated.

Use cases

- Import API definition from standard like OpenAPI
- Generate tests for specific endpoints, scenarios
- Record API traffic
- Inject possible problem cases based on known techniques
- Data validation tests

Abstract Tests

- Semi-formal verbal description:
 - Make a request to '/' endpoint
 - Ensure that result contains text "Hello world"

Abstract Tests

- Semi-formal verbal description:
 - Make a request to ‘/’ endpoint
 - Ensure that result contains text “Hello world”

```
def test_hello(client):  
    """Verify home page."""  
  
    rv = client.get('/')  
    assert b'Hello world' in rv.data
```

Model-based testing

Example: Authenticate user before showing information

- Scenarios:
 - User already logged in - page shown
 - User not yet logged in - redirect to login page
 - Forgot password - after resetting, come back to desired page
- Model:
 - Possible states (logged in, password reset, ...)
 - Possible transitions
 - Generate tests for the possible transitions

Models and Abstract Tests

- Abstract tests apply to generic models
- Create model for system-under-test
- Derive “executable” tests by combining abstract test information with model

(G)UI testing

- User interface: visual output
- Usually GUI - even for web-based systems
 - But specific details of graphical display may be different in web-based systems
- Tests:
 - Are specific elements present on page
 - Are navigation links present
 - What happens on random click on some part of the page

Browser automation

- Some tests cannot be directly run programmatically
 - Browser is **required**, just requests not sufficient
- Example:
 - IRCTC or SBI website - captcha protected
 - Some user input also required - cannot be completely automated
- Request generation:
 - Python requests library
 - Capybara (ruby), ...
- Direct browser automation:
 - Selenium framework - actually instantiate a browser

Security testing

- Generate invalid inputs to test app behaviour
- Try to crash server - overload, injection etc.
- Black-box or White-box approaches
- **Fuzzing** or Fuzz-testing:
 - Generate large number of random/semi-random inputs

pytest

What?

- Framework to make testing easier in Python
- Opinionated:
 - Provides several defaults to make it easier to write tests
- Helpful features:
 - Can automatically set up environment, tear down after test etc.
 - Test fixtures, monkeypatching etc.

Note: python standard library includes `unittest` - `pytest` is an alternative with some more features

Example

```
# content of test_sample.py
```

```
def func(x):  
    return x + 1
```

```
def test_answer():  
    assert func(3) == 5
```

Example

```
# content of test_sample.py
def func(x):
    return x + 1

def test_answer():
    assert func(3) == 5
```

```
$ pytest
===== test session starts =====
platform linux -- Python 3.x.y, pytest-6.x.y, py-1.x.y,
pluggy-1.x.y
cachedir: $PYTHON_PREFIX/.pytest_cache
rootdir: $REGENDOC_TMPDIR
collected 1 item

test sample.py F
[100%]

===== FAILURES =====
_____ test_answer _____

    def test_answer():
>         assert func(3) == 5
E         assert 4 == 5
E         + where 4 = func(3)

test sample.py:6: AssertionError
===== short test summary info =====
FAILED test sample.py::test_answer - assert 4 == 5
===== 1 failed in 0.12s =====
```

Test for exceptions

content of test_sysexit.py

```
import pytest
```

```
def f():  
    raise SystemExit(1)
```

```
def test_mytest():  
    with pytest.raises(SystemExit):  
        f()
```

Temporary directory etc.

```
# content of test_tmpdir.py  
def test_needsfiles(tmpdir):  
    print(tmpdir)  
    assert 0
```


Temporary directory etc.

```
# content of test_tmpdir.py
def test_needsfiles(tmpdir):
    print(tmpdir)
    assert 0
```

```
$ pytest -q test_tmpdir.py
```

```
F [100%]
===== FAILURES =====
_____ test_needsfiles _____

tmpdir = local('PYTEST_TMPDIR/test_needsfiles0')

    def test_needsfiles(tmpdir):
        print(tmpdir)
>         assert 0
E         assert 0

test_tmpdir.py:3: AssertionError
----- Captured stdout call -----
PYTEST_TMPDIR/test_needsfiles0
===== short test summary info =====
FAILED test_tmpdir.py::test_needsfiles - assert 0
1 failed in 0.12s
```

Test Fixtures

- Set up some data before test
- Remove after test
- Examples:
 - initialize dummy database
 - Create dummy users, files

Example: test fixture

```
import pytest

@pytest.fixture
def setup_list():
    return ["apple", "banana"]

def test_apple(setup_list):
    assert "apple" in setup_list

def test_banana(setup_list):
    assert "banana" in setup_list

def test_mango(setup_list):
    assert "mango" in setup_list
```

Result: test fixture

```
test_fruit.py ..F [100%]
```

```
===== FAILURES =====  
_____ test_mango _____
```

```
setup_list = ['apple', 'banana']
```

```
    def test_mango(setup_list):  
>         assert "mango" in setup_list  
E         AssertionError: assert 'mango' in ['apple', 'banana']
```

```
test_fruit.py:14: AssertionError
```

```
===== short test summary info =====
```

```
FAILED test_fruit.py::test_mango - AssertionError: assert 'mango' in  
['apple', 'banana']
```

```
===== 1 failed, 2 passed in 0.01s =====
```

Conventions

- Test discovery starts from current dir or **testpaths** variable
 - Recurse into subdirectories unless specified not to
- Search for files name `test_*.py` or `*_test.py`
- From those files:
 - `test` prefixed test functions or methods outside of class
 - `test` prefixed test functions or methods inside `Test` prefixed test classes (without an `__init__` method)
- Also supports standard python `unittest`

Testing Flask applications

- Create a `client` fixture - known to Flask
- Set up dummy database, temp dir etc. in fixture
- Use `requests` library to generate queries

Fixture setup

```
import os
import tempfile

import pytest

from flaskr import create_app
from flaskr.db import init_db


@pytest.fixture
def client():
    db_fd, db_path = tempfile.mkstemp()
    app = create_app({'TESTING': True, 'DATABASE': db_path})

    with app.test_client() as client:
        with app.app_context():
            init_db()
        yield client

    os.close(db_fd)
    os.unlink(db_path)
```

Test example

```
def test_empty_db(client):  
    """Start with a blank database."""  
  
    rv = client.get('/')  
    assert b'No entries here so far' in rv.data
```


Testing login and other features

```
def login(client, username, password):  
    return client.post('/login', data=dict(  
        username=username,  
        password=password  
    ), follow_redirects=True)  
  
def logout(client):  
    return client.get('/logout', follow_redirects=True)
```

```
def test_login_logout(client):  
    """Make sure login and logout works."""  
  
    username = flaskr.app.config["USERNAME"]  
    password = flaskr.app.config["PASSWORD"]  
  
    rv = login(client, username, password)  
    assert b'You were logged in' in rv.data  
  
    rv = logout(client)  
    assert b'You were logged out' in rv.data  
  
    rv = login(client, f'{username}x', password)  
    assert b'Invalid username' in rv.data  
  
    rv = login(client, username, f'{password}x')  
    assert b'Invalid password' in rv.data
```

Evaluation

```
import pytest
import os.path

class TestWeek1PublicCases:
    # Test case to check if the contact.html file exists
    def test_public_case1(self, student_assignment_folder):
        file_path = student_assignment_folder + "contact.html"
        assert os.path.isfile(file_path) == True

    # Test case to check if the resume.html file exists
    def test_public_case5(self, student_assignment_folder):
        file_path = student_assignment_folder + "resume.html"
        assert os.path.isfile(file_path) == True
```

Summary

- Automated testing is essential to get confidence in design
- Regression testing:
 - ensure previously passed tests do not start failing
- Test generation process:
 - mix of manual and automated

Continuous testing essential for overall system stability