

IIT Madras BSc Degree

Copyright and terms of use


IIT Madras is the sole owner of the content available in this portal - onlinedegree.iitm.ac.in and the content is copyrighted to IIT Madras.

- Learners may download copyrighted material for their use for the purpose of the online program only.
- Except as otherwise expressly permitted under copyright law, no use other than for the purpose of the online program is permitted.
- No copying, redistribution, retransmission, publication or exploitation, commercial or otherwise of material will be permitted without the express permission of IIT Madras.
- Learner acknowledges that he/she does not acquire any ownership rights by downloading copyrighted material.
- Learners may not modify, publish, transmit, participate in the transfer or sale, create derivative works, or in any way exploit, any of the content, in whole or in part.



More about messaging

Inter-service messaging

Message Queues - Recap



Message Queues - Recap




Message Queues

- Multiple services
 - Closely coupled
 - Running on same or closely related servers
 - Example: frontend, email, database, image processing
- Asynchronous message delivery
- Guarantees of delivery
- Ordered transactions

Internet-distributed Services?

- No common message broker
- Servers expose services for public use
- May not need delivery or order guarantees
- Lightweight messaging



Lightweight API calls

- Server exposes certain endpoints
- Meant for others to PUSH messages, not retrieve data
- Request usually through POST, maybe GET
- Data payload may be trivial or even non-existent

Why? - to receive messages from others

Examples

- Every time there is a commit pushed to github, send a message on Google chat room
 - github allows you to register a URL
 - you create a server to receive the request and then push to GChat
- Use Twilio to send several messages
 - Twilio calls you back when done with messages
 - You don't have to keep checking status from Twilio

Webhooks

- Use the existing web infrastructure to send messages
- Server to server communication
 - Usually... can also be direct client invoking hook on server
- Simpler than message queues

Webhooks

What is a webhook?

A way for an “app” to provide other “apps” with real-time information ^[1]

- Also called a **web callback** or **HTTP Push API**
- Regular HTTP request
 - Uses standard HTTP protocol
 - Usually either POST or GET
- Sometimes called reverse API
 - Similar specifications to regular APIs
 - Usually only to push information, not retrieve data
- Synchronous!
 - No store, retry etc - may trigger other behaviour, but webhook response must be immediate

[1] <https://sendgrid.com/blog/whats-webhook/>

Example webhook: gitlab

- Setting up a receiver
 - <https://requestbin.com/r/enhd2m5q5rmi8>
 - <https://replit.com/@nchandra/webhooktest#main.py>
- Setting up the caller
 - <https://gitlab.com/chandrachoodan/webhooktest/-/hooks>

Message contents

- Entirely application dependent
- Keep to minimum
 - Not meant for transfer of large amounts of data
 - Only as a message
- Request body

Message response

- Webhooks are “machine called”
 - Invoked by another server, not a human client
- Response should just indicate status
 - 200 for success, 4xx for failures
 - Minimal data returned - mostly will be discarded

Webhooks vs...

- Websockets

- Real-time 2-way communication vs One way
- Keep connection open
- Custom protocol vs standard HTTP

- Pub/Sub

- Message queue - but public: Google cloud, Apache Kafka, etc.
- Asynchronous
- More oriented to message delivery and processing - may be overkill

- Polling

- Periodic requests to check status
- PULL, not PUSH
- Server can be overloaded when client numbers increase

- APIs

- Collection of endpoints
- Any client can send request to API
- Usually used for retrieving data
- Webhook uses a form of API more suited for pushing messages

How to... ?

- Consume webhook
 - Create URL endpoint, register with provider (eg. gitlab, twilio, ...)
- Debugging
 - requestbin: dummy endpoint to receive data and see content
 - curl or postman: API debugging tools
 - ngrok: public URL endpoint for private code without needing public IP
- Securing webhook
 - Restrict at IP access level? Difficult for public facing
 - Use API key/access token/header: eg. X-Gitlab-Token header

Push to Client

Message targets

- Server to server push
 - Server A requests some messages to be sent
 - Server B calls back webhook after sending all messages
- What about asynchronous push to client?
 - Status updates?
 - Push notifications?

Client-side updates

- Requires persistent connection to/from client
- Pull vs Push
 - Client can pull updates
 - Server can push updates
- Original HTTP spec provided no support for this
 - Connection is stateless
 - Client-side pull easy - always possible with page refresh

Polling

- Client repeatedly sends requests
- Fixed Interval
 - easy to implement at client
 - Server may not have any updates! Unnecessary work
 - Can overwhelm server if too many clients
- Variable interval: long poll
 - Server blocks until it has something to update
 - Keep connection open - data sent only when needed
 - Occupies server resources
- <https://replit.com/@nchandra/simplechat#main.py>
- <https://javascript.info/long-polling#demo-a-chat>

Server-sent Events

- Mechanism for server to “push” events
- Requires WebWorker (service worker) on client
- Service worker can continue running in background
- Receive update, push to page

Needs more work on server side, but true push possible

Push notifications

- JS Push API
 - https://developer.mozilla.org/en-US/docs/Web/API/Push_API
- Web Push Protocol
 - <https://datatracker.ietf.org/doc/html/draft-ietf-webpush-protocol>
- Message urgency, priority possible
- Service worker on client receives and updates

Public push notification providers

- Alternatives
 - Firebase Cloud Messaging (previously Google Cloud Messaging)
 - Apple Push
- Authenticated and registered with app
- Web apps vs native apps
 - Web tech (HTTP) vs custom connections (TCP)

Summary: push messaging important part of user experience